

Ultrasonic cleaning devices Elmasonic Select

Incl. plastic pushdown lid



Application:

The ultrasonic cleaning devices in the Elmasonic Select model series with heating system are designed as single-frequency devices. They are used primarily in the metalworking industry for gentle but intensive cleaning of parts made from a wide variety of materials, such as steel, light metal, non-ferrous base metal, plastic and glass. The temperature-controlled heating system helps dissolve dirt thereby improving cleaning times and cleaning results. Ideal for removing grease, oils, chips, flux, paint and adhesive residues, oxide layers such as rust or verdigris, soot, scale, carbonisation and soldering residues, dust etc.



Execution:

- Includes plastic pushdown lid
- Splashproof housing with front-mounted digital control unit
- Cleaning tub, deep-drawn made from special, highly cavitation-proof stainless steel
- Auto-start function for starting cleaning when a preselected temperature is reached
- Electronic temperature control adjustable from 25 to 80°C in increments of 5°C
- Setup menu for customising the device functions
- Cleaning time preselection: Adjustable cleaning time between 1 minute and 6 hours
- Setup menu for customising the device functions
- Dry-running safety device
- Side drain and stopcock on the back of the device (Elmasonic Select 60-300)

Advantage:

- Memory for four customisable cleaning programs
- Convenient functions such as adjustable temperature limit, auto-degas and auto-start mode
- Five ultrasonic cleaning modes: degas, eco, sweep, pulse and dynamic for perfect cleaning results
- Very easy to use thanks to the clear, easy-to-read display and easily understandable function keys
- Audible and visual feedback on the operating status

Art. no.	43693 070
Brand	ELMA
Manufacturer Part Number	1106993-C
Model	Elmasonic Select 150
Suitable inner basket dimensions	455 x 250 x 45 mm
Max. tray contents	8.7 l
Tray width (inner)	485 mm
Tray depth (inner)	280 mm
Tray height (inner)	95 mm
Effective ultrasonic capacity	300 W
Max. ultrasound peak capacity	1200 W
Heating power	800 W
Max. power drain	1100 W
Single frequency	37 kHz
Min./max. nominal voltage	220 / 240 V
Outlet connection	12 mm
Gross Weight	8.800 kg
Product Group	486