

3M[™] Virtua[™] Series Safety Glasses

Technical datasheet

Product description

The 3M™ Virtua™ series safety spectacle is comprised of a rimless lens and fixed-length temple arm. An integrated side-shield offers maximum protection. Two product sizes are available: Virtua™ and Virtua™ Slim. The range includes clear, grey, amber and blue mirror lens options.

Key features

- Design provides excellent coverage and good field of vision
- Optical Class 1 to allow prolonged comfortable wear
- ▶ Offers excellent protection against UV radiation
- Virtua™ Slim provides a better fit for those with smaller facial features
- Lens coatings provide scratch resistance
- ► Total weight 25g

Product range

| Product ID | Description | Lens colour | Frame colour |
|--------------------|---|----------------|--------------|
| Virtua Clear | 3M™ Virtua™ Safety Glasses with clear PC lens | Clear PC | Clear |
| Virtua Grey | 3M [™] Virtua [™] Safety Glasses with grey PC lens | Grey PC | Grey |
| Virtua Amber | 3M [™] Virtua [™] Safety Glasses with amber PC lens | Amber PC | Amber |
| Virtua Blue Mirror | 3M [™] Virtua [™] Safety Glasses with blue mirror PC lens | Blue Mirror PC | Grey |
| Virtua Slim | 3M™ Virtua™ Slim Safety Glasses with clear PC lens | Clear PC | Clear |

Typical applications

These products can be used in a wide range of applications including:

- Construction
- Engineering
- General assembly
- ► Inspection work
- Light duty maintenance and repair

Intended use

These products are intended for protection against high speed particles at low energy (F) at extreme temperature conditions, -5°C and +55°C, (T) in accordance with EN 166:2001.

These products also help protect against UV radiation in accordance with EN 170:2002 (clear and amber lenses), and sun glare in accordance with EN 172:1994 (grey and blue mirror).

A number of lens options are available for a variety of different applications:

- Clear Good colour recognition and excellent UV protection
- Grey and Blue mirror Good for protection from sun glare.
- Amber Enhanced contrast in low light condition e.g. surface inspection

Use limitation

- Never modify or alter this product
- Do not use this product against hazards other than those specified in this document
- These products are not suitable for grinding or welding
- These products are NOT designed to be worn over prescription spectacles
- In accordance with EN 166:2001 safety spectacles cannot be tested and approved for use against liquid droplets. Where liquid protection is specified a suitable product should be considered, for example safety goggles

Standards and approval

These products are type examined by BSI Group, Notified Body number 2797.

These products are CE marked to the requirements of European Regulation (EU) 2016/425.

The applicable legislation can be determined by reviewing the Certificate and Declaration of Conformity at www.3M.com/Eye/certs

Materials listing

| Description | Material |
|-------------|-------------------|
| Lens | Polycarbonate |
| Temples | Polycarbonate |
| Screws | Zinc plated steel |

Marking

The products have demonstrated compliance with the requirements of EN 166:2001 and associated standards and bear the following marks:

| Product ref | Lens marking | Frame marking |
|--------------------|----------------|----------------|
| Virtua Clear | 2C-1.2 3M 1 FT | 3M EN 166 FT |
| Virtua Grey | 5-2.5 3M 1 FT | 3M EN 166 FT |
| Virtua Amber | 2C-1.2 3M 1 FT | 3M EN 166 FT |
| Virtua Blue Mirror | 5-2.5 3M 1 FT | 3M EN 166 FT |
| Virtua Slim | 2C-1.2 3M 1 FT | 3M EN 166 FT H |

Explanation of marking

| Marking | Description |
|-----------------------------------|--|
| 2C-1.2 (EN 170:2002) | UV protection. This product conforms to the requirements of the standard, providing UV protection for the complete specified range (210nm – 365nm). Products marked C provide good colour recognition. |
| 5-2.5 (EN 172:1994 as amended) | Sun-glare protection conforming to the requirements of the standard, providing UV protection for the complete specified range (280nm – 350nm). |
| 1 | Optical class |
| F | Impact protection against high speed particle at low energy (45m/s) |
| Т | Tested for impact protection at extreme temperature conditions -5°C and +55°C |
| Н | Frame designed to fit a small head |

IMPORTANT NOTICE

The use of the 3M product described within this document assumes that the user has previous experience of this type of product and that it will be used by a competent professional. Before any use of this product it is recommended to complete some trials to validate the performance of the product within its expected application.

All information and specification details contained within this document are inherent to this specific 3M product and would not be applied to other products or environment. Any action or usage of this product made in violation of this document is at the risk of the user.

Compliance to the information and specification relative to the 3M product contained within this document does not exempt the user from compliance with additional guidelines (safety rules, procedures). Compliance to operational requirements especially in respect to the environment and usage of tools with this product must be observed. The 3M group (which cannot verify or control those elements) would not be held responsible for the consequences of any violation of these rules which remain external to its decision and control.

Warranty conditions for 3M products are determined with the sales contract documents and with the mandatory and applicable clause, excluding any other warranty or compensation.

For more information on 3M products and services please contact 3M.



3M United Kingdom PLC 3M Centre, Cain Road Bracknell, Berkshire RG12 8HT Tel.: 0870 60 800 60 www.3M.eu/Safety 3M Ireland Limited The Iveagh Building The Park, Carrickmines Dublin 18 t: 1800 320 500

