3.81mm Pluggable Right Angle Header

multicomp PRO

RoHS

Compliant





Specifications

Current Rating Min. Insulation Withstand Voltage Insulation Resistance Operating Temperature : 12 Amperes, 300V AC : 2,000V AC : >2,000MΩ 500V DC : -40°C to +105°C

> 9.2 ±0.3 (0.362)

Diagram





Dimensions : Millimetres (Inches)

Specification Table

No.	Material		Plating / Finish	Remark
1	Insulating Body	Polyamide 66	-	Green
2	Solder Pin	Brass	Tin Plated	-

Dimensions Table

Pitch : 3.81mm (0.15 inch)				
Poles	A (mm)	A (Inch)		
2	8.23	0.324		
3	12.04	0.474		
4	15.85	0.624		
5	19.66	0.774		
6	23.47	0.924		
8	31.09	1.224		
10	38.71	1.524		
12	46.33	1.824		

Part Number Table

Description	Part Number
Header 3.81mm Right Angle 12A 02 Way	MC000128
Header 3.81mm Right Angle 12A 03 Way	MC000129
Header 3.81mm Right Angle 12A 04 Way	MC000130
Header 3.81mm Right Angle 12A 05 Way	MC000131
Header 3.81mm Right Angle 12A 06 Way	MC000132
Header 3.81mm Right Angle 12A 08 Way	MC000133
Header 3.81mm Right Angle 12A 10 Way	MC000134
Header 3.81mm Right Angle 12A 12 Way	MC000135

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro

