## **SMD** tweezers

## SMD tweezers - Angled tips

- Suitable for perfect handling of chips and miniature components
- Suitable for assembling SMD printedcircuit boards or ceramic substrates
- Bent shape facilitates optimum access to confined spaces and provides excellent visibility of the area to be worked on
- For all models with the suffix CA in the order number: Special stainless steel, non-magnetic, non-rusting, acid-proof, heat-resistant



4.528 Inch / 115 mm	Model	Weight		Material	Description
		oz.	g		
WITE.	0.5 mm 0.19 Inch 1 1 1 1 1 5 mm		15	Special stainless steel	SMD tweezers, angled 45°, with pointed application.
1479	102ACAX	0.49	14	Special stainless steel	SMD tweezers, angled 45°, with pointed application. Model same as 102ACA, but reverse clamping action for easy holding.
qui	103ACA  1 mm	0.53	15	Special stainless steel	SMD tweezers, angled 45°, with slightly wider tips for vertical application.

## SMD tweezers - Round tips straight

- Suitable for gripping and holding round components and wires
- Blunted edges prevent damage to printed-circuit boards

4 221 In ab / 110 mm

For all models with the suffix SA in the order number: Special stainless steel, non-magnetic, non-rusting, acid-proof, heat-resistant

14/-:----



4.331 Inch/ 110 mm	Model	Weight		Material	Description
		oz.	g		
The state of the s	39SA	0.53	15	Special stainless steel	SMD tweezers with round tips, dia. 0.3 mm/.011 Inch. Serrated finger grips for secure handling. For gripping small wires and cylindrical components.
	40SA	0.53	15	Special stainless steel	SMD tweezers with round tips, dia. 0.4 mm/.015 Inch. Serrated finger grips for secure handling. For gripping small wires and cylindrical components.

14-4-4:-1

D = = = = i = 4 i = =



4.724 Inch / 120 mm	Model	Weight		Material	Description
		OZ.	g		
E-S	150SAMF	0.46	13	Stainless steel	SMD tweezers with round, very narrow tips, dia. 1.2 – 2.5 mm/ .047 – .098 Inch. Serrated finger grips for secure handling. For gripping cylindrical components, mini MELFs, etc.
	150SAD  .059118 Inch Ø1,5-3 mm 4 mm .157 Inch	0.46	13	Stainless steel	SMD tweezers with round tips, dia. 1.5 – 3 mm/.059 –.118 Inch.Serrated finger grips for secure handling. For gripping cylindrical components, mini MELFs, etc.
	150SA 6.8 mm	0.46	13	Special stainless steel	SMD tweezers with round tips, dia. 1.5 – 3 mm/.059 –.118 Inch. Serrated finger grips for secure handling. For gripping cylindrical components.

## SMD tweezers - Round tips bent

- Suitable for gripping fine wires and cylindrical components
- Blunted edges prevent damage to printed-circuit boards
- > For all models with the suffix SA in the order number: Special stainless steel, non-magnetic, non-rusting, acid-proof, heat-resistant



4.528 Inch / 115 mm	Model	Weight		Material	Description
		OZ.	g		
(E-real)	150SAMB	0.60	17		SMD tweezers, angled 40°, with round tips, dia. 1.2 – 2.5 mm/ .047 – .098 Inch. Serrated finger grips for secure handling.

