



Figure similar

POWER SUPPLY; PHASES:3; PN(KW):0,324;
 UPRI(V):575(600)-500-460(480)- 400(415)-230(240)-
 200; USEC(V DC):24; ISEC(A DC):13,5/16 (60/40 CEL);
 F(HZ):50...60; VECTOR GR./SHIELD WNG.:Ii0 /0;
 PROTECTION CL.:I; TA/ISOKL:60 /B; W(%):3; IP00;
 TYPE OF TERMINALS:SCREW CONNECTION;
 INSTALLATION:SCREW; EN 61558-2-6, EN61131-2
 >SAFETY ISOLATING TRANSFORMER<

General technical data:

Product designation		4AV3102-2EB00-0C
product brand name		SIDAC
Vector group		Ii0
Certificate of suitability		CE
Product function		
• Temperature monitoring		No
• Insulation monitoring		No
• Short-circuit and overload proof		No
• varistor protective wiring		Yes
Buffering time for rated value of the power output in the event of power failure	s	0.6
Operating resource protection class		I
Number of shielding windings		0

Inputs:

Phase number of the inputs		3
Type of current of the inputs		AC
Input voltage		
• _1 Rated value	V	575
• _2 Rated value	V	500
• _3 Rated value	V	460
• _4 Rated value	V	400
• _5 Rated value	V	230
• _6 Rated value	V	200
Electrical input frequency		

<ul style="list-style-type: none"> • minimum • maximum 	Hz	50
	Hz	60
Input voltage		
<ul style="list-style-type: none"> • minimum • maximum 	V	180
	V	609.5
Type of electrical connection at input for main current circuit		screw-type terminals

Outputs:

Type of current		DC
<ul style="list-style-type: none"> • _1 at output 		
Output voltage		
<ul style="list-style-type: none"> • _1 Rated value 	V	24
Output voltage of the measurement signal at analog output for DC maximum	V	28.8
Output voltage of the measurement signal at analog output for DC minimum	V	20.4
Output current		
<ul style="list-style-type: none"> • _1 Rated value 	A	13.5
Type of electrical connection at output for main current circuit		screw-type terminals
Relative residual ripple		
<ul style="list-style-type: none"> • of the output voltage 1 for main current circuit maximum 	%	5

Ambient conditions:

Thermal class acc. to IEC 60085		B
Ambient temperature Rated value	°C	60
Protection class IP		IP00

Mechanical data:

Mounting type		screws
Construction form of the iron core		3UI 75/40
Width	m	164
Height	m	190
Depth	m	115

Certificates/ approvals:

General Product Approval	Shipping Approval	other
---------------------------------	--------------------------	--------------



[Declaration of Conformity](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mfb=4AV31022EB000C>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/4AV31022EB000C>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mfb=4AV31022EB000C&lang=en

last modified:

16.03.2015