IMPACT XTREME DRY





Name	Impact Xtreme Dry	Article number	IMPXDRY	EN388
Colour	Red / Black	Glove thickness	Palm: 1,5 mm Back of hand: 8,1 mm	3242 CAT II
Size	7-13	Packaging	1 pairs / plastic bag, 24 pairs / carton	
Certification number	0075/1157/162/06/11/0335	Barcode	7: 7340022523457, 8: 7340022523464, 9: 7340022523471, 10: 7340022523488, 11: 7340022523495, 12: 7340022526373, 13: 7340022526373	

Glove purpose	Very high impact protection in dry conditions.			
	Glove in SupraBlock 4; high quality micro fibre in palm. Polyester/Spandex fabric in back of hand.			
	SupraBlock Impact and SupraBlock Stop on back of fingers with micro fibre on top.			
Materials	SupraBlock Impact have a residual force of 3 kN and is Impact approved according to new EN388 standard.			
Fitting (elastic tight, tight, close, loose)	Tight fit.			
Abrasion	Good abrasion resistance.			
	Not suitable for environments where cut resistance is necessary. Strength 0000			
Cut	Hardness OOOOO			
Tear	Very high tear resistance; keep away from machines with moving parts.			
Puncture	Poor puncture and needle resistance.			
	Not suitable for contact with heated objects.			
Heat and insulation	Not suitable for use in cold temperatures.			
Water/Oil	Water and oil repellant with SupraCoat Dry treatment.			
Grip	Good dry grip.			
Breathing	Good breathing properties.			
Impact	Very good Impact protection with residual force after 5 Joule impact only 3 kN.			
Chemical safety	REACH safe.			

Disposal	No special waste	Wash in 30 degrees.
Suitable industries	Offshore, mining, transport, wind mill maintenance and drilling.	 Store in cool, dry and dark place. Avoid storage for several years.