



Figure similar

INSERTABLE JUMPER, 2-POLE, FULLY INSULATED, INSERTED IN LOCKING SLEEVE AND LATCHED FOR 150 MM<sup>2</sup> TERMINALS

### Main circuit

Operating current / Rated value	A	232
---------------------------------	---	-----

### Mechanical Design

Mounting type		others
Contact spacing	mm	150

### Certificates

Design tested acc. to type of protection / EEx e		No
--	--	----

General Product Approval	Declaration of Conformity
--------------------------	---------------------------



### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/8WH90203CA00>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<http://support.automation.siemens.com/WW/view/en/8WH90203CA00/all>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=8WH90203CA00](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WH90203CA00)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://ausschreibungstexte.siemens.com/tiplv>

last modified:

11.03.2015