

SAFETY DATA SHEET

Issue date: Revision date: 14-June-2022 14-June-2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

Multi Oil

of the mixture

Registration number

PR-nr 1937701 **Product registration number**

None. **Synonyms**

Product code BDS000679AF

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Lubricants Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Company name CRC Industries Europe by

Address Touwslagerstraat 1

> 9240 Zele Belgium

+32(0)52/45.60.11 Telephone +32(0)52/45.00.34 Fax E-mail hse@crcind.com Website www.crcind.com

1.4. Emergency telephone

number

Tel.: +32(0)52/45.60.11 (office hours: 9-17h CET)

General in EU 112 (Available 24 hours a day. SDS/Product information may not be available for

the Emergency Service.)

Austria National Poisons

Information Centre

Belgium National Poisons

Control Center

Bulgaria National

Centre

070 245 245 (Available 24 hours a day. SDS/Product information may not be

+431 406 4343 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

available for the Emergency Service.)

Toxicological Information

Czech Republic National Poisons Information

Centre

+359 2 9154233 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

+420 224 919 293, or +420 224 915 402 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Denmark National Poisons

Control Center

+45 82 12 12 12 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.)

Estonia National Poisons Information Centre

16662 or abroad: (+372) 626 9390 (Monday 9:00AM to Saturday 9:00AM (closed on Sundays and on national holidays). SDS/Product information may not be

available for the Emergency Service.)

Finland National Poison Information Center

(09) 471 977 (direct) or (09) 4711 (exchange) (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

France National Poisons Control Center

ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Hungary National Emergency Phone Number

36 80 20 11 99 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

Lithuania Neatidėliotina informacija apsinuodijus +370 5 236 20 52 or +37068753378 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Malta Accident and **Emergency Department**

Material name: Multi Oil - Manufacturers

2545 4030 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Netherlands National Poisons Information Center (NVIC)

030-274 88 88 (Only for the purpose of informing medical personnel in cases of

acute intoxications)

Norway Norwegian Poison 22 59 13 00 (Available 24 hours a day. SDS/Product information may not be

available for the Emergency Service.) **Information Center**

800 250 250 (Available 24 hours a day. SDS/Product information may not be **Portugal Poison Centre**

available for the Emergency Service.)

Romania Număr de telefon

care poate fi apelat în caz de urgență:

021 5992300, int. 291 Spitalul Clinic de Urgență București:

spital@urgentafloreasca.ro

0265 212111, 0265 211292, 0265 217235 Spitalul Clinic Judetean de Urgentă Romania

Târgu Mures: secretariat@spitjudms.ro

Slovakia National

Toxicological Information

Centre

+421 2 5477 4166 (Available 24 hours a day. SDS/Product information may not

be available for the Emergency Service.)

Sweden National Poison 112 - and ask for Poison Information (Available 24 hours a day. SDS/Product

information may not be available for the Emergency Service.) Information Center

Switzerland Tox Info 145 (Available 24 hours a day. SDS/Product information may not be available for

the Emergency Service.) Suisse

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Aerosols Category 1 H222 - Extremely flammable

aerosol.

H229 - Pressurized container: May

burst if heated.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Hazard pictograms

Signal word Danger

Hazard statements

Extremely flammable aerosol. H222

Pressurized container: May burst if heated. H229

Precautionary statements

Prevention

Keep out of reach of children. P102

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P210

Do not spray on an open flame or other ignition source. P211

Do not pierce or burn, even after use. P251

Response Not assigned.

Storage

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P410 + P412

Disposal Not assigned.

Supplemental label information EUH066 - Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards This mixture does not contain substances assessed to be vPvB / PBT according to Regulation

(EC) No 1907/2006, Annex XIII. The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or

Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Material name: Multi Oil - Manufacturers

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	50 - 75	- 926-141-6	01-2119456620-43	-	
Classification:	Asp. Tox.	1;H304			
Carbon dioxide	1 - 5	124-38-9 204-696-9	-	-	#
Classification:	Press. Ga	s:H280			

List of abbreviations and symbols that may be used above

ATE: Acute toxicity estimate.

M: M-factor

PBT: persistent, bioaccumulative and toxic substance. vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume. #: This substance has been assigned Union workplace exposure limit(s).

SECTION 4: First aid measures

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

4.1. Description of first aid measures

InhalationIf symptoms develop move victim to fresh air. Get medical attention if symptoms persist.Skin contactWash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

In the unlikely event of swallowing contact a physician or poison control centre. Rinse mouth. Do

not induce vomiting without advice from poison control center. If vomiting occurs, keep head low

so that stomach content doesn't get into the lungs.

4.2. Most important symptoms and effects, both acute and

Exposure may cause temporary irritation, redness, or discomfort.

delayed
4.3. Indication of any
immediate medical attention

and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

General fire hazards Extremely flammable aerosol. Will burn if involved in a fire.

5.1. Extinguishing media

Suitable extinguishing

media

Foam. Dry chemicals. Carbon dioxide (CO2).

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Contents under pressure. Pressurised container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective

equipment for firefighters

Special fire fighting procedures

Specific methods

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Move containers from fire area if you can do so without risk. Cool containers exposed to heat with

water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapour pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Use standard firefighting procedures and consider the hazards of other involved materials. In the

event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

For emergency responders Keep unnecessary personnel away. Ventilate closed spaces before entering them. Local

authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

see section 8 of the SD

6.2. Environmental precautions Avoid discharge into drains, water courses or onto the ground.

Material name: Multi Oil - Manufacturers

6.3. Methods and material for containment and cleaning up

Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. The product is immiscible with water and will spread on the water surface. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS). Storage class (TRGS 510): 2B (Aerosol dispensers and lighters)

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Austria Components	Туре	Value	
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	TWA (MAK)	200 ppm	
Austria. MAK List, OEL Ordinand			
Components	Туре	Value	
Carbon dioxide (CAS 124-38-9)	Ceiling	18000 mg/m3	
		10000 ppm	
	MAK	9000 mg/m3	
		5000 ppm	
Belgium. Exposure Limit Values			
Components	Туре	Value	Form
Carbon dioxide (CAS 124-38-9)	STEL	54784 mg/m3	
		30000 ppm	
	TWA	9131 mg/m3	
		5000 ppm	
White mineral oil (CAS 8042-47-5)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Bulgaria, OELs, Regulation No 1	3 on protection of workers agains	st risks of exposure to che	mical agents at work
Components	Туре	Value	
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3	
		5000 ppm	
White mineral oil (CAS 8042-47-5)	TWA	5 mg/m3	

Material name: Multi Oil - Manufacturers

Components	Туре	Value	
Carbon dioxide (CAS 124-38-9)	MAC	9000 mg/m3	
		5000 ppm	
Czech Republic. OELs. C			_
Components	Туре	Value	Form
Carbon dioxide (CAS 124-38-9)	Ceiling	45000 mg/m3	
	TWA	9000 mg/m3	
White mineral oil (CAS 8042-47-5)	Ceiling	10 mg/m3	Aerosol
	TWA	5 mg/m3	Aerosol
Denmark. Exposure Limi		Value	Form
Components	Туре		FOIIII
Carbon dioxide (CAS 124-38-9)	TLV	9000 mg/m3	
		5000 ppm	
White mineral oil (CAS 8042-47-5)	TLV	1 mg/m3	Mist.
•	onal Exposure Limits of Hazardous Sul Type	ostances (Regulation No. 105 Value	/2001, Annex), as amende
Carbon dioxide (CAS	TWA	9000 mg/m3	
124-38-9)		5000 ppm	
Finland. Workplace Expo			F
Components	Туре	Value	Form
Carbon dioxide (CAS 124-38-9)	TWA	9100 mg/m3	
		5000 ppm	
White mineral oil (CAS 8042-47-5)	TWA	5 mg/m3	Mist.
France. OELs. Indicative Components	Occupational Exposure Limits as Pres Type	cribed by Order of 30 June 20 Value	004, as amended
Carbon dioxide (CAS	VME	9000 mg/m3	
124-38-9)		9000 mg/m3	
		5000 mg/mo	
		5000 ppm	
France. Threshold Limit	Values (VLEP) for Occupational Exposi	• •	IRS ED 984
Components	Туре	Value	
Carbon dioxide (CAS 124-38-9)	VME	9000 mg/m3	
Regulatory status:	Regulatory indicative (VRI)		
		5000 ppm	
Regulatory status:	Regulatory indicative (VRI)		
Germany Components	Туре	Value	
Hydrocarbons, C11-C14, n-alkanes, isoalkanes,	TWA	300 mg/m3	
	(advisory OELs). Commission for the I	nvestigation of Health Hazard	ls of Chemical Compound
in the Work Area (DFG)			
Components	Type	Value	Form

Material name: Multi Oil - Manufacturers

SDS EU

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)

Components	Туре	Value	Form
		5000 ppm	
White mineral oil (CAS 8042-47-5)	TWA	5 mg/m3	Respirable fraction.
Germany. TRGS 900, Limit Values in the Components	e Ambient Air at the Workplace Type	Value	Form
Carbon dioxide (CAS	AGW	9100 mg/m3	
124-38-9)		5000	
MMI: 14- main a mail ail (OAO	A 014/	5000 ppm	Descinable for the
White mineral oil (CAS 8042-47-5)	AGW	5 mg/m3	Respirable fraction.
Greece. OELs (Decree No. 90/1999, as a	amended)		
Components	Туре	Value	Form
Carbon dioxide (CAS	STEL	54000 mg/m3	
124-38-9)		•	
		5000 ppm	
	TWA	9000 mg/m3	
		5000 ppm	
White mineral oil (CAS	TWA	5 mg/m3	Mist.
8042-47-5)			
Hungary. OELs. Joint Decree on Chemi Components		Value	
•	Туре		
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3	
White mineral oil (CAS 8042-47-5)	TWA	5 mg/m3	
Iceland. OELs. Regulation 154/1999 on o	occupational exposure limits Type	Value	Form
Carbon dioxide (CAS	TWA	9000 mg/m3	
124-38-9)		J	
		5000 ppm	
White mineral oil (CAS 8042-47-5)	TWA	1 mg/m3	Mist.
0012 11 0)			
Ireland. Occupational Exposure Limits			_
Ireland. Occupational Exposure Limits Components	Туре	Value	Form
Ireland. Occupational Exposure Limits Components Carbon dioxide (CAS	Type TWA	Value 9000 mg/m3	Form
Ireland. Occupational Exposure Limits Components Carbon dioxide (CAS		9000 mg/m3	Form
Ireland. Occupational Exposure Limits Components Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3 5000 ppm	
Ireland. Occupational Exposure Limits Components Carbon dioxide (CAS 124-38-9) White mineral oil (CAS 8042-47-5)		9000 mg/m3	Form Inhalable fraction.
Ireland. Occupational Exposure Limits Components Carbon dioxide (CAS 124-38-9) White mineral oil (CAS 8042-47-5)	TWA	9000 mg/m3 5000 ppm	
Ireland. Occupational Exposure Limits Components Carbon dioxide (CAS 124-38-9) White mineral oil (CAS	TWA	9000 mg/m3 5000 ppm	
Ireland. Occupational Exposure Limits Components Carbon dioxide (CAS 124-38-9) White mineral oil (CAS 8042-47-5) Italy. Occupational Exposure Limits Components	TWA	9000 mg/m3 5000 ppm 5 mg/m3 Value	Inhalable fraction.
Ireland. Occupational Exposure Limits Components Carbon dioxide (CAS 124-38-9) White mineral oil (CAS 8042-47-5) Italy. Occupational Exposure Limits Components Carbon dioxide (CAS	TWA TWA	9000 mg/m3 5000 ppm 5 mg/m3 Value 9000 mg/m3	Inhalable fraction.
Ireland. Occupational Exposure Limits Components Carbon dioxide (CAS 124-38-9) White mineral oil (CAS 8042-47-5) Italy. Occupational Exposure Limits Components Carbon dioxide (CAS	TWA TWA	9000 mg/m3 5000 ppm 5 mg/m3 Value	Inhalable fraction.
Ireland. Occupational Exposure Limits Components Carbon dioxide (CAS 124-38-9) White mineral oil (CAS 8042-47-5) Italy. Occupational Exposure Limits Components Carbon dioxide (CAS 124-38-9) White mineral oil (CAS	TWA TWA	9000 mg/m3 5000 ppm 5 mg/m3 Value 9000 mg/m3	Inhalable fraction.
Ireland. Occupational Exposure Limits Components Carbon dioxide (CAS 124-38-9) White mineral oil (CAS 8042-47-5) Italy. Occupational Exposure Limits	TWA Type TWA TWA	9000 mg/m3 5000 ppm 5 mg/m3 Value 9000 mg/m3 5000 ppm 5 mg/m3	Inhalable fraction. Form Inhalable fraction.
Ireland. Occupational Exposure Limits Components Carbon dioxide (CAS 124-38-9) White mineral oil (CAS 8042-47-5) Italy. Occupational Exposure Limits Components Carbon dioxide (CAS 124-38-9) White mineral oil (CAS 8042-47-5) Latvia. OELs. Occupational exposure lin Components Carbon dioxide (CAS	TWA TWA Type TWA TWA TWA TWA TWA mit values of chemical substances	9000 mg/m3 5000 ppm 5 mg/m3 Value 9000 mg/m3 5000 ppm 5 mg/m3 in work environment	Inhalable fraction. Form Inhalable fraction.
Ireland. Occupational Exposure Limits Components Carbon dioxide (CAS 124-38-9) White mineral oil (CAS 8042-47-5) Italy. Occupational Exposure Limits Components Carbon dioxide (CAS 124-38-9) White mineral oil (CAS 8042-47-5) Latvia. OELs. Occupational exposure lin Components	TWA TWA Type TWA TWA TWA TWA mit values of chemical substances Type	9000 mg/m3 5000 ppm 5 mg/m3 Value 9000 mg/m3 5000 ppm 5 mg/m3 in work environment Value 9000 mg/m3	Inhalable fraction. Form Inhalable fraction.
Ireland. Occupational Exposure Limits Components Carbon dioxide (CAS 124-38-9) White mineral oil (CAS 8042-47-5) Italy. Occupational Exposure Limits Components Carbon dioxide (CAS 124-38-9) White mineral oil (CAS 8042-47-5) Latvia. OELs. Occupational exposure lin Components Carbon dioxide (CAS	TWA TWA Type TWA TWA TWA TWA mit values of chemical substances Type	9000 mg/m3 5000 ppm 5 mg/m3 Value 9000 mg/m3 5000 ppm 5 mg/m3 in work environment Value	Inhalable fraction. Form Inhalable fraction.

Lithuania. OELs. Limit Values for Components	Туре	Value	Form
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3	
		5000 ppm	
White mineral oil (CAS 3042-47-5)	STEL	3 mg/m3	Fume and mist.
	TWA	1 mg/m3	Fume and mist.
uxembourg. Binding Occupation Components	al exposure limit values (Annex Type	I), Memorial A Value	
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3	
		5000 ppm	
Malta. OELs. Occupational Exposi	re Limit Values (L.N. 227. of Oc	cupational Health and Safet	y Authority Act (CAP. 42
Schedules I and V) Components	Туре	Value	
Carbon dioxide (CAS	TWA	9000 mg/m3	
124-38-9)		5000 ppm	
Netherlands	_		
Components	Туре	Value	
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	TWA (MAC)	1200 mg/m3	
Netherlands. OELs (binding) Components	Туре	Value	Form
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3	
White mineral oil (CAS 8042-47-5)	TWA	5 mg/m3	Mist.
Norway. Administrative Norms for Components	Contaminants in the Workplace Type	Value	Form
Carbon dioxide (CAS 124-38-9)	TLV	9000 mg/m3	
		5000 ppm	
White mineral oil (CAS 8042-47-5)	TLV	1 mg/m3	Mist.
Poland. Ordinance of the Minister concentrations and intensities of I	narmful health factors in the wor	k environment, Journal of I	_aws 2014, item 817
Components	Туре	Value	Form
Carbon dioxide (CAS 124-38-9)	STEL	27000 mg/m3	
•	TWA	9000 mg/m3	
White mineral oil (CAS 8042-47-5)	TWA	5 mg/m3	Inhalable fraction.
Portugal. OELs. Decree-Law n. 290 Components	0/2001 (Journal of the Republic - Type	1 Series A, n.266) Value	
Carbon dioxide (CAS	TWA	9000 mg/m3	
124-38-9)		5000 ppm	
124-38-9)			
124-38-9) Portugal. VLEs. Norm on occupati	onal exposure to chemical agen Type		Form
Portugal. VLEs. Norm on occupati Components Carbon dioxide (CAS		ts (NP 1796)	Form
	Туре	ts (NP 1796) Value	Form

Romania. OELs. Protection of wo Components	Type	cal agents at the workplace Value	
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3	
,		5000 ppm	
White mineral oil (CAS 8042-47-5)	STEL	10 mg/m3	
,	TWA	5 mg/m3	
Slovakia. OELs. Regulation No. 3			cal agents Form
Components	Type	Value	FOIIII
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3	
		5000 ppm	
White mineral oil (CAS 8042-47-5)	STEL	3 mg/m3	Fume and mist.
		15 ppm	Fume and mist.
	TWA	1 mg/m3	Fume and mist.
		5 ppm	Fume and mist.
Slovenia. OELs. Regulations con (Official Gazette of the Republic		against risks due to exposure	to chemicals while workin
Components	Туре	Value	Form
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3	
,		5000 ppm	
White mineral oil (CAS 3042-47-5)	TWA	5 mg/m3	Respirable fraction.
Spain. Occupational Exposure Li Components	imits Type	Value	Form
Carbon dioxide (CAS	TWA	9150 mg/m3	
124-38-9)		5000 ppm	
White mineral oil (CAS	STEL	10 mg/m3	Mist.
8042-47-5)	TWA	5 mg/m3	Mist.
		•	
Sweden. OELs. Work Environme Components	nt Authority (AV), Occupationa Type	ll Exposure Limit Values (AFS Value	2015:7) Form
Carbon dioxide (CAS			
	STEL	18000 mg/m3	
	STEL	18000 mg/m3 10000 ppm	
	STEL	· ·	
		10000 ppm	
124-38-9) White mineral oil (CAS		10000 ppm 9000 mg/m3	Mist.
124-38-9) White mineral oil (CAS	TWA	10000 ppm 9000 mg/m3 5000 ppm	Mist. Mist.
124-38-9) White mineral oil (CAS 8042-47-5) Switzerland. SUVA Grenzwerte a	TWA STEL TWA m Arbeitsplatz	10000 ppm 9000 mg/m3 5000 ppm 3 mg/m3 1 mg/m3	Mist.
White mineral oil (CAS 8042-47-5) Switzerland. SUVA Grenzwerte a Components	TWA STEL TWA m Arbeitsplatz Type	10000 ppm 9000 mg/m3 5000 ppm 3 mg/m3 1 mg/m3	
White mineral oil (CAS 8042-47-5) Switzerland. SUVA Grenzwerte a Components Carbon dioxide (CAS	TWA STEL TWA m Arbeitsplatz	10000 ppm 9000 mg/m3 5000 ppm 3 mg/m3 1 mg/m3 Value 9000 mg/m3	Mist.
White mineral oil (CAS 8042-47-5) Switzerland. SUVA Grenzwerte a Components Carbon dioxide (CAS 124-38-9) White mineral oil (CAS	TWA STEL TWA m Arbeitsplatz Type	10000 ppm 9000 mg/m3 5000 ppm 3 mg/m3 1 mg/m3	Mist.
White mineral oil (CAS 8042-47-5) Switzerland. SUVA Grenzwerte a Components Carbon dioxide (CAS 124-38-9) White mineral oil (CAS 8042-47-5)	TWA STEL TWA m Arbeitsplatz Type TWA TWA	10000 ppm 9000 mg/m3 5000 ppm 3 mg/m3 1 mg/m3 Value 9000 mg/m3 5000 ppm	Mist. Form
White mineral oil (CAS 8042-47-5) Switzerland. SUVA Grenzwerte a Components Carbon dioxide (CAS 124-38-9) White mineral oil (CAS 8042-47-5) UK. EH40 Workplace Exposure L	TWA STEL TWA m Arbeitsplatz Type TWA TWA	10000 ppm 9000 mg/m3 5000 ppm 3 mg/m3 1 mg/m3 Value 9000 mg/m3 5000 ppm	Mist. Form
Carbon dioxide (CAS 124-38-9) White mineral oil (CAS 8042-47-5) Switzerland. SUVA Grenzwerte a Components Carbon dioxide (CAS 124-38-9) White mineral oil (CAS 8042-47-5) UK. EH40 Workplace Exposure L Components Carbon dioxide (CAS 124-38-9)	TWA STEL TWA m Arbeitsplatz Type TWA TWA TWA	10000 ppm 9000 mg/m3 5000 ppm 3 mg/m3 1 mg/m3 Value 9000 mg/m3 5000 ppm 5 mg/m3	Mist. Form

UK. EH40 Workplace Exposure Limits (WELs)

 Components
 Type
 Value

 TWA
 9150 mg/m3

5000 ppm

EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU

Components Type Value

Carbon dioxide (CAS TWA 9000 mg/m3

124-38-9)

5000 ppm

Biological limit values No biological exposure limits noted for the ingredient(s).

Recommended monitoring

procedures

Follow standard monitoring procedures.

Derived no effect levels (DNELs)

General Population

Components Value Assessment factor Notes

White mineral oil (CAS 8042-47-5)

Long-term, Systemic, Dermal 93 mg/kg bw/day Long-term, Systemic, Inhalation 35 mg/m3

Workers

Components Value Assessment factor Notes

White mineral oil (CAS 8042-47-5)

Long-term, Systemic, Dermal 220 mg/kg bw/day Long-term, Systemic, Inhalation 160 mg/m3

Predicted no effect concentrations (PNECs)

ComponentsValueAssessment factorNotesWhite mineral oil (CAS 8042-47-5)300Oral

8.2. Exposure controls

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been

established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

General information Use personal protective equipment as required. Personal protection equipment should be chosen

according to the CEN standards and in discussion with the supplier of the personal protective

equipment.

Eye/face protection Wear safety glasses with side shields (or goggles). Use eye protection conforming to EN 166.

Skin protection

- Hand protection For accidental contact the use of disposable gloves should be sufficient provided they are changed

immediately after a splash or spill may occur. If intentional contact is expected reusable gloves should be used with a breakthrough time greater than the total duration of the product use. Suitable gloves can be recommended by the glove supplier. Nitrile gloves are recommended.

Other Not available.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment. Chemical respirator with

organic vapour cartridge. (Filter type A)

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Hygiene measures When using do not smoke. Always observe good personal hygiene measures, such as washing

after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

Environmental exposure

controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or

engineering modifications to the process equipment may be necessary to reduce emissions to

acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical stateLiquid.FormAerosol.ColourColourless.

Odour Solvent.

Melting point/freezing point -56,6 °C (-69,9 °F) estimated

Boiling point or initial boiling

point and boiling range

Not available.

Flammability (solid, gas) Not available.

Flash point 74,0 °C (165,2 °F) Closed cup

Auto-ignition temperature $> 200 \, ^{\circ}\text{C} \, (> 392 \, ^{\circ}\text{F})$

Decomposition temperatureNot available.pHNot applicable.

Solubility(ies)

Solubility (water)

Vapour pressure

Vapour density

Relative density

Particle characteristics

Insoluble in water

Not available.

Not available.

Not available.

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No relevant additional information available.

9.2.2. Other safety characteristics

Aerosol spray ignition

distance

> 75 cm

Explosive properties Not explosive.

Heat of combustion (NFPA

30B)

10,74 kJ/g estimated

Oxidising properties Not oxidising.

Viscosity 2,91 mPa·s at 40°C

2,91 mPa·s at 40 C

VOC 515 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability Material is stable under normal conditions.

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid Avoid high temperatures.10.5. Incompatible materials Strong oxidising agents.

10.6. Hazardous

Carbon oxides.

decomposition products

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contactBased on available data, the classification criteria are not met. **Eye contact**Based on available data, the classification criteria are not met.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms Exposure may cause temporary irritation, redness, or discomfort.

11.1. Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

Components Species Test Results

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Acute Dermal

Material name: Multi Oil - Manufacturers

LD50 Rabbit > 5000 mg/kg

Components	Species	Test Results	
Inhalation			
LC50	Rat	> 5000 mg/m3, 8 h	
Oral			
LD50	Rat	> 5000 mg/kg	
Skin corrosion/irritation	Based on available data, the classification criteria are not met.		
Serious eye damage/eye irritation	Based on available data, the classification criteria are not met.		
Respiratory sensitisation	Based on available data, the classification criteria are not met.		
Skin sensitisation	Based on available data, the classification criteria are not met.		
Germ cell mutagenicity	Based on available data, the classification criteria are not met.		
Carcinogenicity	Based on available data, the classification criteria are not met.		

Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)

Not listed.

Based on available data, the classification criteria are not met. Reproductive toxicity Based on available data, the classification criteria are not met. Specific target organ toxicity -

single exposure

Based on available data, the classification criteria are not met.

Specific target organ toxicity repeated exposure

Aspiration hazard

Mixture versus substance

information

Not available.

11.2. Information on other hazards

Endocrine disrupting

properties

The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU)

2018/605 at levels of 0.1% or higher.

Not likely, due to the form of the product.

Other information Not available.

SECTION 12: Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the 12.1. Toxicity

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components Species **Test Results**

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Aquatic

Acute

EC50 1000 mg/l, 48 h Crustacea Daphnia LC50 1000 mg/l, 96 h Fish Oncorhynchus mykiss

12.2. Persistence and

degradability

No data is available on the degradability of any ingredients in the mixture.

12.3. Bioaccumulative potential No data available.

Partition coefficient n-octanol/water (log Kow) Not available.

Bioconcentration factor (BCF) Not available. No data available. 12.4. Mobility in soil

12.5. Results of PBT and vPvB

assessment

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.

12.6. Endocrine disrupting

properties

The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU)

2018/605 at levels of 0.1% or higher.

12.7. Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential. GWP: 0

SECTION 13: Disposal considerations

13.1. Waste treatment methods

SDS FU

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

EU waste code The Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents **Disposal methods/information**

under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance

with local/regional/national/international regulations.

Dispose in accordance with all applicable regulations. **Special precautions**

SECTION 14: Transport information

ADR

14.1. UN number UN1950 14.2. UN proper shipping **AEROSOLS**

name

14.3. Transport hazard class(es)

2.1 Class Subsidiary risk 2.1 Label(s)

Not available. Hazard No. (ADR)

Tunnel restriction code D

14.4. Packing group Not available.

14.3. Transport hazard class(es)

ADR/RID - Classification 5F

code.

14.5. Environmental hazards No

Read safety instructions, SDS and emergency procedures before handling. 14.6. Special precautions

for user

IATA

14.1. UN number UN1950 **AEROSOLS** 14.2. UN proper shipping

name

14.3. Transport hazard class(es)

2.1 Class Subsidiary risk

Not available. 14.4. Packing group

14.5. Environmental hazards No. **ERG Code**

14.6. Special precautions

for user

Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

Allowed with restrictions.

aircraft Cargo aircraft only

Allowed with restrictions.

IMDG

14.1. UN number UN1950 14.2. UN proper shipping **AEROSOLS**

name 14.3. Transport hazard class(es)

> 2.1 Class Subsidiary risk

Not available. 14.4. Packing group

14.5. Environmental hazards

Marine pollutant Nο F-D S-U **EmS**

14.6. Special precautions

for user

Read safety instructions, SDS and emergency procedures before handling.

14.7. Maritime transport in bulk

according to IMO instruments

Not established.

Material name: Multi Oil - Manufacturers



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture **EU regulations**

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended Carbon dioxide (CAS 124-38-9)

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Not listed.

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Other regulations

Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation

(EC) No 1907/2006, as amended.

National regulations Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as

amended.

15.2. Chemical safety

assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road. ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road.

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert - Germany).

ATE: Acute Toxicity Estimate according to REGULATION (EC) No 1272/2008 (CLP).

CAS: Chemical Abstract Service.

Ceiling: Short Term Exposure Limit Ceiling value. CEN: European Committee for Standardization.

Material name: Multi Oil - Manufacturers

CLP: Classification, Labeling and Packaging REGULATION (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures.

GWP: Global Warming Potential.

IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.

IMDG: International Maritime Dangerous Goods.

MAC: Maximum Allowed Concentration.

MAK: Threshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG).

MARPOL: International Convention for the Prevention of Pollution from Ships.

PBT: Persistent, bioaccumulative and toxic.

REACH: Registration, Evaluation and Authorization of Chemicals (REGULATION (EC) No 1907/2006 concerning Registration, Evaluation Authorization and Restriction of Chemicals). RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer).

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short term exposure limit. TLV: Threshold Limit Value. TWA: Time Weighted Average. VLE: Exposure Limit Value. VME: Exposure Average Value.

VOC: Volatile organic compounds. vPvB: Very persistent and very bioaccumulative.

STEL: Short-term Exposure Limit.

Not available. References

Information on evaluation method leading to the classification of mixture

Full text of any H-statements not written out in full under Sections 2 to 15

Revision information Training information

Disclaimer

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

H280 Contains gas under pressure: may explode if heated.

H304 May be fatal if swallowed and enters airways.

None.

Follow training instructions when handling this material.

CRC Industries Europe byba cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.

Material name: Multi Oil - Manufacturers