

TDR500/3

Handheld TDR



- **Simple operation**
- **AUTO set up for instant use**
- **Ultra fast pulse for near end fault identification**
- **Trace HOLD feature**
- **IP54 rating offers real life working**
- **Designed for use on all metallic cable pairs**

DESCRIPTION

The TDR500/3 is a hand held, compact time domain reflectometer for locating faults on metallic cables. It has a minimum resolution of 0.1 m and a 5 km maximum range depending on velocity factor selected and cable type.

Four output impedances are available (25, 50, 75, and 100 Ω) and a velocity factor between 0.2 and 0.99 will meet any cable test requirements

The TDR500/3 has a simple selection option which together with a 4 way control switch offers an intuitive operation for the user.

FEATURES AND BENEFITS

An AUTO selection option ensures that the most effective parameters are selected depending on the range required, aiding rapid diagnosis of the TDR trace. A clear operator controlled cursor allows instant measurement of the distance to the fault.

A trace HOLD feature also allows the operator to hold a trace on the screen, something not seen on most other handheld TDRs. Extra high resolution together with whitelight backlight and grey scale tones give the graphical display a vibrancy, aiding the user in identifying key events on the trace.

- Backlit graphics monochrome LCD (256 x 128)
- Adjustable display contrast
- Resolution to 0.1 m
- For use on Telecom TNV-3 circuit, or 150V CAT IV power circuits
- Power blocking filter not required
- Environmental protection to IP54
- 2ns pulse for near end fault location
- AUTO option selecting gain and pulse for each range
- Display distance in metres or feet
- Uses five AA (LR6) primary cells

SPECIFICATIONS

| | |
|-------------------------|---|
| Note | Except where otherwise stated, this specification applies at an ambient temperature of 20 °C |
| Range | 10 m, 25 m, 100 m, 250 m, 1000 m, 2500 m, 5000 m (30 ft, 75 ft, 300 ft, 750 ft, 3000 ft, 7500 ft, 15000 ft) |
| Accuracy | ±1% of range ± pixel at 0.67 VF [Note - The measurement accuracy is for the indicated cursor position only and is conditional on the velocity factor being correct.] |
| Resolution | 1% of range |
| Input protection | This instrument complies with IEC61010-1 for connection to live systems up to 150 V CAT IV when used with the optional fused test lead set. |
| Output pulse | 5 volts peak to peak into open circuit. Pulse widths determined by range and cable. |
| Gain | Set for each range with three user selectable steps (in manual operating mode) |
| Velocity factor | Variable from 0.2 to 0.99 in steps of 0.01 |
| TX null | Automatic |
| Power down | Automatic after 5 minutes with no key press |
| Backlight | Stays on for 1 minute with no key press |
| Battery | Five LR6 (AA) type batteries, Manganese alkali or nickel metal-hydride cells |
| Battery life | Up to 14 hours (typical) |
| IP rating | The instrument is designed for use indoors or outdoors and is rated to IP54 |
| Dimensions | 230 x 115 x 48 mm (9 x.0 x 4.5 x 2.0 inches) |
| Weight | 0.6 kg (1.32 lbs) |
| Case | ABS |
| Connectors | Two 4 mm-safety terminals |
| Test lead | (TDR500/3): 1.5 metres long consisting of 2 x 4 mm shrouded connector to miniature crocodile clips |
| Display | 256 x 128 pixel Graphics LCD |

ENVIRONMENTAL

| | |
|---|--|
| Operating temperature range and humidity | 15 °C to +50 °C (5 °F to 122 °F) |
| Storage temperature range and humidity | -20 °C to 70 °C (-4 °F to 158 °F) |
| Safety | When using the optional fused test lead set this instrument complies with IEC61010-1 for connection to live systems with less than 300 V between the terminals and up to 150 V CAT IV to earth |
| EMC | Complies with Electromagnetic Compatibility Specifications (Light industrial) BS EN 61326-1, with a minimum performance of 'B' for all immunity tests |

ORDERING INFORMATION

| Description | Order Code |
|------------------------------|------------|
| Time Domain Reflectometer | 1002-227 |
| Included accessories | |
| Hard case | 5410-420 |
| Miniature clip test lead set | 6231-652 |
| User guide CD | 2002-178 |
| Optional accessories | |
| Fused test lead set | 1002-015 |
| Pouch - test and carry case | 2001-322 |
| Rubber boot with stand | 6231-802 |

UK
Archcliffe Road Dover
CT17 9EN England
T +44 (0) 1304 502101
F +44 (0) 1304 207342
UKsales@megger.com

UNITED STATES
4271 Bronze Way
Dallas TX 75237-1019 USA
T 800 723 2861 (USA only)
T +1 214 333 3201
F +1 214 331 7399
USsales@megger.com

OTHER TECHNICAL SALES OFFICES
Valley Forge USA, College Station USA,
Sydney AUSTRALIA, Danderyd SWEDEN,
Ontario CANADA, Trappes FRANCE,
Oberursel GERMANY, Aargau SWITZERLAND,
Kingdom of BAHRAIN, Mumbai INDIA,
Johannesburg SOUTH AFRICA, Chonburi THAILAND

CERTIFICATION ISO
Registered to ISO 9001:2000 Cert. no. Q 09290
Registered to ISO 14001:1996 Cert. no. EMS 61597

TDR500-3_DS_en_V04
www.megger.com
Megger is a registered trademark