



CONNECTION CABLE; LENGTH 0,5M; FLAT;  
 CONNECTION OF BASIC UNIT TO CURRENT  
 MEASURING MODULE, CURRENT/VOLTAGE  
 MEASUR. MODULE, OPERATOR PANEL OR TO  
 EXPANSION MODULES VIA SYSTEM INTERFACE

General technical data:

<b>product brand name</b>		SIRIUS
<b>Product designation</b>		connecting cable
<b>Design of the product</b>		<kein Wert>
<b>Protection class IP</b>		<kein Wert>
<b>Ambient temperature</b>		
• during storage	°C	-40 ... +80
• during operation	°C	-25 ... +60
• during transport	°C	-40 ... +80
<b>Equipment marking acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750</b>		<kein Wert>
<b>Equipment marking acc. to DIN EN 61346-2</b>		<kein Wert>

Certificates/ approvals:

**General Product Approval**      **EMC**      **Test Certificates**



[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)

**Shipping Approval**



**other**

[Confirmation](#)



Profibus

[PROFINET-Certification](#)

[PROFISafe-Certification](#)

**Further information**

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/industrial-controls/catalogs>

**Industry Mall (Online ordering system)**

<http://www.siemens.com/industrymall>

**Cax online generator**

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mfb=3UF79320AA000>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3UF79320AA000>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mfb=3UF79320AA000&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mfb=3UF79320AA000&lang=en)

