



CONNECTION CABLE; LENGTH 2,5M; ROUND;
CONNECTION OF BASIC UNIT TO CURRENT
MEASURING MODULE, CURRENT/VOLTAGE
MEASUR. MODULE, OPERATOR PANEL OR TO
EXPANSION MODULES VIA SYSTEM INTERFACE

General technical data:

product brand name		SIRIUS
Product designation		connecting cable
Design of the product		<kein Wert>
Protection class IP		<kein Wert>
Ambient temperature		
• during storage	°C	-40 ... +80
• during operation	°C	-25 ... +60
• during transport	°C	-40 ... +80
Equipment marking acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750		<kein Wert>
Equipment marking acc. to DIN EN 61346-2		<kein Wert>

Certificates/ approvals:

General Product Approval **EMC** **Test Certificates**



[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)

Shipping Approval



other

[Confirmation](#)

[PROFINET-Certification](#)

[PROFISafe-Certification](#)



Profibus

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mfb=3UF79330BA000>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3UF79330BA000>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mfb=3UF79330BA000&lang=en

