

Product no.: TZ150 grün

Current version: 2.0.0, issued: 10.09.2014 Region: 1.0.0, issued: 02.09.2014 Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

Boardmarker refill ink 119904 contained in: TZ 150

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Refilling ink

1.3 Details of the supplier of the safety data sheet

Address

LegaMaster GmbH Kwinkweerd 62 Postbus 111

7240 AC Lochem

Netherlands

Telephone no. +31 (0) 573-713000 Information provided by / telephone +31 (0) 573-713000

Advice on Safety Data Sheet

sdb_info@umco.de

1.4 Emergency telephone number

For medical advice (in German and English): +49 (0)30 30686 790 (Giftnotruf Berlin)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Eye Dam. 1; H318 Flam. Liq. 2; H225 STOT SE 3; H336

Classification in accordance with Directive 67/548/EEC or 1999/45/EC

F; R11 R67 Xi; R41

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms



GHS02



GHS05



2 GHS

Signal word Danger

Hazardous component(s) to be indicated on label:

propan-1-ol

Hazard statements

H225 Highly flammable liquid and vapour.
 H318 Causes serious eye damage.
 H336 May cause drowsiness or dizziness.



Trade name: Boardmarker refill ink 119904 contained in: TZ 150

Product no.: TZ150 grün

Current version: 2.0.0, issued: 10.09.2014 Region: 1.0.0, issued: 02.09.2014 Region: GB

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smokina.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P370+P378 In case of fire: Use water spray, extinguishing powder, foam or CO2 for extinction.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local and national regulations.

2.3 Other hazards

No data available.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures

Chemical characterization

Mixture (preparation)

Hazardous ingredients

No	Substance name			Additional information	
	CAS / EC / Index /	Classification	Classification (EC)	Concentration	%
	REACH no	67/548/EEC	1272/2008 (CLP)		
1	propan-1-ol				
	71-23-8	F; R11	Eye Dam. 1; H318	> 50.00 - < 100.00	%-b.w.
	200-746-9	Xi; R41	Flam. Liq. 2; H225		
	603-003-00-0	R67	STOT SE 3; H336		
	-				
2	propan-2-ol				
	67-63-0	F; R11	Eye Irrit. 2; H319	> 2.50 - < 10.00	%-b.w.
	200-661-7	Xi; R36	Flam. Liq. 2; H225		
	603-117-00-0	R67	STOT SE 3; H336		
	-				
3	1-methoxy-2-propanol				
	107-98-2	R10	Flam. Liq. 3; H226	> 2.50 - < 10.00	%-b.w.
	203-539-1	R67	STOT SE 3; H336		
	603-064-00-3				
	-				

Full Text for all R-phrases , H-phrases and EUH-phrases: pls. see section 16 $\,$

3.3 Other information

The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

After inhalation

Remove affected person from the immediate area. Ensure supply of fresh air.

After skin contact

Wash off immediately with soap and water.



Trade name: Boardmarker refill ink 119904 contained in: TZ 150

Product no.: TZ150 grün

Current version: 2.0.0, issued: 10.09.2014 Reglaced version: 1.0.0, issued: 02.09.2014 Region: GB

After eye contact

Remove contact lens. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

After ingestion

Do not induce vomiting. Call a doctor immediately. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

No data available.

4.3 Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam; Extinguishing powder; Carbon dioxide; Water spray jet

Unsuitable extinguishing media

High power water jet

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon dioxide (CO2); Carbon monoxide (CO)

5.3 Advice for firefighters

Use self-contained breathing apparatus. Cool endangered containers with water spray jet. Suppress gases/vapours/mists with water spray jet. Wear protective clothing.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep away sources of ignition.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). Send in suitable containers for recovery or disposal.

6.4 Reference to other sections

No data available.

SECTION 7: Handling and storage

.1 Precautions for safe handling

Advice on safe handling

Provide good ventilation of working area (local exhaust ventilation, if necessary). If workplace exposure limits are exceeded, respiratory protection approved for this particular job must be worn. Product inherent handling risks must be minimised taking the appropriate measures for protection and preventive actions. The working process should be designed to rule out the release of hazardous substances or skin contact as far it is possible by the state of the art.

General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Clean skin thoroughly after work; apply skin cream.



Product no.: TZ150 grün

Current version: 2.0.0, issued: 10.09.2014 Region: 1.0.0, issued: 02.09.2014 Region: GB

Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Take precautionary measures against static charges. Keep away from sources of heat and ignition.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight.

Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original one.

Advice on storage assembly

None known

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No	Substance name	CAS no.		EC no.		
1	propan-1-ol	71-23-8		200-746-9		
	List of approved workplace exposure limits (WELs) / E	List of approved workplace exposure limits (WELs) / EH40				
	Propan-1-ol					
	STEL	625	mg/m³	250	ml/m³	
	TWA	500	mg/m³	200	ml/m³	
	Skin resorption / sensibilisation	Sk				
2	propan-2-ol	67-63-0		200-661-7		
	List of approved workplace exposure limits (WELs) / E	H40				
	Propan-2-ol					
	STEL	1250	mg/m³	500	ml/m³	
	TWA	999	mg/m³	400	ml/m³	
3	1-methoxy-2-propanol	107-98-2		203-539-1		
	2000/39/EWG					
	1-Methoxypropanol-2					
	STEL	568	mg/m³	150	ml/m³	
	TWA	375	mg/m³	100	ml/m³	
	Skin resorption / sensibilisation	Skin				
	List of approved workplace exposure limits (WELs) / EH40					
	1-Methoxypropan-2-ol					
	STEL	560	mg/m³	150	ml/m³	
	TWA	375	mg/m³	100	ml/m³	
	Skin resorption / sensibilisation	Sk	_			

8.2 Exposure controls

Appropriate engineering controls

No data available.

Personal protective equipment

Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

Eye / face protection

Safety glasses with side protection shield (EN 166)



Product no.: TZ150 grün

Current version: 2.0.0, issued: 10.09.2014 Replaced version: 1.0.0, issued: 02.09.2014 Region: GB

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Other

Normal chemical work clothing.

Environmental exposure controls

No data available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form/Colour					
liquid					
green					
Odour					
characteristic					
Odour threshold					
No data available					
pH value					
No data available					
Boiling point / boiling range					
Value		82	°C		
Melting point / melting range					
No data available					
Decomposition point / decomposition range					
No data available					
Flash point					
Value		13	°C		
Ignition temperature					
Value		287	°C		
Auto-ignition temperature					
Remarks	Product is not selfi	gniting.			
Oxidising properties					
No data available					
Explosive properties					
This product is not explosive. In and after use danger of production of inflammable compounds.					
Flammability (solid, gas)					
No data available					
Lower flammability or explosive limits					
Value		2.1	% vol		
Upper flammability or explosive limits					
Value		13.5	% vol		
Vapour pressure					
Value		19	hPa		
Reference temperature		20	°C		



Product no.: TZ150 grün

Current version: 2.0.0, issued: 10.09.2014 Reglaced version: 1.0.0, issued: 02.09.2014 Region: GB

Vapour density		
No data available		
Evaporation rate		
No data available		

Relative density

No data available

Density
no data available

Remarks partially miscible

Solubility(ies)
No data available

Partition coefficient: n-octanol/water

No data available

ViscosityValue12 mPa*sReference temperature20 °CTypedynamic

Value 80.8 %

Solids contentValue1.6%

9.2 Other information

Other information

No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available.

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

No data available.

10.4 Conditions to avoid

No data available.

10.5 Incompatible materials

No data available.

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute oral toxicity					
No	Substance name	CAS no.		EC no.	
1	1-methoxy-2-propanol	107-98-2		203-539-1	
LD50			5660	mg/kg bodyweight	
Species		rat			
Source		Manufacturer			



Trade name: Boardmarker refill ink 119904 contained in: TZ 150

Product no.: TZ150 grün

Current version: 2.0.0, issued: 10.09.2014 Replaced version: 1.0.0, issued: 02.09.2014 Region: GB

Acute dermal toxicity						
No	Substance name	CAS no.		EC no.		
1	1-methoxy-2-propanol	107-98-2		203-539-1		
LD50			9999.99	mg/kg bodyweight		
Species		rabbit				
Source		Manufacturer				

Acute inhalational toxicity

No data available

Skin corrosion/irritation

No data available

Serious eye damage/irritation

No data available

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Reproduction toxicity

No data available

Carcinogenicity

No data available

STOT-single exposure

No data available

STOT-repeated exposure

No data available

Aspiration hazard

No data available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Inhalation of solvent vapours in higher concentration may lead to nausea, headache, drowsiness and dizziness. Repeated and prolonged skin contact may cause removal of natural fat from the skin and irritation of the skin. Eye contact with the product may lead to irritation.



Trade name: Boardmarker refill ink 119904 contained in: TZ 150

Product no.: TZ150 grün

Current version: 2.0.0, issued: 10.09.2014 Reglaced version: 1.0.0, issued: 02.09.2014 Region: GB

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish (acute)

No data available

Toxicity to fish (chronic)

No data available

Toxicity to Daphnia (acute)

No data available

Toxicity to Daphnia (chronic)

No data available

Toxicity to algae (acute)

No data available

Toxicity to algae (chronic)

No data available

Bacteria toxicity

No data available

12.2 Persistence and degradability

No data available.

12.3 Bioaccumulative potential

No data available.

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Other adverse effects

No data available.

12.7 Other information

Other information

Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Packaging

Residuals must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.



Product no.: TZ150 grün

Current version: 2.0.0, issued: 10.09.2014 Reglaced version: 1.0.0, issued: 02.09.2014 Region: GB

SECTION 14: Transport information

14.1 Transport ADR/RID/ADN

Class 3
Classification code F1
Packing group II
Hazard identification no. 33
UN number UN1263

Technical name PAINT RELATED MATERIAL

Special Provision 640 640D Tunnel restriction code D/E Label 3

14.2 Transport IMDG

Class 3
Packing group II
UN number UN1263

Proper shipping name PAINT RELATED MATERIAL

EmS F-E+S-E

Label 3

14.3 Transport ICAO-TI / IATA

Class 3 Packing group II UN number UN1263

Proper shipping name Paint related material

Label 3

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

No data available.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU regulations</u>

Council Directive 96/82/EC on the control of major-accident hazards involving dangerous substances

Remarks Annex I, part 2, category 7 b

15.2 Chemical safety assessment

No data available.

SECTION 16: Other information

Sources of key data used to compile the data sheet:

EC Directive 67/548/EC resp. 1999/45/EC as amended in each case.

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

EC Directives 2000/39/EC, 2006/15/EC, 2009/161/EU

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding chapter.



Trade name: Boardmarker refill ink 119904 contained in: TZ 150

Product no.: TZ150 grün

Current version: 2.0.0, issued: 10.09.2014 Region: 1.0.0, issued: 02.09.2014 Region: GB

Full text of the R-, H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these

sections)

R10 Flammable.
R11 Highly flammable.
R36 Irritating to eyes.

R41 Risk of serious damage to eyes.

R67 Vapours may cause drowsiness and dizziness.

H225
Highly flammable liquid and vapour.
H226
H318
H319
Causes serious eye damage.
H336
May cause drowsiness or dizziness.

Department issuing safety data sheet

UMCO Umwelt Consult GmbH

Georg-Wilhelm-Str. 183, D-21107 Hamburg

Tel.: +49 40 / 79 02 36 300 Fax: +49 40 / 79 02 36 357 e-mail: umco@umco.de

This information is based on our present state of knowledge and experience.

The security data sheet describes products with a view to the security requirements.

However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.