

Section 1. Product and Company Identification.

1.1 Model Number; SCS300 v1

1.2 Description; Super Glue Activating Aerosol 200ml Pack of 6

1.3 Manufacturer;

Sealey Group. Kempson Way, Bury St. Edmunds, Suffolk. IP32 7AR

1.4 Emergency telephone number; 44 (0) 1284 757 500 (Office Hours)

Date of source compilation; 20 October 2013



Section 2. Hazards Identification.

2.1 Classification of the substance or mixture.

Contains:

Butane, Low Boiling Point Hydrogen Treated Naphtha – Naphtha (Petroleum). Hydrotreated Light.

2.2 Label elements.

Hazard pictogram(s)



Signal Word. Danger

Hazard statements;

H222: Extremely flammable aerosol.

H315: Causes skin irritation.

H411: Toxic to aquatic life with long lasting effects.

Precautionary statements;

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P211 Do not spray on an open flame or other ignition source.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P251 Pressurized container: Do not pierce or burn, even after use.

P264 Wash contaminated skin thoroughly after handling.

P273 Avoid release to the environment.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P332 + P313 If skin irritation occurs: Get medical advice/attention.

P410 Protect from sunlight.

P412 Do not expose to temperatures exceeding 50°C.

P501 Dispose of contents/container to comply with Local, National and International regulations.

2.3 Other hazards.

In use, may form flammable / explosive vapour-air mixture.



Section 3. Substances.

			Classification		
3.1 Chemical Name (substance)	3.1 CAS No.	3.2 Concentration Volume	Hazard Class & Category Code	Hazard Statements ¹	
BUTANE	106-97-8	20 – 35 %	Flam. Gas 1 Press. Gas	H220	
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT	64742-49-0	20 - 35 %	Carc. 1B Asp. Tox. 1	H350 H304	
N,N-DIMETHYL-P-TOLUIDINE	99-97-8	< 1 %	Acute Tox. 3 Acute Tox. 3 Acute Tox. 3 STOT RE 2 Aquatic Chronic 3	H331 H311 H301 H373 H412	

¹For full text of Phrases and Statements, see Section 16.

Section 4. First Aid Measures.

General information

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

4.1 Description of first aid measures

Eye Contact

Make sure to remove any contact lenses from the eyes before rinsing.

Promptly wash eyes with plenty of water while lifting the eye lids.

Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

Skin Contact

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

Ingestion

DO NOT INDUCE VOMITING! Rinse mouth thoroughly with water and give large amounts of milk or water to people not unconscious. Get medical attention if any discomfort continues.

Inhalation

Move the exposed person to fresh air at once.

Keep the affected person warm and at rest. Get prompt medical attention.

- **4.2.** Most important symptoms and effects, both acute and delayed No data available.
- **4.3.** Indication of any immediate medical attention and special treatment needed No data available.



Section 5. Fire Fighting Measures.

5.1. Extinguishing media

Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

5.2. Special hazards arising from the substance or mixture

Aerosol cans may explode in a fire.

5.3. Advice for fire-fighters

Containers close to fire should be removed or cooled with water.

Use water to keep fire exposed containers cool and disperse vapours.

Section 6. Accidental Release Measures.

6.1. Personal precautions, protective equipment and emergency procedures

H222: Extremely flammable aerosol.

H315: Causes skin irritation.

H411: Toxic to aquatic life with long lasting effects.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P211 Do not spray on an open flame or other ignition source.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P251 Pressurized container: Do not pierce or burn, even after use.

P264 Wash contaminated skin thoroughly after handling.

P273 Avoid release to the environment.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P332 + P313 If skin irritation occurs: Get medical advice/attention.

P410 Protect from sunlight.

P412 Do not expose to temperatures exceeding 50°C.

P501 Dispose of contents/container to comply with Local, National and International regulations.

6.2. Environmental precautions

H411: Toxic to aquatic life with long lasting effects.

6.3. Methods and material for containment and cleaning up

Wear necessary protective equipment. Extinguish all ignition sources.

Avoid sparks, flames, heat and smoking.

Ventilate.

Let evaporate.

Keep out of confined spaces because of explosion risk.

If leakage cannot be stopped, evacuate area.

6.4. Reference to other sections

See Section 7 for information on Safe Handling

See Section 8 for information of Personal Protective Equipment.

See Section 13 for information on disposal.



Section 7. Handling and Storage.

7.1. Precautions for safe handling

Keep away from heat, sparks and open flame.

Avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

Avoid direct contact with the substance.

Ensure there is sufficient ventilation of the area.

Do not handle in a confined space.

Avoid the formation or spread of mists in the air.

Smoking is forbidden.

Use non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

Store in cool, well-ventilated area.

Keep container tightly closed. Keep away from sources of ignition.

Prevent the build-up of electrostatic charge in the immediate area.

Ensure lighting and electrical equipment are not a source of ignition.

7.3. Specific end use(s)

No data available

Intended for use as Super Glue Activating Aerosol: Model Number identified in 1.1 with Description stated in 1.2.



Section 8. Exposure Controls/Personal Protection.

8.1. Control parameters

Workplace exposure limits.

		Workplace exposure limit.			
Substance	CAS number	Long term.		Short term.	
		ppm	mg.m ³	ppm	mg.m ³
BUTANE	106-97-8	600	1450	750	1810

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P211 Do not spray on an open flame or other ignition source.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P251 Pressurized container: Do not pierce or burn, even after use.

P264 Wash contaminated skin thoroughly after handling.

P273 Avoid release to the environment.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P332 + P313 If skin irritation occurs: Get medical advice/attention.

P410 Protect from sunlight.

P412 Do not expose to temperatures exceeding 50°C.

P501 Dispose of contents/container to comply with Local, National and International regulations.

8.2. Exposure controls

Appropriate Engineering Controls

Ventilation

Provide adequate general and local exhaust ventilation.

Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

Eye/Face Protection

Use chemical resistant safety goggles or face shield.

Skin Protection

Use solvent resisting protective gloves.

Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Respiratory Protection

Use chemical cartridge protection with appropriate cartridge.



Section 9. Physical and Chemical Properties.

9.1. Information on basic physical and chemical properties

The following information is not a technical specification or sales specification.

(a) Appearance: Colourless aerosol.

(b) Odour: Aromatic.

(c) Odour threshold; No data available.

(d) pH: Not relevant. (e) Melting point/freezing point; Not relevant.

Not relevant.

(f) Initial boiling point and boiling range;

(g) Flash point; -5°C

(h) Evaporation rate; No data available.

(i) Flammability (solid, gas); No data available.

(j) Upper/lower flammability or explosive limits; No data available. No data available.

(k) Vapour pressure; (I) Vapour density; No data available.

(m) Relative density; 0.71

(n) Solubility(ies); No data available.

(o) Partition coefficient: n-octanol/water; No data available.

(p) Auto-ignition temperature; No data available.

(q) Decomposition temperature; No data available.

(r) Viscosity; Not relevant.

(s) Explosive properties; No data available.

(t) Oxidising properties. No data available.

No data available. 9.2 Other information



Section 10. Stability and Reactivity.

10.1. Reactivity Stable under recommended transport or storage conditions.

10.2. Chemical stability Stable under normal conditions. Stable at room

temperature.

10.3. Possibility of hazardous reactions Hazardous reactions will not occur under normal transport

or storage conditions.

Decomposition may occur on exposure to conditions or

materials listed below.

10.4. Conditions to avoid Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials10.6. Hazardous decomposition productsStrong oxidising agents. Strong acids.In combustion emits toxic fumes.

Section 11. Toxicological Information.

11.1. Information on toxicological effects

Hazardous ingredients.

N, N-DIMETHYL-P-TOLUIDINE

IPR	MUS	LD50	212	mg/kg
-----	-----	------	-----	-------

Relevant effects for mixture:

Effect	Route	Basis
Irritation	DRM	Hazardous: Calculated

Symptoms / routes of exposure

Skin contact:

There may be irritation and redness at the site of contact.

Eye contact:

There may be irritation and redness. The eyes may water profusely.

Ingestion:

There may be soreness and redness of the mouth and throat.

Inhalation:

There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects:

Immediate effects can be expected after short-term exposure.



Section 12. Ecological Information.

12.1. ToxicityNo data available.12.2. Persistence and degradabilityNo data available.12.3. Bioaccumulative potentialNo data available.12.4. Mobility in soilNo data available.

12.5. Results of PBT and vPvB assessment Not identified as a PBT substance.

12.6. Other adverse effects No data available.

Section 13. Disposal Considerations.

13.1. Waste treatment methods

Dispose of in accordance with local authority requirements.

Section 14. Transport Information.

ADR. International Carriage of Dangerous Goods by Road.

14.1. UN number UN 1950

14.2. Name and Description AEROSOLS, flammable

14.3. Transport hazard class(es) 2 **14.4.** Packing group -

14.5. Environmental hazards Toxic to aquatic life with long lasting effects.

14.6. Special precautions for user No special precautions necessary.

IATA. International Air Transport Association.

14.1. UN number UN 1950

14.2. UN Proper Shipping Name/Description AEROSOLS, flammable

14.3. Transport hazard class(es) Division 2.1

14.4. Packing group -

14.5. Environmental hazards Toxic to aquatic life with long lasting effects.

14.6. Special precautions for user No special precautions necessary.

IMDG. International Maritime Dangerous Goods.

14.1. UN number UN 1950

14.2. UN proper shipping name AEROSOLS, flammable

14.3. Transport hazard class(es) 2 **14.4.** Packing group -

14.5. Environmental hazards Toxic to aquatic life with long lasting effects.

14.6. Special precautions for user No special precautions necessary.

14.7. Transport in bulk – Maritime only. Bulk transport is not applicable to this product



Section 15. Regulatory Information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture No data available.

15.2. Chemical safety assessment No data available.

Section 16. Additional Information.

Full text of Phrases and Statements used in Section 3;

H220 Extremely flammable gas.

H301 Toxic if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H331 Toxic if inhaled.

H350 May cause cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

The above information is believed to be accurate and represents the best information currently available.

No warranty is expressed or implied by the above information.

We assume no liability resulting from use of the above information.

The end user should conduct their own investigations to determine the suitability of the above information for their particular purpose.

Issue level	Date	Revisions
1	15/04/16	First issue.
2	16/09/16	Sections 3.2, 14 & 15.
3	28/05/19	Sections 2, 6, 8 and 13.

End of Safety Data Sheet.