

## **GENERAL PRODUCT SPECIFICATION**

Date	3-27-07	Replaces	5-31-06	No. Pages	1

**Product Description:** 

Item No.

GP100-M

Style	Pads; perforated on centerline for dividing in half for smaller applications			
Item Size (each)	41 cm x 51 cm			
Color	Gray			
Composition	Polypropylene >98%, Surfactant < 1.0%, color pigment < 0.1 %			
Structure	A nonwoven mat of randomly oriented Micro-fibers [2-10 micron diameters]			
Technology	Meltblown			
Absorbency	Universal ( <b>Hydrophilic</b> + Oleophilic)			
Bonding	Bonded (staggered pattern) + Mechanical entanglement			

Intended Application	Chemical Resistant Sorbent for Water, Oil, or Solvent Base Liquids

<b>Absorbency Capacity</b>	95 l per box (saturated; medium viscosity-14x)
----------------------------	--

**Packaging Description:** 

Package configuration	Case	Pkg. Weight	7,1 kg (5,9kg)
Items per Package	100-Pads/Case	Pkg. Dimensions	53cm x 43cm x
			44cm H
Container type	Carton		

## **Physical Properties**;

<u>Parameter</u>	SPC Test Method	<u>Units</u>	Nominal	(+/-)Tolerance
Basis Weight	SPCTM-002A	G/M2	280	28
Caliper	SPCTM-020	mm	5	0.5
Absorbency ** (med. Oil)	SPCTM-004B	gL/gS	14	2
Tensile strength	SPCTM-007	daN	6,3	0.6
Color	Visual		Gray	per standard

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped. \*\* The "Absorbency" Spec and "SPCTM004" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.
Labeling	Each package to be clearly labeled with Company Name, Address, Item No.,
	Date, and/or Package Code (Bar Code).
Certification	Make no changes in basic process or composition without notifying customer.
	Claims for non-conformance of goods must be made within 60-days of delivery.