

MATERIAL SAFETY DATA SHEET

Reference No......: WTX21D10116671B002

Applicant.....: SYSMAX Innovations Co., Ltd.

Address...... : Rm 2601-06, Central Tower, NO.5 Xiancun Road, Tianhe District,

Guangzhou, 510623, Guangdong, China

Manufacturer.....: Sysmax Power Technology.LLC

Address.....: B4 Happy Factory, 81 East Huahong Commercial Street, North Zhenxing

Road, Gaobu Dongguan, China

Sample's name......: Power station

Date of Issue.....: 2022-01-05

Prepared By:

Waltek Testing Group Co., Ltd.

Address: No. 77, Houjie Section, Guantai Road, Houjie Town, Dongguan City, Guangdong, China

Tel:+86-769-2267 6998

Fax:+86-769-2267 6828


Compiled by:

Jason Zhen / Project Engineer

Approved by:

Deval Qin / Designated Reviewer

Devalgin





Material Safety Data Sheet

Section 1-Chemical Product and Company Identification

Product Name:	Power station	
Model No.:	NPS600	
Ratings	10.8V, 55Ah, 594Wh	
Weight:	Approx. 5.86Kg	
Manufacturer:	Sysmax Power Technology.LLC	
Address:	B4 Happy Factory, 81 East Huahong Commercial Street, North Zhenxing Road, Gaobu Dongguan, China	
EmergencyTeleph one:	0769-82660898	
Fax:	0769-82690896	
Email:	525874853@qq.com	

Section 2-Hazards Identification

Classification:	Not dangerous with normal use. Do not dismantle, open or shred battery. The hazards indicated are for a ruptured battery. Exposure to the ingredients contained within or their ingredients products could be harmful.
Appearance, Color and odor	Solid object with no odor, no color.
Invasion route:	ACUTE : see Section 8 for exposure controls In the event that this battery has been ruptured, the electrolyte solution contained within the battery would be corrosive and can cause burns.
	Skin contact: The leakage of the electrolyte may cause sore and stimulation on the skin
	Eye contact : The steam of the electrolyte may stimulate eyes. Especially, substance that may cause inflammation of the eyes is contained
	Inhalation: Inhalation of materials from a sealed battery is not an expected route of exposure. Vapors or mists from a ruptured battery may cause respiratory irritation.
	Ingestion: Swallowing is not anticipated due to the battery size. The ingestion of the electrolyte causes tissue damage to throat
Health hazards:	For the battery or cell, chemical materials are stored in a sealed metal or metal laminated plastic case, which designed to withstand temperatures and pressures encountered during normal use. As a result, during normal use, there is no physical danger of ignition, explosion or leakage of hazardous materials. However, if exposed to a fire, added mechanical shocks or decomposed, these improper handlings would cause the leakage of electrolyte. Moreover, if heated strongly by the surrounding fire, acrid gas may be emitted
Environment hazards:	Electrolyte leakage or battery container rupture may lead to the leakage of inner component into the environment
Burn & burst danger:	Do not dispose of battery in firemay explode. Do not short-circuit the battery—may cause fire



Reference No: WTX21D10116671B002 Page 3 of 7

Section 3 - Composition/information on Ingredient

Pure ☐ Admixture ☒

Chemical Composition	Molecular Formula	CAS No.	Weight (%)	
Lithium Cobalt Oxide	LiCoO ₂	12190-79-3	36	
Aluminum	MAI MAI	7429-90-5	E THE 8 THE	
Graphite	the Comment	7782-42-5	15	
Copper	Cu	7440-50-8	10	
Phosphate(1-), hexafluoro-, lithium	N/A	21324-40-3	10	
Ethylene carbonate	N/A	96-49-1	9	
Other	N/A	N/A	12	

Note: CAS number is Chemical Abstract Service Registry Number.

N/A=Not apply.

Section 4 - First Aid Measure

Skin touch:	Remove all contaminated clothing and flush extraneous matter with soap and plenty of water immediately for at least 15 minutes. Get medical aid.
Eyes touch:	In case of contact electrolyte with eyes, rinse immediately with plenty of water. Have the victims remove contact lenses if he is wearing them before rinsing. Do not let the victims rub his eyes. Get medical aid.
Inhalation:	Remove to fresh air. Give oxygen or artificial respiration if needed. Get medical aid.
Ingestion:	Swallowing is not anticipated in normal condition. If accidentally eat the product, dilute by giving plenty of water and get medical aid. Assure that mucus does not obstruct the airway. Do not give anything by mouth to an unconscious person

Section 5 – Fire Fighting measures

Danger characteristic:	Non-flammable. The batteries can leak combustible electrolyte fumes in case of over heat resulting from inappropriate use.
Hazardous combustion products:	Irritant gas may be emitted if burned or exposed to fire
Hazardous combustion products:	Irritant gas may be emitted if burned or exposed to fire
Fire-Fighting method & media:	The staff must equipped with filter mask (full mask) or isolated breathing apparatus. The staff must wear the clothes and gloves which can defend the fire and the toxic gas. When the battery burns with other combustibles simultaneously, take fire-extinguishing method which correspond to the combustibles. Extinguish a fire from the windward as much as possible
Extinguishant:	Carbon dioxide, dry chemical, foam, etc

Reference No: WTX21D10116671B002 Page 4 of 7

Section 6 - Accidental Release Measures

Personal precautions	Attention! Corrosive material. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.
Other Information	Refer to protective measures listed in section 7 and 8.
Environmental precautions	Refer to protective measures listed in Section 7 and 8. Prevent further leakage or spillage if safe to do so. Should not be released into the environment. Do not allow to enter into soil/subsoil. Prevent product from entering drains.
Methods for containment	Prevent further leakage or spillage if safe to do so.
Methods for cleaning up	Pick up and transfer to properly labeled containers.

Section 7 – Handing and storage

Handing:	Before handling the batteries, the users should read the product specification carefully. Do not crush, pierce the battery terminals with conductive goods. Not directly heat or solder. Do not throw in fire. Do not mix batteries of different types. Do not mix new and used batteries. Keep batteries in non-conductive trays
Storage:	Store batteries in cool and ventilated area away from sources of heat, open flames, corrosive chemicals, food and drink. Since short circuit can cause burn, leakage and rupture, keep batteries in original packaging until use and do not jumble them. Keep away form children

Section 8 – Exposure controls, Personal Protection

Maximum admissible concentration:	No information is available
Monitoring Method:	Use ventilation or other monitoring devices to control temperature, humidity and fumes
Engineering Control:	Use ventilation or other monitoring devices to control temperature, humidity and fumes
Respiratory Protection:	Not necessary under normal use. In case of battery rupture, use self-contained respiratory equipment
Eyes/face Protection:	Not necessary under normal use. Wear safety goggles if handing a leaking or ruptured batteries
Skin and Body protection:	Not necessary under normal use. Use rubber apron and protective clothes in case of handing a leaking or ruptured batteries
Hands Protection:	Not necessary under normal use. Use rubber gloves if handing a leaking or ruptured batteries
Hygiene Measures:	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Contaminate work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. For environmental protection, remove and wash all contaminated protective equipment before re-use.
Other Protections:	None The secretary that the second se



Reference No: WTX21D10116671B002 Page 5 of 7

Section 9 – Physical and Chemical Properties

Physical state:	Solid
Color:	Black
Odor:	Odorless
pH Value:	Not available
Boiling point	Not available
/range	The state of the s
Melting /freezing	Not available
Point:	
Flash point:	Not available
Evaporation	Not available
rate:	The state of the s
Upper	the partie with which and any are the fift that it
flammable(explo	Ned and the last state and state and and and
sive) limits in air-	Not available
Lower (vol%)- UEL:	WAL WALL THE WILL SEE SEE STEE STEEL WITH WITH MILL
	Not available
Vapor pressure:	Not available Not available
Vapor density:	
Specific Gravity:	Not available
Water Solubility:	Immiscible in water
Solubility in other solvents:	Not available
Partition	THE THE THE THE THE WAY WITH THE
coefficient (n-	Not available Not available
octanol / water):	N THE REPORT OF THE REPORT OF THE PARTY OF T
Autoignition	Not available
temperature	Tvot available
Decomposition	Not available
temperature:	Trot dvalidate
Kinematic	Not available
viscosity:	Trot dvallable
Dynamic	Not available
viscosity:	the strain and the st
Explosive	Not available
properties:	the state of the s
Oxidizing	Not available
properties:	
Evaporation rate:	Not available
Ignition	The second secon
temperature:	No information is available
Any addition information:	None None The state of the stat

Reference No: WTX21D10116671B002 Page 6 of 7

Section 10 - Stability and Reactivity

Reactivity:	No data is available
Chemical stability:	Stable under recommended storage condition
Possibility of Hazardous Reactions:	None under normal processing.
Hazardous Polymerization:	No information is available
Conditions to avoid:	Exposure to air or moisture over prolonged periods.
Incompatible materials	Acids, Bases, Oxidizing agent.
Hazardous Decomposition Products:	Irritant gas may be emitted if burned or exposed to fire

Section 11 – Toxicological Information

Acute Toxicity:	No information is available	
Sub-acute and Chronic Toxicity:	Lithium ion batteries do not contain toxic materials	
Irritation:	Irritation only occurs if the batteries are abused and it may cause irritation to skin, eyes, respiratory tract.	
Sensitization:	No information is available	
Mutagenicity:	No information is available	
Carcinogenicity:	No information is available	
Others:	None	

Section 12 - Ecological Information

Eco-toxicity:	When properly used and disposed, lithium iron batteries do not present environment hazard
Biodegradable:	No information is available
Non- biodegradable:	No information is available
Bioconcentration or biological accumulation:	No information is available
Other harmful effects:	None None

Section 13 - Disposal Considerations

Nature of waste:	No information is available
Waste disposal methods:	Dispose in accordance with applicable regulations which vary from country to country. In more countries the discard of used batteries is forbidden and the endusers are invited to dispose them properly. Lithium ion battery should have their terminals insulated and be preferably wrapped in plastic bags prior to disposal
Contaminated Packaging:	Dispose of contents/containers in accordance with local regulations.
Attention abandoned:	Incineration should never be performed by battery user

Waltek Testing Group Co., Ltd. http://www.waltek.com.cn

Reference No: WTX21D10116671B002 Page 7 of 7

Section 14 - Transport information

Note: Education of the control of th	This report applies to transportation of by air、by sea and by road. The Power station NPS600 has passed the test Section 38.3 of Recommendations on the Transport of Dangerous Goods, Manual of Test and Criteria. Report No.: WTX19S11082540B001
	The transportation of lithium cells and batteries is regulated by the International Civil Aviation Organization, International Air Transport Association, International Maritime Dangerous Goods Code.
	When shipped by air, package should according to packing instruction 965~967 of IATA DGR 63rd Edition for transportation.
	When shipped by sea, package should according to packing instruction P903 of IMDG CODE 40-20 Edition for transportation.
	When shipped by road, package should according to packing instruction P903 of Euro pean Agreement concerning the International Carriage of Dangerous Goods by Road (ADR) for transportation.
UN Number:	3480
Class:	9
Packing group:	II all the state of the state of the state of
Proper shipping name:	Lithium-ion batteries shipping singly
Packaging Mark:	Each package must be labeled with a lithium battery label.
Packaging Method:	No information is available
Transport Fashion:	By air /By sea/By road
Transport Attentions:	Examine whether the package of the containers are integrate and tight-closed or not before transport. No divulgence, no collapse, no precipitation or no damage during the course of transportation. Don't put the goods together with corrosive chemicals. Stopovers should be away from fire and heat sources

Section 15 – Regulatory Information		
Regulatory Information:	ISO 11014-2009 Safety data sheet for chemical products – Content and order of sections.	
	GB/T 16483-2008 Safety data sheet for chemical products – Content and order of sections The international Maritime Dangerous Goods (IMDG) Code International Air Transport Association (IATA) Dangerous Goods Regulations, 63rd, 2022	
	The European Agreement concerning the International Carriage of Dangerous Goods by Road (ADR)	
	The Regulations Concerning the International Transport of Dangerous Goods by Rail (RID)	
	U.S. Department of Transportation (DOT)	
	Globally Harmonized System of Classification and Labeling of Chemicals (GHS)	

Section 16 - Additional Information

made available subsequent to the data hereof may suggest modifications of the information, we do not assume any responsibility for the result of its use. This	Additional Information:	information, we do not assume any responsibility for the result of its use. This information is furnished upon condition that the person receiving it shall make his
----------------------------------------------------------------------------------------------------------------------------------------------------------------	-------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------

===== End of Report =====