Electro Mechanical Indicator

Features

•

White in colour

Fitted with flying leads

Panel or base flange mounted Housing material: ABS

multicomp PRO


RoHS Compliant



Specifications

Rated Voltage	: 6V DC	
Operating Voltage	: 4V DC to 8V DC	
Rated Current*	: ≤33mA	
Sound output at 30cm*	: ≥95dB	
Resonant Frequency	: 400 ±100Hz	
Tone	: Single	
Operating Temperature	: -20°C to +60°C	
Storage Temperature	: -30°C to +70°C	
Lead Material	: UL1007 AWG28	
Weight	: 17g	
*Value applying at rated voltage (DC)		

Diagram



Dimensions : Millimetres Tolerance : ±0.5mm

Part Number Table

Description	Part Number
Electro Mechanical Indicator, 6V DC	ABI-048-RC

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro

