

DYMO®

LabelManager™ 160



CREATE LABELS FAST WITH SMART KEYS

Just type your text, format it with one-touch smart keys and print!
It's easy to create professional labels in and around the office.

Features

- Large LCD Display
- Computer-style keyboard
- One-touch Smart Keys for fast formatting
- 20+ ways to form text
- 200+ symbols and clip-art images
- Print up to 1/2 in (12mm) wide labels
- Powered by 6xAAA alkaline batteries (not included) or optional adapter



Single Unit Includes:

- LabelManager 160
- D1 Starter Label Cassette, 12mm x 3m Black on White
- Quick Start Guide
- 2 + 1 - Year Limited Warranty*



Quick Specs

| | |
|-----------------------------|---------------------------------|
| Unit Dimensions (H x W x L) | 118 x 203 x 49 mm |
| Weight (excluding battery) | 350 g |
| Mac®/PC Compatible | No |
| Accepts Label Sizes | 6mm, 9mm and 12mm |
| Tape Platform | D1, Durables |
| Resolution | 180 dpi |
| Printing System | Thermal Transfer |
| Print Speed | 12 mm/sec |
| Barcodes | No |
| Cutter Type | Manual |
| Batteries | 6 AAA (not included) |
| Adapter | Yes (optional, sold separately) |
| Networking | No |
| Country of Origin | China |


| Item Number | Description | Unit | Length (cm) | Width (cm) | Height (cm) | QTY | EAN | Customer Price |
|-----------------------------------|-------------------------|------|-------------|------------|-------------|-----|---------------|----------------|
| S0946320 | LabelManager 160 QWERTY | Unit | 6.5 | 16.0 | 26.5 | 1 | 3501170946329 | |
| Accessories (www.dymo.com) | | | | | | | | |
| S0721440 | Charging Adapter | Unit | 11.5 | 6.0 | 9.0 | 1 | - | |

* +1 year if registered on the Dymo website

D1 Standard Polyester Labels

For hundreds of tasks around the office or home office, such as filing, storage and asset tracking.
Temperature rating: -18°C to 90°C

| D1 STANDARD LABELS (3 m) | 6 mm | 9 mm | 12 mm |
|------------------------------|----------|----------|----------|
| ABC | - | - | 2084349 |
| ABC | - | - | 2084401 |
| D1 STANDARD LABELS (7 m) | 6 mm | 9 mm | 12 mm |
| ABC | S0720780 | S0720680 | S0720530 |
| ABC | S0720770 | S0720670 | S0720500 |
| ABC | S0720790 | S0720730 | S0720580 |
| ABC | - | S0720710 | S0720560 |
| ABC | - | S0720740 | S0720590 |
| ABC | - | S0720720 | S0720570 |
| ABC | - | - | S0720610 |
| ABC | - | S0720690 | S0720540 |
| ABC | - | - | S0720510 |
| ABC | - | - | S0720600 |
| ABC | - | S0720700 | S0720550 |
| ABC | - | - | S0720520 |
| D1 STANDARD MULTIPACKS (7 m) | 6 mm | 9 mm | 12 mm |
| ABC | - | 2093096 | 2093097 |



D1 Durable Vinyl Labels

Industrial strength adhesive helps to ensure labels stay stuck to a variety of surfaces.
Temperature rating: -40°C to 80°C

| D1 DURABLE LABELS (3 m) | 12 mm |
|---------------------------|---------|
| ABC | 1978366 |
| ABC | 1978365 |
| ABC | 1978367 |
| D1 DURABLE LABELS (5.5 m) | 12 mm |
| ABC | 1978364 |



D1 Permanent Polyester Labels

Professional, polished finish ideal for panels, blocks, faceplates, shelves, bins and more.
Temperature rating: -40°C to 150°C*

| D1 PERMANENT POLYESTER (5.5 m) | 12 mm |
|--------------------------------|----------|
| ABC | S0718060 |

*depends on surface



D1 Flexible Nylon Labels

Specifically designed for curved surfaces and wire and cable marking.
Temperature rating: -40°C to 60°C

| D1 FLEXIBLE NYLON (3.5 m) | 12 mm |
|---------------------------|----------|
| ABC | S0718040 |



The DYMO high quality labels are made in Belgium



This information is being provided for general information purposes and the compliance standards and certifications referenced herein are based on current standards which are subject to change.

