

**Industrial Ethernet
IE-C5ED8UG0400A44A44-X**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Industrial Ethernet connection technology by Weidmüller offers the optimal solution for the infrastructure of your machine, system or factory. All connection technology is available from one source.

The benefits for you:

- IEC-standardised connectors, in the variants 1, 4, 5 , 6 and 14
- Cat. 6 throughout_A with **STEADYTEC®** technology
- pre-assembled cables and cables sold by the metre
- Copper and fibre-optic cables
- in IP20 and IP67
- all relevant industrial connections: RJ45, M12, SC, ...
- comprehensive range of accessories

General ordering data

Type	IE-C5ED8UG0400A44A44-X
Order No.	1347700000
Version	Dragline cable, RJ45 IP 67 PushPull V04 plastic, RJ45 IP 67 PushPull V04 plastic, Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B), PUR, 40 m
GTIN (EAN)	4050118152302
Qty.	1 pc(s).

Industrial Ethernet IE-C5ED8UG0400A44A44-X

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technische Daten

Dimensions and weights

Length	40 m	Net weight	2,273.2 g
--------	------	------------	-----------

Temperatures

Operating temperature	-40 °C...+80 °C	Storage temperature	-40 °C...+80 °C
Installation temperature	-20 °C...+60 °C		

Electrical properties

Insulation resistance	500.000 Ω	Operating voltage	100 V
-----------------------	-----------	-------------------	-------

Standards

Impervious to smoke	According to IEC 61034-2	Standard, assembly	UL-Style 20963 (80°C/30V)
Standard, insulating material	DIN EN 50290-2-25 (HD 624.5)	Standard, wire material	DIN EN 13602 Cu-ETP-A
Standard, shielding material	DIN EN 13602 Cu-ETP-A..B		

Cable structure

Wire material	Stranded tin-plated copper wire	Standard designations	LI9Y(ST)C11Y 4X2X0.14 VZN GN, SF/UTP
Strands	7	Cross-section	4*2*AWG 26/7 - 4*2*0.128 mm ²
Insulation cross-section	0.95 mm	Wire core insulation thickness	0.23 mm
Arrangement of wire cores	Twisted pair	Diameter of wire pair	1.9 mm
Colour sequence or wires - wire pairs	white/blue - blue, white/ orange - orange, white/ green - green, white/ brown - brown	Filler	As central element, Between the individual wire pairs
Shielding	SF/UTP	Complete shielding	Plastic foil, Aluminium foil, Shielding braid made from copper wiring
Shielding braid thickness	0.1 mm	Overlap of shielding braid	90 %
Material sheath	PUR	Sheath diameter, min.	6.3 mm
Sheath diameter, max.	6.8 mm	Sheathing material thickness	0.85 mm
Sheathing colour	green (RAL 6018)		

Electrical properties of cable

Category	Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B)	Operating voltage	100 V
Operating voltage, UL	30 V	Test voltage: wire-wire-shield, at RMS 50Hz, 1 min.	700 V
Characteristic impedance	100 ± 5 Ω at 100MHz	Loop resistance	270 Ω/km
Deviation	40 ns/100m	Resistance differential	2 %
Transfer impedance	100 mΩ/m at 10 MHz	Insulation resistance	500.000 Ω
Capacity at 800 Hz	50 nF/km	Signal propagation time	5.55 ns/m

Industrial Ethernet IE-C5ED8UG0400A44A44-X

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technische Daten

Mechanical and material properties of cable

Min. bending radius, once only	4 *diameter	Min. bending radius, repetitive	7.5 *diameter
Pulling force	≤ 100 N	Speed	180 m/min
Acceleration	5 m/s ²	Torsion resistance	30 °/m
Abrasion resistance	very good	Resistance to spread of flame	in accordance with IEC 60332-1
Resistance to oils	in accordance with IEC 60811-2-1	UV-resistant	Yes
Silicone-free	Yes	Halogen	halogen-free, according to IEC 60754-2
Impervious to smoke	According to IEC 61034-2	Fire propagation	No

plug

Version connector left	RJ45 IP 67 PushPull V04 plastic	Version connector right	RJ45 IP 67 PushPull V04 plastic
------------------------	---------------------------------	-------------------------	---------------------------------

Classifications

eClass 6.2	27-14-91-90
------------	-------------