

Coaxial Cable Connector 24_QMA-50-2-1/111_N

Description

Straight bulkhead cable feed through

Interface standards
QMA QLF compliant



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 6 GHz

Mechanical Data

Centre contact plugged
Outer contact soldered
Weight 0.0041 kg

Environmental Data

Operating temperature -40 °C to 85 °C
2011/65/EU (RoHS - including
2015/863 and 2017/2102) compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Brass	SUCOPRO Plating
Body	Brass	SUCOPRO Plating
Insulator	PFA / PTFE	
Gasket	VMQ (Silicone rubber)	
Fastening nut	Brass	SUCOPRO Plating
Washer	Bronze	SUCOPRO Plating

Related Documents

Outline drawing DOU-00009765
Catalogue drawing DCA-00009767
Assembly instruction DOC-0000389604
Mounting hole DOU-00008748

Ordering Information

Single package 24_QMA-50-2-1/111_NE
Bulk 100 pcs package 24_QMA-50-2-1/111_NH

Additional Information

Suitable cables SUCOFORM_86, EZ_86_TP_M17, MULTIFLEX_86