

## Product/Process Change Notification

### PCN-082322-AGA Auto

Dielectric material formulation change.

<b>Date:</b>	<b>ID Number (MMDDYY):</b> 082322										
<b>Affected Products</b>	<b>Product Line:</b> X7R		<b>Case Size:</b> 0805		<b>Cap:</b> 106 (10.0µF)						
	<b>Voltage:</b> 10V & 6.3V		<b>Tolerances:</b> All		<b>C-spec's:</b> AUTO, 3123, 3124, 3020, 3083						
	<b>Grade:</b> Automotive		<b>Termination:</b> 100% Sn & Flexible Termination Automotive								
<b>Change</b>											
KEMET has improved its dielectric material formulation ensuring additional supply of MLCCs to meet increasing customer demand. Qualification testing has been performed in accordance with the requirements of AEC Q200.											
<b>Standard Termination</b>											
Part Type	Length (mm)		Width (mm)		Thickness (mm)		DF (Max %)		IR MIN (Mohm)		pcs / reel (7in / 13in)
	Current	Planned	Current	Planned	Current	Planned	Current	Planned	Current	Planned	
0805 X7R 10µF 10V	2.0±0.30	2.0±0.30	1.25±0.20	1.25±0.20	1.25±0.20	1.25±0.20	10%	10%	10	10	2,500 / 10,000
0805 X7R 10µF 6.3V	2.0±0.30	2.0±0.30	1.25±0.20	1.25±0.20	1.25±0.20	1.25±0.20	10%	10%	10	10	2,500 / 10,000
<b>Flexible Termination</b>											
Part Type	Length (mm)		Width (mm)		Thickness (mm)		DF (Max %)		IR MIN (Mohm)		pcs / reel (7in / 13in)
	Current	Planned	Current	Planned	Current	Planned	Current	Planned	Current	Planned	
0805 X7R 10µF 10V	2.0±0.35	2.0±0.35	1.25±0.30	1.25±0.30	1.25±0.20	1.25±0.25	10%	10%	10	10	2,500 / 10,000
0805 X7R 10µF 6.3V	2.0±0.35	2.0±0.35	1.25±0.30	1.25±0.30	1.25±0.20	1.25±0.25	10%	10%	10	10	2,500 / 10,000
<b>Ordering Information</b>											
<b>C</b>	<b>0805</b>	<b>C</b>	<b>106</b>	<b>K</b>	<b>8</b>	<b>R</b>	<b>A</b>	<b>C</b>	<b>AUTO</b>		
<b>Cer</b>	<b>Case Size (LxW)</b>	<b>Specification / Series</b>	<b>Capacitance Code (pF)</b>	<b>Capacitance Tolerance</b>	<b>Rated Voltage (VDC)</b>	<b>Diel.</b>	<b>Failure Rate/ Design</b>	<b>Termination Finish</b>	<b>Packaging/ Grade (C-Spec)</b>		
	0805	C= Standard X= Flexible Termination	Two significant digits + number of zeros.	J = ±5% K = ±10% M = ±20%	9 = 6.3V 8 = 10V	R = X7R	A= N/A	C=100% Sn	AUTO = 7in T&R Automotive Grade		
<b>Effective Date and Identification</b>		<i>Beginning implementation Date</i> <b>02/27/23</b>									

<b>To Obtain Samples or General Information Contact</b>	Ana Garza Technical Product Engineer   Ceramic Product Business Unit KEMET Electronics Corporation <a href="mailto:Ana.Garza@yageo.com">Ana.Garza@yageo.com</a>  Craig Scruggs Director Product Management – Automotive Ceramics   Ceramic Product Business Unit KEMET Electronics Corporation <a href="mailto:Craig.Scruggs@yageo.com">Craig.Scruggs@yageo.com</a>
---	---

**KEMET Proprietary Information**  
Entire Contents not to be shared without express written consent of KEMET Electronics Corporation.