

### Product data sheet uvex silv-Air 5220+ FFP2 NR D with Carbon



#### Product information

<b>Product features</b>	<ul style="list-style-type: none"><li>• Particle-filtering folding mask with exhalation valve</li><li>• Protection level FFP2</li><li>• Ergonomically adapted for large face shapes</li><li>• Innovative design with optimized shape</li><li>• Soft material edges for high wearing comfort</li><li>• Continuous head band (adjustable) for a comfortable and secure fit</li><li>• The masks are individually packed</li><li>• Exhalation valve reduces breathing resistance and build-up of heat and moisture in the mask</li><li>• Flexible and adjustable nose clip</li><li>• Compatible with uvex safety eyewear</li><li>• Soft sealing lip (nose area) guarantees a secure, comfortable sealed position of the mask</li><li>• Activated carbon filter for odors, gases and vapors below limit value</li><li>• Mask fulfils the requirements of the dolomite dust test (D)</li></ul>
<b>Materials</b>	Headband: textile Adjustment piece: silicone Nose clip: aluminum Filter/mask: Melt blown PP, Polyester Sealing lip: PVC Valve: ABS
<b>Weight</b>	20 g
<b>Standard</b>	EN 149:2001 + A1:2009

## Versions

Article number	Colour/Version	Retail unit
8735221	Folding mask FFP2, white with valve and carbon, large version	15 pcs. per box
8745221	Folding mask FFP2, white with valve and carbon, large version	3 pcs. per box

## Packaging sizes

Box	approx. 300 x 220 x 100 mm
Outer Carton	approx. 610 x 410 x 480 mm

## Maximum breathing resistance acc. to EN149 in mbar

	Inhalation resistance 30l/min.	Inhalation resistance 95l/min.	Exhalation resistance 160l/min.
FFP1	0,6	2,1	3,0
<b>FFP2</b>	<b>0,7</b>	<b>2,4</b>	<b>3,0</b>
FFP3	1,0	3,0	3,0

## Areas of use\*

The respiratory protection mask can be used against solid, aqueous and non-volatile liquid aerosols up to <b>10 times</b> the respective limit values.	Woodworking, softwood, cement, metal, smog, fine dust, concrete, iron dust, ash, cotton dust, fluoride, carbon fibres, gypsum, fibre glass, copper, nickel, soot, pollen, house dust, pet hair.
--	---

\*Please note that the above mentioned areas of use are examples only. The selection of PPE needs to be carried out by a competent person, in conjunction with relevant and current legislation.

All respiratory protective devices fall into PPE category III (high risks).

Uvex accepts no liability for any possible harm or damage which may result from this information.  
This data sheet does not replace a detailed risk assessment nor seeking specialist advice.

UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth