

FANNING STRIP FOR PT SCREW TERMINAL  
SOCKET

General technical data:

|  |  |    |
|--|--|----|
| Number of NC contacts for auxiliary contacts       |  | 0  |
| Number of NO contacts for auxiliary contacts       |  | 0  |
| Number of CO contacts for auxiliary contacts       |  | 0  |
| Design of the switching function positively driven |  | No |

Mechanical data:

|                                  |    |                      |
|----------------------------------|----|----------------------|
| Type of electrical connection    |    | screw-type terminals |
| Product component Plug-in socket |    | No                   |
| Width                            | mm | 147                  |
| Height                           | mm | 15                   |
| Depth                            | mm | 8                    |

Certificates/ approvals:

|                          |       |
|--------------------------|-------|
| General Product Approval | other |
|--------------------------|-------|



[Declaration of Conformity](#)

Further information

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=LZS:PT170R6>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/LZS:PT170R6>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=LZS:PT170R6&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=LZS:PT170R6&lang=en)

last modified:

15.01.2015