




8-Port Gigabit Long Range PoE+ Switch

TPE-LG80 (v1.0R)

- · Easy installation
- 8 x Gigabit PoE+ ports
- Enable the DIP switch to extend PoE+ signal up to 200m (656 ft.) at 10Mbps
- · DIP switch supports VLAN port isolation and QoS
- · 16Gbps switching capacity
- · 65W PoE budget
- · Wall mountable design
- · Sturdy metal switch
- Use with TRENDnet's PoE splitter to network and power non-PoE devices


The 8-Port Gigabit Long Range PoE+ Switch, model TPE-LG80, delivers data and power over Ethernet cables to PoE devices such as access points, VoIP phones, and IP cameras. It supports both PoE and PoE+ devices with a 65W PoE power budget. Enable the DIP switch to extend the PoE+ signal up to 200m (656 ft.) at 10Mbps for long distance PoE installations. Plug and play this sturdy metal switch for reliable high-speed PoE networking. Its fanless design is perfect for guiet environments that require silent operation.

TRENDIET




PoE+ Power

A 65W PoE power budget supports up to eight Power over Ethernet devices.



Gigabit


Eight gigabit ports provide a 16Gbps switching capacity to support edge network installations.



Long Range PoE+ Switch

Enable the DIP switch to extend the PoE+ signal up to 200m (656 ft.) at 10Mbps.

Networking Solution





PoE+

Supplies up to 30W of PoE+ power per PoE port with a 65W total power budget



Ports

Eight gigabit PoE+ ports



Switching Capacity

16Gbps switching capacity



LED Indicators

LED indicators convey PoE and port status



Housing

Wall mountable metal housing



Long Range PoE+ Switch

Enable the DIP switch to extend the PoE+ signal up to 200m (656 ft.) for long distance PoE installations



Port Isolation

Ideal for surveillance networking applications, the DIP switch also enables port isolation



Specifications

Standards	• IEEE 802.3 • IEEE 802.3u • IEEE 802.3ab • IEEE 802.3x • IEEE 802.3p • IEEE 802.3af • IEEE 802.3at • IEEE 802.3az			
Device Interface	8 x Gigabit PoE+ ports LED indicators DIP switch			
Data Transfer Rate	Ethernet: 10Mbps (half duplex), 20Mbps (full duplex) Fast Ethernet: 100Mbps (half duplex), 200Mbps (full duplex) Gigabit Ethernet: 2000Mbps (full duplex)			
Performance	Switch Fabric: 16Gbps RAM Buffer: 192KB MAC Address Table: 4K entries Jumbo Frames: 9KB Forwarding rate: 11.9Mpps (64-byte packet size)			
DIP Switch	Switch	Status	Function	
	1	OFF	Ports 1 & 2: Default gigabit PoE+	
		ON	Ports 1 & 2: Long range PoE+ up to 200m at 10Mbps	
	2	OFF	Ports 3 & 4: Default gigabit PoE+	
		ON	Ports 3 & 4: Long range PoE+ up to 200m at 10Mbps	
	3	OFF	VLAN port isolation disabled	
		ON	VLAN port isolation on ports 1-4	
	4	OFF	QoS disabled	
		ON	QoS Enabled: Video & Voice – High Priority	
	5	OFF	Port 5: Long range PoE+ up to 200m at 10Mbps	
		ON	Port 5: Default gigabit PoE+	
	6	OFF	Port 6: Default gigabit PoE+	
		ON	Port 6: Long range PoE+ up to 200m at 10Mbps	
	7	OFF	Port 7: Default gigabit PoE	
		ON	Port 7: Long range PoE+ up to 200m at 10Mbps	
	8	OFF	VLAN port isolation disabled	
		ON	VLAN port isolation on ports 5-7	
	*DIP Sw	ritch 3 &	8 cannot be enabled at the same time	

Special Features	 Long range PoE+ up to 200m at 10Mbps VLAN port isolation 802.1p Class of Service (CoS) Wall mountable 		
Power	 Input: 100 – 240 V AC, 50/60Hz, 2.5A Output: 55V DC, 1.3A external power adapter Max. consumption: 70.6W 		
РоЕ	• PoE budget: 65 Watts • PoE Mode A: Pins 1,2 for power and pins 3,6 for power		
Operating Temperature	• 0° – 40 °C (32° – 104 °F)		
Operating Humidity	Max. 90% non-condensing		
Dimensions	• 240 x 105 x 27mm (9.45 x 4.13 x 1.1 in.)		
Weight	• 592g (20.9 oz.)		
Certifications	• CE • FCC		
Warranty	Lifetime Warranty*		

PACKAGE CONTENTS

- TPE-LG80
- Quick Installation Guide
- Power brick (55V DC, 1.3A)
- Power cord (1.8m/6 ft.)

TRENDnet offers a lifetime warranty for all of its metal-enclosed network switches that have been purchased in the United States/Canada on or after 1/1/2015. Cooling fan and internal power supply carry a one-year warranty.

All references to speed are for comparison purposes only. Product specifications, size, and shape are subject to change without notice, and actual product appearance may differ from that depicted herein.

20675 Manhattan Place • Torrance • CA 90501 • USA • T: 1-888-326-6061 • F: 1-310-961-5511 • sales@trendnet.com • www.TRENDnet.com

TRENDnet is a registered trademark. Other Brands and product names are trademarks of their respective holders. Information provided in this document pertain to TRENDnet products and is subject to change at any time, without notice. For the most recent product information please visit http://www.trendnet.com. Copyright © TRENDnet. All Rights Reserved.