

SURGE SUPPRESSOR RC ELEMENT FOR
SNAPPING ON AC 48 TO 127V/DC 70 TO 150V FOR
CONTACTORS SIZE 8 TO 12, AC OPERATION SIZE 3
TO 6, DC OPERATION




General technical data:

Product designation	surge suppressor
Design of the surge suppressor	with RC elements

Control circuit/ Control:

Type of voltage of the control supply voltage		AC/DC
Control supply voltage frequency		
<ul style="list-style-type: none"> • 1 Rated value 	Hz	50
<ul style="list-style-type: none"> • 2 Rated value 	Hz	60
Control supply voltage 1		
<ul style="list-style-type: none"> • for DC <ul style="list-style-type: none"> — Initial rated value — Final rated value • with AC <ul style="list-style-type: none"> — at 50 Hz Initial rated value — at 50 Hz Final rated value — at 60 Hz Final rated value — at 60 Hz Initial rated value 	V	70 150 48 127 127 48

Certificates/ approvals:

General Product Approval  CSA  UR  EAC	other Declaration of Conformity Confirmation
---	---

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrymall>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TX75223S>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3TX75223S>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TX75223S&lang=en

last modified:

16.03.2015