

TECHNICAL DATA SHEET

PRO-POWER

**RoHS
Compliant**

DOUBLE-SIDED TAPE

**MODELS: SH5011-10,
SH5011-25, PP01022**

Specifications:

Double-sided cloth tape
Coated with hot-melt adhesive
Brown liner
Length: 10m, 25m

Applications:

Carpets, hole closure, repairing, masking, packaging, holding, and bundling
Interior and exterior use

Data:



| Total Thickness | Adhesive to Steel | Tensile Strength | Rolling Ball Tack | Elongation | Holding Power | Temperature Range |
|-----------------|-------------------|------------------|-------------------|------------|---------------|-------------------|
| 0.24-0.25mm | 45-55oz/inch | ≥20-30N/cm | >10 (Ball No.) | N/A | >2 hours | -15°C to +60°C |

Model: SH5011-10 – single roll, 50mm x 10m
Model: SH5011-25 – single roll, 50mm x 25m
Model: PP01022 – pack of ten rolls, 50mm x 10m

Usage:

Temperature: Between 0°C and +35°C. Surface must be clean and free from dust and grease. Avoid touching the tapes exposed adhesive surface in order to keep full adhesive performance. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24 hours at 23°C.

Important Notice: This data sheet and its contents (the "Information") belong to pro-POWER. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but pro-POWER assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where pro-POWER was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict pro-POWER's liability for death or personal injury resulting from its negligence.

PRO-POWER

TECHNICAL DATA SHEET

PRO-POWER

**RoHS
Compliant**

Storage and Shelf Life:

Clean and dry in a well ventilated area, preferably at a temperature between 10°C and 30°C. Stored under these conditions shelf life will be a minimum of six months.

Complies With:

RoHS 2011/65/EU

Important Notice: This data sheet and its contents (the "Information") belong to pro-POWER. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but pro-POWER assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where pro-POWER was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict pro-POWER's liability for death or personal injury resulting from its negligence.

PRO-POWER