



Type 1

Male-male \varnothing 4 mm stackable patchcord, retractable sleeve
 Cordon mâle-mâle \varnothing 4 mm + reprise arrière, fourreau rétractable
 Messleitung mit \varnothing 4 mm Stecker, stapelbar, retraktierbar



Type 2

Male-male \varnothing 4 mm patchcord, retractable sleeve
 Cordon mâle-mâle \varnothing 4 mm, fourreau rétractable
 Messleitung mit \varnothing 4 mm Stecker, retraktierbar

Reference - Référence - Bestell-Nr	L cm	Wire Câble Litze	Max current I admissible Bemessungs- strom	Voltage Tension Bemessungs- spannung	m Ω maxi	Pack	Colours Couleurs Farben #									
							R	N	Bl	V	J	Bc				
							Type 1	Type 2								
2210/600 V - 10 # 2210/600 V - 25 # 2210/600 V - 50 # 2210/600 V - 100 # 2210/600 V - 150 # 2210/600 V - 200 #	10 25 50 100 150 200	PVC 0,75 mm ² T °C - 20 + 80	12 A	600 V - CAT II	10 12 15 30 45 55	10	Red - Rouge - Rot	Black - Noir - Schwarz	Blue - Bleu - Blau	Green - Vert - Grün	Yellow - Jaune - Gelb	White - Blanc - Weiss				
2211/600 V - 10 # 2211/600 V - 25 # 2211/600 V - 50 # 2211/600 V - 100 # 2211/600 V - 150 # 2211/600 V - 200 #	10 25 50 100 150 200	Silicone 0,75 mm ² T °C - 60 + 180 (pic + 230)			10 12 15 30 45 55											
2212/600 V - 25 # 2212/600 V - 50 # 2212/600 V - 100 # 2212/600 V - 150 # 2212/600 V - 200 #	25 50 100 150 200	PVC 1,00 mm ² T °C - 20 + 80			20 A								12 15 25 35 45	10		
2219/600 V - 25 # 2219/600 V - 50 # 2219/600 V - 100 # 2219/600 V - 150 # 2219/600 V - 200 #	25 50 100 150 200	Silicone 1,00 mm ² T °C - 60 + 180 (pic + 230)											12 15 25 35 45			
2215/600 V - 25 # 2215/600 V - 50 # 2215/600 V - 100 # 2215/600 V - 150 # 2215/600 V - 200 #	25 50 100 150 200	PVC 1,50 mm ² T °C - 20 + 80											25 A		12 15 20 25 30	10
2213/600 V - 25 # 2213/600 V - 50 # 2213/600 V - 100 # 2213/600 V - 150 # 2213/600 V - 200 #	25 50 100 150 200	Silicone 1,50 mm ² T °C - 60 + 180 (pic + 230)													12 15 20 25 30	
2217/600 V - 25 # 2217/600 V - 50 # 2217/600 V - 100 # 2217/600 V - 150 # 2217/600 V - 200 #	25 50 100 150 200	PVC 2,50 mm ² T °C - 20 + 80													36 A	
2214/600 V - 25 # 2214/600 V - 50 # 2214/600 V - 100 # 2214/600 V - 150 # 2214/600 V - 200 #	25 50 100 150 200	Silicone 2,50 mm ² T °C - 60 + 180 (pic + 230)											12 15 20 25 30			

Material : Contacts : brass and CuBe / Ni (Au/Ni feasible) . Insulators : Polypropylène.
Matière : Contacts : laiton et CuBe / Ni (Au/Ni possible) . Isolants : Polypropylène.
Material : Kontakte : CuBe und Messing vernickelt/Au/Ni auf Anfrage. Isolation : Polypropylen.