

# Straight SMA Plug U.FL Jack Adapter

**multicomp** PRO

**RoHS  
Compliant**



## Specifications:

### Electrical

Frequency Range : DC-6GHz  
 Nominal Impedance : 50Ω  
 Voltage Rating : 100V Max.  
 VSWR : 1.3 Max.


### Materials

Bodies : Brass  
 Centre Contact : Brass  
 Insulation : PTFE

### Environmental

Operating Temperature Range : -40°C to +90°C

## Diagram



Dimensions : Millimetres (Inches)

## Finishes and Others

No.	Description	Material	Qty	Finish
1	Shell	Brass	1	Gold 3μ" Min.
2	Centre Contact	Brass		Gold 50μ" Min.
3	Gasket	Silicon		Red
4	Insulation	PTFE		None
5	Washer	Stainless Steel		None
6	Body	Brass		Gold 3μ" Min.

## Part Number Table

Description	Part Number
Straight SMA Plug U.FL Jack Adapter	MC000984

**Important Notice :** This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro  
 Farnell.com/multicomp-pro  
 Element14.com/multicomp-pro

**multicomp** PRO