

## Balancer with load capacity of 12.0-100.0 kg

Type 724 1, cable extraction 2000 mm

AUTOSTAT

### Application:

Can be used for following tools and devices, e. g.: Multi-purpose screwdriver, butcher's machines, welding tongs, X-ray equipment, monitor suspensions, measuring robots, riveting machines.

### Execution:

- Housing and the cable drum made of high-pressure die cast aluminium
- Cable drum double ball bearings
- Suspension can be positioned to the load which is done by a safety hook in free rotating and swivelling design with hook mouth securing
- Carrying force is infinitely variable via adjusting screw
- Load is attached via a screw snap hook
- Cable feed limitation is impact absorbing and adjustable
- Rope is infinitely variable in its length via a rope clamp
- If required, the cable can be replaced very easily
- Safety device: Fall arrester in line with DIN 15 112 included in scope of delivery, patented over-twist safeguard of suspension spring, spring safety device, fully encapsulated special motive spring, cable drum, can be blocked with integrated locking device, push clamp for securing the cable end
- Working area: Cable extraction: 2000 mm, cables in special lengths available on request. Special design with manual cable retraction lock deliverable upon request. This allows the cable to be blocked with a single movement when working. Locking not to be used for load change!

### Advantage:

- Effortless work



<b>Art. no.</b>	<b>7700 705</b>
<b>Brand</b>	AUTOSTAT
<b>Manufacturer Part Number</b>	77000705
<b>Min. load-carrying capacity</b>	60 kg
<b>Max. load-carrying capacity</b>	75 kg
<b>Type</b>	724 1
<b>With automatic locking</b>	No
<b>Max. cable pull-out length</b>	2000 mm
<b>Adjustable cord length</b>	Yes
<b>Material of cord</b>	Steel
<b>Wire cable diameter</b>	5 mm
<b>Replaceable cord</b>	Yes
<b>Cord in-feed restriction</b>	Absorbs impacts, adjustable
<b>Material of cable drum</b>	Die-cast aluminium
<b>Suspension type</b>	Freely rotating and pivot safety hook, positionable
<b>Load attachment</b>	Screw Karabiner hook
<b>Material of housing</b>	Die-cast aluminium
<b>Surface</b>	Powder-coated
<b>Housing width</b>	249 mm
<b>Housing thickness</b>	202 mm
<b>Design</b>	Standard
<b>Height</b>	750 mm
<b>Spring design</b>	Riveted special mainspring in separate spring housing
<b>With overrotation protection</b>	Yes
<b>Spring breakage protection</b>	Yes
<b>Number of springs</b>	1 PCS
<b>DIN</b>	151 12
<b>Gross Weight</b>	19.623 kg
<b>Product Group</b>	772

### EAN

40392476 1810 1

LET'S WORK TOGETHER.