



BLUE ADHESIVE LUBRICANT



BLUE ADHESIVE LUBRICANT is a multipurpose lubricant with a temporary blue tint to assist with application coverage. It exhibits strong attachment to substrates, is non-dripping, has good penetrating properties, is resistant to high pressure and has excellent water repellence.

BENEFITS

- Excellent water resistance
- Functional over a wide temperature range
- Produces a very low coefficient of friction
- Reduces stick slip problems
- Provides long lasting lubrication
- Safe on all metal surfaces, does not stain
- Safe on most rubbers, plastics and coatings. Test on sensitive or stressed materials before use

TYPICAL USES

- Engine assembly
- Handling equipment
- Chains
- Bearings
- Railroad equipment
- Agricultural equipment
- Surface treatment
- Guide rails
- Hinges
- Cables

TECHNICAL DATA

Physical Appearance	:	Viscous liquid
Colour	:	Blue
Odour	:	Solvent
Density	:	0.80 g/cm ³ (@20°C)
Flash Point	:	< 0°C
Density Active Product	:	0.87 (@25°C)
Flash Point Active Product	:	230°C (Open Cup)
Dynamic Viscosity Active Product	:	1894 mPa.s (@40°C)
4-ball Wear	:	0.25mm ²
Operating Temperature	:	-35°C to +200°C
Packaging	:	12x 400ml aerosol

APPLICATION METHOD

- Apply to a clean, dry surface
- Apply a thin even film
- Allow a few minutes for good penetration
- Do not use on energised equipment
- Do not mix with other lubricants
- To remove residues or excess product, use a solvent based Ambersil cleaner

STORAGE

The product may be stored at normal ambient temperatures and has a shelf life of 72 months with correct storage.

Aerosols should always be stored below 50°C, away from direct heat and naked flame.

HEALTH AND SAFETY

Health and Safety sheet available separately.

TECHNICAL SERVICE

CRC Industries UK Ltd provides a technical support service and maintains a constant programme of research and development. We are able to assist customers by specific product development to meet particular requirements.

MISREPRESENTATION ACT 1967 TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

CRC Industries UK Limited, Wylds Road, Bridgwater, Somerset, TA6 4DD

Tel: +44 (0) 1278 727200

Fax: +44 (0) 1278 425644

Web: www.ambersil.com

Email: sales.uk@ambersil.com

Created: June 2015

Version: 1