

**ALPHA WIRE COMPANY**  
**CUSTOMER PRODUCT SPECIFICATION**

<b>Part Number: 1181/60C</b> <b>Page 1 of 1 Pages</b>	<b>Issue: 6</b> <b>Issue Date: 5/19/2005</b> <b>Effective Date: 8/1/2005</b>
--	--

**A. Construction**

**Diameters (In)**

- |                |                                 |       |
|----------------|---------------------------------|-------|
| 1) Component 1 | 60 X 1 COND                     |       |
| a) Conductor   | 22 (7/30) AWG TC                |       |
| b) Insulation  | 0.010" Wall, Nom. PVC           | 0.050 |
| (1) Color Code | Alpha Wire Company Color Code D |       |

Cond	Color	Cond	Color	Cond	Color
1	BLACK	21	WHITE/BROWN	41	WHITE/GREEN/RED
2	RED	22	WHITE/ORANGE	42	WHITE/GREEN/GREEN
3	WHITE	23	WHITE/SLATE	43	WHITE/GREEN/BLUE
4	GREEN	24	WHITE/VIOLET	44	WHITE/GREEN/BROWN
5	ORANGE	25	WHITE/BLACK/RED	45	WHITE/GREEN/VIOLET
6	BLUE	26	WHITE/BLACK/GREEN	46	WHITE/BLUE/BLACK
7	BROWN	27	WHITE/BLACK/YELLOW	47	WHITE/BLUE/RED
8	YELLOW	28	WHITE/BLACK/BLUE	48	WHITE/BLUE/GREEN
9	VIOLET	29	WHITE/BLACK/BROWN	49	WHITE/BLUE/BLUE
10	SLATE	30	WHITE/BLACK/ORANGE	50	WHITE/BLUE/BROWN
11	PINK	31	WHITE/BLACK/SLATE	51	WHITE/BLUE/VIOLET
12	TAN	32	WHITE/BLACK/VIOLET	52	WHITE/BROWN/BLACK
13	RED/GREEN	33	WHITE/BLACK/BLACK	53	WHITE/BROWN/RED
14	RED/YELLOW	34	WHITE/RED/BLACK	54	WHITE/BROWN/GREEN
15	RED/BLACK	35	WHITE/RED/RED	55	WHITE/BROWN/BLUE
16	WHITE/BLACK	36	WHITE/RED/GREEN	56	WHITE/BROWN/BROWN
17	WHITE/RED	37	WHITE/RED/BLUE	57	WHITE/BROWN/VIOLET
18	WHITE/GREEN	38	WHITE/RED/BROWN	58	WHITE/VIOLET/RED
19	WHITE/YELLOW	39	WHITE/RED/VIOLET	59	WHITE/VIOLET/GREEN
20	WHITE/BLUE	40	WHITE/GREEN/BLACK	60	WHITE/VIOLET/BLUE

- |                   |  |                    |
|-------------------|--|--------------------|
| 2) Cable Assembly | 60 Components Cabled   |                    |
| a) Twists:        | 1.8 Twists/foot (min)  |                    |
| 3) Jacket         | 0.035" Wall, Nom.,PVC  | 0.520 (0.547 Max.) |
| a) Color(s)       | SLATE  |                    |
| b) Print          | ALPHA WIRE-* P/N 1181/60C 60C 22 AWG<br>75C (UL) TYPE CM OR AWM 2576 --- LLXXXXXX<br>CSA TYPE CMG FT4 ROHS<br>* = Factory Code |                    |

*[Note: Product may have c(UL) or CSA markings depending upon plant of manufacture.]*

**B. Industry Approvals**

- |                                   |                |                 |
|-----------------------------------|----------------|-----------------|
| 1) UL                             | AWM/STYLE 2576 | 80°C / 150 VRMS |
|                                   | CM             | 75°C            |
|                                   | VW-1           |                 |
| 2) CSA International              | CMG            | 60°C            |
|                                   | FT4            |                 |
| 3) EU Directive 2002/95/EC(RoHS): |                |                 |

All materials used in the manufacture of this part are in compliance with EU Directive 2002/95/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment. Consult Alpha Wire's web site for compliance Date of Manufacture.

- |                               |  |
|-------------------------------|--|
| 4) California Proposition 65: | The outer surface materials used in the manufacture of this part meet the requirements of California Proposition 65. |
|-------------------------------|--|

**C. Physical & Mechanical Properties**

- |                      |                    |
|----------------------|--------------------|
| 1) Temperature Range | -20 to 80°C        |
| 2) Bend Radius       | 10X Cable Diameter |
| 3) Pull Tension      | 330 Lbs, Maximum   |

**D. Electrical Properties**

- |                                 |   |
|---------------------------------|---|
| (For Engineering purposes only) |   |
| 1) Voltage Rating               | 300 VRMS  |
| 2) Capacitance                  | 33 pF/ft @1 kHz, Nominal Conductor to Conductor |
| 3) Inductance                   | 0.18 µH/ft, Nominal                             |

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

**ALPHA WIRE COMPANY**  
**CUSTOMER PRODUCT SPECIFICATION**

**Part Number: 1181/60C**  
**Page 2 of 1 Pages**

**Issue: 6**  
**Issue Date: 5/19/2005**  
**Effective Date: 8/1/2005**

4) Conductor DCR                      16.5  $\Omega$ /1000ft @20°C, Nominal

**E. Other**

- 1) Packaging
  - a) 1000 FT
  - b) 500 FT
  - c) 100 FT

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.  
Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.