



All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface

According to IEC 60169-17, MIL-PRF-39012, DIN EN 122200

Documents

Assembly instruction 51 D

Material and plating

Connector parts

- Center contact
- Outer contact
- Body
- Dielectric
- Gasket
- Gasket

Material

- Brass
- Brass
- Brass
- PTFE
- NeopreneCR 50C6
- Silicone

Plating

- AuroDur®, gold plated
- Flash white bronze over silver(e.g. Optargen®)
- Flash white bronze over silver(e.g. Optargen®)

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF_35/08.13/6.1

Electrical data

| | |
|--|---|
| Impedance | 50 Ω |
| Frequency | DC to 10 GHz |
| Return loss | ≥ 35 dB @ DC to 1 GHz ≥ 30 dB @ 1 GHz to 2.5 GHz ≥ 27 dB @ 2.5 GHz to 4 GHz |
| Insertion loss | ≤ 0.05 x √ f [GHz] dB, DC to 4 GHz |
| Insulation resistance | ≥ 5 GΩ |
| Center contact resistance | ≤ 1.5 mΩ |
| Outer contact resistance | ≤ 1 mΩ |
| Test voltage (at sea level) | 1500 V rms |
| Working voltage (at sea level) | 500 V rms |
| Power handling (at 20 °C, sea level, VSWR 1.0) | 80 W @ 2 GHz |

- Limitations are possible due to the used cable type -

Mechanical data

| | |
|----------------------|--------------------|
| Mating cycles | ≥ 500 |
| Coupling test torque | ≤ 1.7 Nm |
| Recommended torque | 0.46 Nm to 0.69 Nm |

Environmental data

| | |
|-----------------------------------|--------------------------------------|
| Temperature range | -65 °C to +165 °C |
| Thermal shock | MIL-STD-202, Method 107, Condition B |
| Corrosion | MIL-STD-202, Method 101, Condition B |
| Vibration | MIL-STD-202, Method 204, Condition B |
| Shock | MIL-STD-202, Method 213, Condition G |
| Moisture resistance | MIL-STD-202, Method 106 |
| Degree of protection (mated pair) | IEC 60529, IP 63 |
| RoHS | compliant |

Tooling

N/A

Suitable cables

RG 213 /U , RG 214 /U

Weight

Weight 41.8 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

| | | | | | | | |
|---------------|----------|-------------------|----------|------|---------------------------|-----------|----------|
| Draft | Date | Approved | Date | Rev. | Engineering change number | Name | Date |
| Inge Mühlauer | 10.08.04 | Sa. Krautenbacher | 20.03.14 | e00 | 14-0352 | T. Krojer | 20.03.14 |

| | | | | | | | |
|--|--|--|--|--|--|---------------|--|
| Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de | | | | Tel. : +49 8684 18-0 Fax : +49 8684 18-499 Email : info@rosenberger.de | | Page 2 / 2 | |
|--|--|--|--|--|--|---------------|--|