## S2C-S/H6R



Products Low Voltage Products and Systems Modular DIN Rail Products Miniature Circuit Breakers MCBs Accessories Auxiliary / Signal Contacts

General Information

Extended Product Type: S2C-S/H6R

 Product ID:
 2CDS200922R0001

 EAN:
 4016779563819

Catalog Description: S2C-S/H6R - Signal / Auxiliary Contact

Long Description: Choice through a selector between indication of the position of the device's contacts and si

gnalling of a fault (overcurrent/short-circuit for MCBs and RCBOs, earth fault for RCCBs and RCBOs). Suitable for MCBs S 200 series, SN 201 series, RCCBs F 200 series, RCBOs D

S201, DS202C, DS 200 series.

## Additional Information

Country of Origin:	Germany (DE)
Customs Tariff Number:	85365080
Data Sheet, Technical Information:	2CSC400002D0208
Declaration of Conformity - CE:	2CDK400629D2701
E-nummer:	2102501
EAN:	4016779563819
ETIM 4:	EC001286 - Auxiliary contact unit for distribution board
ETIM 5:	EC001286 - Auxiliary contact unit for distribution board
ЕТІМ 6:	EC001286 - Auxiliary contact unit for distribution board
Function:	Signal / Auxiliary Contact
Industrial IT Certification Level:	0
Instructions and Manuals:	GHS2007072P0004
Invoice Description:	S2C-S/H6R Universal Auxiliary/Signal Con
Minimum Order Quantity:	1 piece
Package Level 1 EAN:	4016779678872
Package Level 1 Gross Weight:	0.045 kg
Package Level 1 Height:	115 mm
Package Level 1 Length:	104 mm
Package Level 1 Units:	1 piece
Package Level 1 Width:	20 mm
Package Level 2 EAN:	4016779946209
Package Level 2 Gross Weight:	7 kg
Package Level 2 Height:	560 mm
Package Level 2 Length:	1200 mm
Package Level 2 Units:	60 piece
Package Level 2 Width:	820 mm
Power Loss:	0,5 W
Product Main Type:	S2C
Product Name:	Signal / Auxiliary Contact
Product Net Depth:	69 mm
Product Net Height:	85 mm
Product Net Weight:	0.043 kg
Product Net Width:	8.8 mm
RoHS Date:	0335
RoHS Information:	2CDK440016K0201

RoHS Status:	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Selling Unit of Measure:	piece
Short Description:	S2C-S/H6R Universal Auxiliary/Signal Con
Standards:	GB14048.5
	CSA 22.2 No. 235
	UL 1077
	IEC/EN 60947-5-1
Suitable For:	S200
	S200M
	S200P
	S200S
	SN201L
	SN201
	SN201M
	F200
	DS201
	DS202C
	DS200
Suitable for Product Class:	Miniature Circuit Breaker
	Residual Current Device
UNSPSC:	39120000
eClass:	7.0 27143502

