# **Adjustable Tension Levers**

## 24440.0428



## **Product Description**

#### **Material**

#### Lever

· Steel, blackened

### Inner parts

• Steel, blackened, quality 5.8

• Steel, blackened, quality 5.8

#### Ball knob

· Thermosetting plastic PF 31, black, DIN 319

## **Operation**


By lifting the lever the serrations are disengaged. The lever can be positioned by the serrations. On releasing the lever, the serrations are automatically re-engaged.


#### More information


#### **Notes**

The threaded portion can be exchanged.

## **Drawing**







### **Order information**

Dimensions										I	Art. No.
d <sub>1</sub>	d <sub>2</sub>	I <sub>1</sub>	d <sub>3</sub>	d₄	d <sub>5</sub>	h <sub>1</sub>	h <sub>2</sub>	h <sub>3</sub>	l ~	_	
[mm]										[9]	
with screw – picture 2, steel											
33	M16	63	23	12	32	55	5.5	6	124	461	24440.0428

## Compliance

## **RoHS** compliant

Contains lead - compliant according to exceptions 6a / 6b / 6c

## Contains SVHC substances >0,1% w/w

Contains lead - SVHC list [REACH] as of 10.06.2022

### **Contains Proposition 65 substances**



Lead can cause cancer and reproductive harm from exposure https://www.P65Warnings.ca.gov/

Erwin Halder KG

#### **Free from Conflict Minerals**

This product does not contain any substances designated as "conflict minerals" such as tantalum, tin, gold or tungsten from the Democratic Republic of Congo or adjacent countries.



www.halder.com Page 1 of 1 Published on: 8.7.2022