

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.08.2021

Version number 305 (replaces version 304)

Revision: 16.08.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier** 600202
- **Trade name:** Synthetic resin thinner E-COLL
- **Article number:** 4317784006804, 4330816996638
- **UFI:** E5TT-39VE-XA01-54NN
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**
 - SU21 Consumer uses: Private households / general public / consumers
 - SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Application of the substance / the mixture** Solvents
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 - E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH
 - EDE Platz 1
 - D-42389 Wuppertal
 - Germany

Tel. +49 202 6096-0
e-mail: sdb@ede.de
- **Further information obtainable from:** Product safety department
- **1.4 Emergency telephone number:** Giftinformationszentrum Mainz – Tel.: +49 (6131) 19240

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 3	H226 Flammable liquid and vapour.
Skin Irrit. 2	H315 Causes skin irritation.
Eye Irrit. 2	H319 Causes serious eye irritation.
STOT SE 3	H336 May cause drowsiness or dizziness.
STOT RE 2	H373 May cause damage to organs through prolonged or repeated exposure.
Asp. Tox. 1	H304 May be fatal if swallowed and enters airways.
Aquatic Chronic 3	H412 Harmful to aquatic life with long lasting effects.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.08.2021

Version number 305 (replaces version 304)

Revision: 16.08.2021

Trade name: Synthetic resin thinner E-COLL

(Contd. of page 1)

· Hazard pictograms

GHS02 GHS07 GHS08

· Signal word Danger**· Hazard-determining components of labelling:**Hydrocarbons, C9-C11, n-alkanes, isoalkanes, aromatics <2%
xyleneHydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics
n-butyl acetate**· Hazard statements**

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P243 Take action to prevent static discharges.

P260 Do not breathe mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P370+P378 In case of fire: Use CO₂, powder or water spray to extinguish.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

(Contd. on page 3)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.08.2021

Version number 305 (replaces version 304)

Revision: 16.08.2021

Trade name: Synthetic resin thinner E-COLL

(Contd. of page 2)

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

- **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
EC number: 919-857-5 Reg.nr.: 01-2119471843-32-xxxx	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, aromatics <2% ⚠ Flam. Liq. 3, H226 ☠ Asp. Tox. 1, H304 ⚠ STOT SE 3, H336 EUH066	70-80%
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 02-2119752448216-32	xylene ⚠ Flam. Liq. 3, H226 ☠ STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	10-<25%
EC number: 920-750-0 Reg.nr.: 01-2119473851-33-xxxx	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics ⚠ Flam. Liq. 2, H225 ☠ Asp. Tox. 1, H304 ⚠ Aquatic Chronic 2, H411 ⚠ STOT SE 3, H336 EUH066	2.5-10%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29-xxxx 01-2119485493-29-0059	n-butyl acetate ⚠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H336 EUH066	1-<3%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
Supply fresh air.
Seek medical treatment in case of complaints.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.08.2021

Version number 305 (replaces version 304)

Revision: 16.08.2021

Trade name: Synthetic resin thinner E-COLL

(Contd. of page 3)

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: Do not induce vomiting; call for medical help immediately.**· 4.2 Most important symptoms and effects, both acute and delayed**

Headache

Dizziness

Unconsciousness

Nausea

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures**· 5.1 Extinguishing media****· Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents: Water with full jet**· 5.2 Special hazards arising from the substance or mixture**

In case of fire, the following can be released:

Carbon monoxide (CO)

· 5.3 Advice for firefighters**· Protective equipment:** Wear self-contained respiratory protective device.**· Additional information**

Collect contaminated fire fighting water separately. It must not enter the sewage system.

Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures**· 6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Prevent seepage into sewage system, workpits and cellars.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.08.2021

Version number 305 (replaces version 304)

Revision: 16.08.2021

Trade name: Synthetic resin thinner E-COLL

(Contd. of page 4)

See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.
Keep receptacles tightly sealed.
Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Fumes can combine with air to form an explosive mixture.
Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities**Storage:****Requirements to be met by storerooms and receptacles:**

Provide solvent resistant, sealed floor.
Store only in the original receptacle.

Information about storage in one common storage facility: Store away from oxidising agents.**Further information about storage conditions:** Store in a cool place.**Storage class:** -**7.3 Specific end use(s)** No further relevant information available.**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Ingredients with limit values that require monitoring at the workplace:****CAS: 1330-20-7 xylene**

IOELV	Short-term value: 442 mg/m ³ , 100 ppm Long-term value: 221 mg/m ³ , 50 ppm Skin
-------	--

CAS: 123-86-4 n-butyl acetate

IOELV	Short-term value: 723 mg/m ³ , 150 ppm Long-term value: 241 mg/m ³ , 50 ppm
-------	--

Additional information: The lists valid during the making were used as basis.

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.08.2021

Version number 305 (replaces version 304)

Revision: 16.08.2021

Trade name: Synthetic resin thinner E-COLL

(Contd. of page 5)

· 8.2 Exposure controls

- **Appropriate engineering controls** No further data; see item 7.
- **Individual protection measures, such as personal protective equipment**

· General protective and hygienic measures:

Wash hands before breaks and at the end of work.
Keep away from foodstuffs, beverages and feed.
Do not inhale gases / fumes / aerosols.

· Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation - filter A2

· Hand protection

Protective gloves

· Material of gloves

Nitrile rubber, NBR
Fluorocarbon rubber (Viton)
Recommended thickness of the material: ≥ 0.4 mm

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection

Tightly sealed goggles

- **Body protection:** Solvent resistant protective clothing

SECTION 9: Physical and chemical properties**· 9.1 Information on basic physical and chemical properties****· General Information**

- **Colour:** Colourless
- **Odour:** Characteristic
- **Odour threshold:** Not determined.
- **Melting point/freezing point:** -76 °C
- **Boiling point or initial boiling point and boiling range** > 118 °C
- **Flammability** Not applicable.
- **Lower and upper explosion limit**
- **Lower:** 0.6 Vol %
- **Upper:** 12 Vol %
- **Flash point:** > 23 °C

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.08.2021

Version number 305 (replaces version 304)

Revision: 16.08.2021

Trade name: Synthetic resin thinner E-COLL

(Contd. of page 6)

· Auto-ignition temperature:	Product is not selfigniting.
· Decomposition temperature:	Not determined.
· pH at 20 °C	7
· Viscosity:	
· Kinematic viscosity	Not determined.
· Kinematic: 23 °C - 4 mm (ISO 2431)	
· Dynamic:	Not determined.
· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure at 20 °C:	10 hPa
· Density and/or relative density	
· Density at 20 °C:	0.78 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· 9.2 Other information	
· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	200 °C
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· VOC (EC) g/l	850.0 g/l
· Change in condition	
· Softening point/range	
· Oxidising properties	Not determined.
· Evaporation rate	Not determined.
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	
Flammable liquid and vapour.	
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

EU

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.08.2021

Version number 305 (replaces version 304)

Revision: 16.08.2021

Trade name: Synthetic resin thinner E-COLL

(Contd. of page 7)

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Reacts with strong acids and oxidising agents.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, aromatics <2%

Oral	LD50	>15,000 mg/kg (rat) (OECD 401)
Dermal	LD50	3,400 mg/kg (rat) (OECD 402)
Inhalative	LC50/4h	13,100 ppm (rat) (OECD 403)

CAS: 1330-20-7 xylene

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	2,920 mg/kg (rabbit)

CAS: 123-86-4 n-butyl acetate

Oral	LD50	13,100 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4h	>21 ppm (rat)

- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.08.2021

Version number 305 (replaces version 304)

Revision: 16.08.2021

Trade name: Synthetic resin thinner E-COLL

(Contd. of page 8)

- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure**
May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard**
May be fatal if swallowed and enters airways.
- **11.2 Information on other hazards**

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information**· 12.1 Toxicity****· Aquatic toxicity:****Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

LL50/96h 3-10 mg/l (Fis)

CAS: 123-86-4 n-butyl acetate

LC50 (96h) 18 mg/L (Pimephales promelas)

EC50 (48h) 44 mg/L (Daphnia magna)

EC50/24h 73 mg/l (Daphnia magna)

EC50/72h 647.7 mg/l (S)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
Toxic for aquatic organisms
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.08.2021

Version number 305 (replaces version 304)

Revision: 16.08.2021

Trade name: Synthetic resin thinner E-COLL

(Contd. of page 9)

Do not allow product to reach ground water, water course or sewage system.
Also poisonous for fish and plankton in water bodies.

SECTION 13: Disposal considerations**13.1 Waste treatment methods:**

Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste.
Observe local regulations.

European waste catalogue

07 03 04* other organic solvents, washing liquids and mother liquors

SECTION 14: Transport information**14.1 UN number or ID number****ADR, IMDG, IATA** UN1263**14.2 UN proper shipping name****ADR** UN1263 PAINT RELATED MATERIAL
IMDG, IATA PAINT RELATED MATERIAL**14.3 Transport hazard class(es)****ADR****Class** 3 (F1) Flammable liquids.
Label 3**IMDG, IATA****Class** 3 Flammable liquids.
Label 3**14.4 Packing group****ADR, IMDG, IATA** III**14.5 Environmental hazards:**

Product contains environmentally hazardous substances: Naphtha (petroleum), hydrodesulfurized heavy (Benzene < 0.1%)

Marine pollutant:

Yes

14.6 Special precautions for user

Warning: Flammable liquids.

Hazard identification number (Kemler code):

33

EMS Number:

F-E,S-E

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.08.2021

Version number 305 (replaces version 304)

Revision: 16.08.2021

Trade name: Synthetic resin thinner E-COLL

(Contd. of page 10)

- **Stowage Category** A
 - **14.7 Maritime transport in bulk according to IMO instruments** Not applicable.
 - **Transport/Additional information:**
-
- **ADR**
 - **Limited quantities (LQ)** 5L
 - **Excepted quantities (EQ)** Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml
 - **Transport category** 3
 - **Tunnel restriction code** D/E
-
- **IMDG**
 - **Limited quantities (LQ)** 5L
 - **Excepted quantities (EQ)** Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml
 - **UN "Model Regulation":** UN 1263 PAINT RELATED MATERIAL, 3, III

SECTION 15: Regulatory information

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** Methanol
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **Verordnung (EU) Nr. 528/2012 - Verwendung von Biozidprodukten**
- **Information about limitation of use:**
Employment restrictions concerning pregnant and lactating women must be observed.
- **Exposure scenario(s)**
Exposure scenario(s) of ingredients (if present) are available on request at:
sdb@ede.de

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.

(Contd. on page 12)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.08.2021

Version number 305 (replaces version 304)

Revision: 16.08.2021

Trade name: Synthetic resin thinner E-COLL

(Contd. of page 11)

- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.

- **Date of previous version:** 16.08.2021

- **Version number of previous version:** 304

- **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

- *** Data compared to the previous version altered.**