



REDUCING JUMPER, TO CONNECT SPRING CONNECTIONS 6 MM<sup>2</sup> WITH SPRING TERMINALS 2.5 MM<sup>2</sup> OR 4 MM<sup>2</sup>, SIEMENS COLOR

Main circuit		
Operating current / Rated value	A	40

Mechanical Design		
Mounting type		plug-in
Contact spacing	mm	6

Certificates		
Design tested acc. to type of protection / EEx e		No

General Product Approval	Declaration of Conformity
--------------------------	---------------------------



### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/8WH90200FC10>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<http://support.automation.siemens.com/WW/view/en/8WH90200FC10/all>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=8WH90200FC10](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WH90200FC10)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://ausschreibungstexte.siemens.com/tiplv>

last modified:

11.03.2015