

# **Material Safety Data Sheet**

# 1. Identification of the substance/mixture and of the company/undertaking

| Product name: | Ni-MH battery, rechargeable |
|---------------|-----------------------------|
|---------------|-----------------------------|

| Item no. | Size           | Nominal Voltage | Capacity | Energy content |
|----------|----------------|-----------------|----------|----------------|
| 2973095  | AA/Mignon/HR06 | 1.2 V           | 1800 mAh | 2.16 Wh        |

| Manufacturer:                    | Conrad Electronic SE                       |  |
|----------------------------------|--|--|
| Address:                         | Klaus-Conrad-Str. 1, D-92240 Hirschau      |  |
| Telephone:                       | <b>Telephone:</b> +49 (0) 9604 / 40 - 8988 |  |
| <b>Date of issue:</b> 22.12.2022 |  |  |

#### 1.1 Product identifier

Trade name: Ni-MH Battery

## 1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture: Household & Industrial power

#### Remarks:

This product is likely to be classified as article with substances not intended to be released and is out of scope of a SDS as set out in Regulation (EC) No 1907/2006. This SDS is generated for applicant's reference only.



# **Material Safety Data Sheet**

## 2. Hazards identification

#### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



Flam. Sol. 1 H228 Flammable solid.



Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Muta. 2 H341 Suspected of causing genetic defects.

Carc. 1A H350 May cause cancer.

Repr. 1B H360FD May damage fertility. May damage the unborn child.

STOT RE 1 H372 Causes damage to the respiratory system through prolonged or repeated exposure.

Route of exposure: Inhalation.



Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



Acute Tox. 4 H302 Harmful if swallowed.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

### Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of Regulation (EC) No.1272/2008.

#### Classification system:

The classification is according to the latest edition of EU Regulation (EC) No. 1272/2008, and extended by company and literature data.



# **Material Safety Data Sheet**

#### 2.2 Label elements

### Labelling according to Regulation (EC) No. 1272/2008

The product is classified and labelled according to the CLP regulation.

#### Hazard pictograms









GHS02

2 GHS07

GHS08

GHS09

## Signal word:

Danger

# Hazard-determining components of labelling:

Nickel dihydroxide

Nickel

Cobalt

Potassium hydroxide

#### Hazard statements:

H228 Flammable solid.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H341 Suspected of causing genetic defects.

H350 May cause cancer.

H360FD May damage fertility. May damage the unborn child.

H372 Causes damage to the respiratory system through prolonged or repeated exposure. Route of exposure: Inhalation.

H410 Very toxic to aquatic life with long lasting effects.

#### Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.



# **Material Safety Data Sheet**

#### Additional information:

Restricted to professional users.

## 2.3 Other hazards

Results of PBT and vPvB assessment: PBT: Not applicable

vPvB: Not applicable

# 3. Composition/information on ingredients

## 3.2 Mixtures

### **Description:**

Mixture of the substances listed below with nonhazardous additions.

For the wording of the listed hazard statements refer to section 16.

| Composition:               |   |       |
|----------------------------|---|-------|
| CAS: 7440-02-0             | Nickel  | 35.5% |
| EINECS: 231-111-4          | & Carc. 2, H351; STOT RE 1, H372; (1) Skin Sens. 1, H317                                |       |
| Index number: 028-002-00-7 |   |       |
| CAS: 12054-48-7            | Nickel dihydroxide  | 28.5% |
| EINECS: 235-008-5          | & Resp. Sens. 1, H334; Muta. 2, H341; Carc. 1A, H350i; Repr. 1B,                        |       |
| Index number: 028-008-00-X | H360D; STOT RE 1, H372; 🕸 Aquatic Acute 1, H400; Aquatic Chronic 1,                     |       |
|                            | H410; • Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Irrit. 2, H315; Skin Sens. 1, H317 |       |
| CAS: 7439-91-0             | Lanthanum   | 12.5% |
| EINECS: 231-099-0          |   |       |
| CAS: 7440-45-1             | Cerium  | 11%   |
| EINECS: 231-154-9          | <b>(b)</b> Flam. Sol. 1, H228   |       |
| CAS: 7440-48-4             | Cobalt 7  |       |
| EINECS: 231-158-0          | & Resp. Sens. 1, H334;Muta. 2, H341; Carc. 1B, H350;                                    |       |
| Index number: 027-001-00-9 | Repr. 1B, H360F;  Skin Sens. 1, H317; Aquatic Chronic 4, H413                           |       |
| CAS: 7439-96-5             | Manganese   | 3%    |
| EINECS: 231-105-1          | Substance with a community workplace exposure limit                                     |       |
| CAS: 1310-58-3             | Potassium hydroxide   | 1%    |
| EINECS: 215-181-3          | Skin Corr. 1A, H314; (1) Acute Tox. 4, H302   |       |
| Index number: 019-002-00-8 | ·   |       |
| CAS: 1310-73-2             | Sodium hydroxide  | 0.5%  |
| EINECS: 215-185-5          | Skin Corr. 1A, H314   |       |
| Index number: 011-002-00-6 | *   |       |
| CAS: 1310-65-2             | Lithium hydroxide   | 0.3%  |
| EINECS: 215-183-4          | Skin Corr. 1A, H314; Eye Dam. 1, H318; (1) Acute Tox. 4, H302                           |       |
| CAS: 7440-00-8             | Neodymium   | 0.1%  |
| EINECS: 231-109-3          |   |       |



# **Material Safety Data Sheet**

#### 4. First aid measures

#### 4.1 Description of first aid measures

#### General description:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

#### After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

#### After skin contact:

Immediately wash with water and soap and rinse thoroughly.

#### After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

#### After swallowing:

Call for a doctor immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

#### 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

# 5. Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing agents:

Use fire extinguishing methods suitable to surrounding conditions.

## For safety reasons unsuitable extinguishing agents:

Water.

#### 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

#### 5.3 Advice for firefighters

#### Protective equipment:

Mouth respiratory protective device.



# **Material Safety Data Sheet**

## 6. Accidental release measures

## 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

## **6.2 Environmental precautions**

Do not allow product to reach sewage system or any water sourse.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

### 6.3 Methods and material for containment and cleaning up

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

#### 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# 7. Handling and storage

### 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

For the general occupational hygienic measures refer to Section 8.

#### Information about fire and explosion protection:

Keep respiratory protective device available.

#### 7.2 Conditions for safe storage, including any incompatibilities

#### Requirements to be met by storerooms and receptacles:

No special requirements.

## Information about storage in one common storage facility:

Not required.

### Further information about storage conditions:

Keep container tightly sealed.

#### 7.3 Specific end use(s)

No further relevant information available.



# **Material Safety Data Sheet**

# 8. Exposure controls/personal protection

## **8.1 Control parameters**

Ingredients with limit values that require monitoring at the workplace:

| 7440-02-0 (35.5%)                              |   |  |
|--|---|--|
| WEL (Great Britain) Long-term value: 0.5 mg/m³ |   |  |
| TIZE (Groat Britain)                           | as Ni; Sk; Carc                                 |  |
| AGW (Germany)                                  | Long-term value: 0.006A; 0.030E* mg/m³          |  |
| 7.0(00   | 8(II);AGS, 24, Sh, Y, 10*, 31*                  |  |
| VLEP (France)                                  | Long-term value: 1 mg/m³                        |  |
| (  | C2  |  |
| 12054-48-7 Nickel dihy                         |   |  |
| WEL (Great Britain)                            | Long-term value: 0.5 mg/m³                      |  |
|  | as Ni; Sk; Carc                                 |  |
| AGW (Germany)                                  | Long-term value: 0.030E mg/m <sup>3</sup>       |  |
| , , , , , ,                                    | 8(II);AGS, Sh, Y, 10, 24, 31                    |  |
| TRGS 910 (Germany)                             | Short-term value: 0.006 (A) mg/m³               |  |
|  | Long-term value: 0.006 (A) mg/m³                |  |
|  | 8, Konzentrationen beziehen sich auf Ni-Gehalt  |  |
| VLEP (France)                                  | Long-term value: 1 mg/m³                        |  |
| , ,  | C1A, M2, R1B                                    |  |
| 7440-48-4 Cobalt (7.6%                         |   |  |
| WEL (Great Britain)                            | Long-term value: 0.1 mg/m³                      |  |
|  | as Co; Carc, Sen                                |  |
| MAK (Germany)                                  | einatembare Fraktion; vgl. Abschn.XIII          |  |
| 7439-96-5 Manganese                            | (3%)  |  |
| IOELV (EU)                                     | Long-term value: 0.2* 0.05** mg/m³              |  |
|  | as Mn; *inhalable, **respirable fraction        |  |
| WEL (Great Britain)                            | Long-term value: 0.2* 0.05** mg/m³              |  |
|  | as Mn *inhalable fraction **respirable fraction |  |
| AGW (Germany)                                  | Long-term value: 0.02A; 0.2E mg/m³              |  |
|  | 8(II);DFG,Y,10, 20                              |  |
| VLEP (France)                                  | Long-term value: 0.05* 0.20** mg/m³             |  |
|  | *fraction alvéolaire **inhalable; en manganèse  |  |
| 1310-58-3 potassium hydroxide (1%)             |   |  |
| WEL (Great Britain)                            | Short-term value: 2 mg/m³                       |  |
| VLEP (France)                                  | Short-term value: 2 mg/m³                       |  |
| 1310-73-2 sodium hydroxide (0.5%)              |   |  |
| WEL (Great Britain)                            | Short-term value: 2 mg/m³                       |  |
| MAK (Germany)                                  | vgl.Abschn.llb                                  |  |
| VLEP (France)                                  | Long-term value: 2 mg/m³                        |  |
| 1310-65-2 Lithium hyd                          |   |  |
| WEL (Great Britain)                            | Short-term value: 1 mg/m³                       |  |
| MAK (Germany)                                  | vgl. Abschn. IIb                                |  |
|  |   |  |

## Regulatory information

WEL (Great Britain): EH40/2020 AGW (Germany): TRGS 900 VLEP (France): ED 1487 12.2019 MAK (Germany): MAK- und BAT-Liste

IOELV (EU): (EU) 2019/1831



# **Material Safety Data Sheet**

**DNELs:** Not available **PNECs:** Not available

#### Ingredients with biological limit values:

| 7439-96-5 Manganese |  |  |
|---------------------|--|--|
| BGW (Germany)       | 20 μg/l  |  |
|                     | Untersuchungsmaterial: Vollblut  |  |
|                     | Probennahmezeitpunkt: bei Langzeitexposition: am Schichtende nach mehreren vorangegangenen Schichten, Expositionsende bzw. Schichtende |  |
|                     | Parameter: Mangan  |  |

#### Additional information:

The lists valid during the making were used as basis.

#### 8.2 Exposure controls

Based on the composition shown in Section 3, the following measures are suggested for occupational safety measure.

#### Appropriate engineering controls:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

See Section 7 for information about design of technical facilities.

#### Personal protective equipment

#### Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

#### Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/the chemical mixture

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material:

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.



# **Material Safety Data Sheet**

## Eye protection:



Tightly sealed goggles

#### **Environmental exposure controls:**

Control measures must be made in accordance with Community environmental protection legislation.

# 9. Chemical and Physical Properties

## 9.1 Information on basic physical and chemical properties

Appearance: Form: Solid

Colour: Specific Odour: Odourless

Odour threshold: Not available

pH-value: Not available

Change in condition

Melting point/Freezing point: Not available Initial boiling point and boiling range: Not available Not available Flash point: Flammability (solid, gas): Not available Auto-Ignition temperature: Not available Decomposition temperature: Not available Not available Self-igniting: Not available Explosion properties:

Explosion limits: Lower: Not available

Upper: Not available

Oxidizing properties: Not available Not available Vapour pressure: Density: Not available Relative density: Not available Vapour density: Not available Evaporation rate: Not available Solubility in / Miscibility with water: Not available Partition coefficient (n-octanol/water): Not available. Not available. Viscosity: Dynamic: Not available Kinematic:

#### 9.2 Other information

No further relevant information available.



# **Material Safety Data Sheet**

# 10. Stability and Reactivity

#### 10.1 Reactivity

Data not available

#### 10.2 Chemical stability

Data not available

## 10.3 Possibility of hazardous reactions

No dangerous reactions known.

#### 10.4 Conditions to avoid

No further relevant information available.

#### 10.5 Incompatible materials

No further relevant information available.

### 10.6 Hazardous decomposition products

No dangerous decomposition products known.

# 11. Toxicological information

## 11.1 Information on toxicological effects

#### Acute toxicity:

Harmful if swallowed.

## LD/LC50 values relevant for classification:

| 7440-48-4 Cobalt    |      |                   |
|---------------------|------|-------------------|
| Oral                | LD50 | 6,170 mg/kg (rat) |
| 7439-96-5 Manganese |      |                   |
| Oral                | LD50 | 9,000 mg/kg (rat) |

#### Skin corrosion/irritation:

Causes skin irritation.

## Serious eye damage/irritation:

Causes serious eye irritation.

## Respiratory or skin sensitization:

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

#### Germ cell mutagenicity:

Suspected of causing genetic defects.

#### Carcinogenicity:

May cause cancer.



# **Material Safety Data Sheet**

### Reproductive toxicity:

May damage fertility. May damage the unborn child.

#### STOT-single exposure:

Based on available data, the classification criteria are not met.

### STOT-repeated exposure:

Causes damage to the respiratory system through prolonged or repeated exposure. Route of exposure: Inhalation.

### Aspiration hazard:

Based on available data, the classification criteria are not met.

## 12. Ecological information

#### 12.1 Toxicity

### Aquatic toxicity:

No further relevant information available.

#### 12.2 Persistence and degradability

No further relevant information available.

#### 12.3 Bioaccumulative potential

No further relevant information available.

### 12.4 Mobility in soil

No further relevant information available.

#### 12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

#### 12.6 Other adverse effects

No further relevant information available.

#### 12.7 Additional ecological information

#### **General notes:**

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms.



# **Material Safety Data Sheet**

# 13. Disposal considerations

#### 13.1 Waste treatment methods

Recommendation:

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging

Recommendation: Disposal must be made according to official regulations.

Recommended cleansing agents: Water, if necessary together with cleansing agents.

# 14. Transport information

14.1 UN-Number

ADR/RID/ADN, IATA: Not applicable IMDG: UN3496

14.2 UN proper shipping name

ADR/RID/ADN, IATA: Not applicable

IMDG: Batteries, nickel-metal hydride, MARINE POLLUTANT

14.3 Transport hazard class(es)

ADR/RID/ADN, IATA:

Class: Not applicable

Label: -

IMDG:





Class: 9 Miscellaneous dangerous substances and articles.

Label: 9

14.4 Packing group

ADR/RID/ADN, IATA: Not applicable

14.5 Environmental hazards

Marine pollutant: Symbol (fish and tree)

14.6 Special precautions for user

Special precautions for user: Not applicable

Hazard identification number (Kemler code): -

EMS Number: F-A, S-I

Stowage Category: A

Stowage Code: SW1 Protected from sources of heat.



# **Material Safety Data Sheet**

## 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

### 14.8 Transport/Additional information

IMDG:

Limited quantities (LQ): 0

Excepted quantities (EQ): Code: E0

Not permitted as Excepted Quantity

#### IATA:

Remarks: Referring to the Certification for Safe Transport of Chemical Goods (Report No. 202300709671607) issued by Shanghai Institute of Chemical Industry Testing Co., Ltd, AA Nickel Metal Hydride Battery is tested / assessed and is not subject to IATA Dangerous Goods Regulations.

(DGR) 64th Edition to special provision A199 (Effective Date 2023-01-01) (upon supplier's information)



# **Material Safety Data Sheet**

# 15. Regulatory information

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

| MAK(German Maximum Workplace Concentration) |                    |   |
|---|--------------------|---|
| 7440-02-0                                   | Nickel             | 1 |
| 12054-48-7                                  | Nickel dihydroxide | 1 |
| 7440-48-4                                   | Cobalt             | 2 |

#### Directive 2012/18/EU:

Named dangerous substances - ANNEX I: None of the ingredients is listed.

Seveso category: E1 Hazardous to the Aquatic Environment

Qualifying quantity (tonnes) for the application of lower-tier requirements: 100 t Qualifying quantity (tonnes) for the application of upper-tier requirements: 200 t

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

#### National regulations:

#### Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

Water hazard class: Water hazard class 3 (Self-assessment): extremely hazardous for water.

Other regulations, limitations and prohibitive regulations:

SVHC Candidate List of REACH Regulation Annex XIV Authorisation (10/06/2022)

None of the ingredients is listed.

### REACH Regulation Annex XVII Restriction (13/12/2021)

See Section 16 for information about restriction of use.

None of the ingredients is listed.

#### REACH Regulation Annex XIV Authorisation List (08/04/2022)

None of the ingredients is listed.

### 15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.



# **Material Safety Data Sheet**

## 16. Other information

#### Relevant hazard statements

| H228  | Flammable solid.   |
|-------|--|
| H302  | Harmful if swallowed.  |
| H314  | Causes severe skin burns and eye damage.   |
| H315  | Causes skin irritation.  |
| H317  | May cause an allergic skin reaction.   |
| H318  | Causes serious eye damage.   |
| H332  | Harmful if inhaled.  |
| H334  | May cause allergy or asthma symptoms or breathing difficulties if inhaled.                                     |
| H341  | Suspected of causing genetic defects.  |
| H350  | May cause cancer.  |
| H350i | May cause cancer by inhalation.  |
| H351  | Suspected of causing cancer.   |
| H360D | May damage the unborn child.   |
| H360F | May damage fertility.  |
| H372  | Causes damage to the respiratory system through prolonged or repeated exposure. Route of exposure: Inhalation. |
| H400  | Very toxic to aquatic life.  |
| H410  | Very toxic to aquatic life with long lasting effects.  |
| H413  | May cause long lasting harmful effects to aquatic life.  |

## Classification according to Regulation (EC) No. 1272/2008

| Flammable solids  | Bridging principles   |
|---|---|
| Acute toxicity - oral   | The classification of the mixture is generally based on the                         |
| Skin corrosion/irritation   | calculation method using substance data according to Regulation (EC) No. 1272/2008. |
| Serious eye damage/eye irritation   | 1109diation (20) 110. 1212/2000.  |
| Respiratory sensitisation   |   |
| Skin sensitisation  |   |
| Germ cell mutagenicity  |   |
| Carcinogenicity   |   |
| Reproductive toxicity   |   |
| Specific target organ toxicity (repeated exposure)                        |   |
| Hazardous to the aquatic environment – short-term (acute) aquatic hazard  |   |
| Hazardous to the aquatic environment – long-term (chronic) aquatic hazard |   |

The contents and format of this SDS are in accordance with Regulation (EC) No 1907/2006, 1272/2008 and Regulation (EU) No 2015/830.



# **Material Safety Data Sheet**

#### DISCLAIMER OF LIABILITY

The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reason, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.

#### Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Sol. 1: Flammable solids - Category 1

Acute Tox. 4: Acute toxicity - oral - Category 4

Skin Corr. 1A: Skin corrosion/irritation - Category 1A

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Muta. 2: Germ cell mutagenicity - Category 2

Carc. 1A: Carcinogenicity - Category 1A

Carc. 1A: Carcinogenicity - Category 1Ai

Carc. 1B: Carcinogenicity - Category 1B

Carc. 2: Carcinogenicity - Category 2

Repr. 1B: Reproductive toxicity - Category 1B

STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4