



ALPHA 160 DIN, WALL-MOUNTED DB, SM  
PARTIALLY EQ. W. RAPID MOUNTING KIT FOR  
BUILT-IN DEV., RAL 9016, IP43, SK2, H=500 W=550  
D=140

Protection class		
Protection class IP		IP43
Mechanical Design		
Height	mm	500
Width	mm	550
Depth	mm	140
Installation depth	mm	140
Material / of the enclosure		sheet steel/plastic

General Product Approval	Declaration of Conformity	Test Certificates
--------------------------	---------------------------	-------------------



[other](#)



[other](#)

[Special Test Certificate](#)

## Test Certificates

[Type Test Certificates/Test Report](#)

## Further information

Information- and Downloadcenter (Catalogs, Brochures,...)  
<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/8GK10521KK21>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<http://support.automation.siemens.com/WW/view/en/8GK10521KK21/all>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**


[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=8GK10521KK21](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8GK10521KK21)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://ausschreibungstexte.siemens.com/tiplv>



last modified:

11.03.2015