

PTSI 4/LD 400V AC**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



Power distribution using uncut cables with cross-sections from 1.5 to 6 mm².

Power supply / T-branch tap via PUSH IN connection (0.5 to 10 mm²) and/or plug-in connection (0.5 to 4 mm²).

Coloured markings provide clear assignment of wires.

- Power supply
- Power distribution
- Power branching

General ordering data

Version	FieldPower®, Field Power® plug-in connector, PUSH IN, 0.5 mm ² - 4 mm ²
Order No.	1961770000
Type	PTSI 4/LD 400V AC
GTIN (EAN)	4032248641765
Qty.	1 pc(s).

Creation date May 2, 2022 9:15:58 AM CEST

Catalogue status 22.04.2022 / We reserve the right to make technical changes.

PTSI 4/LD 400V AC

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data
Dimensions and weights

Depth	55 mm	Depth (inches)	2.165 inch
Height	85 mm	Height (inches)	3.346 inch
Width	57 mm	Width (inches)	2.244 inch
Net weight	100 g		

Temperatures

Continuous operating temp., min.	-50 °C	Continuous operating temp., max.	120 °C
----------------------------------	--------	----------------------------------	--------

Clamping capacity, IDC connection - PT6

Blade size	3.0 x 0.5 mm	Connection cross-section, finely stranded, max.	4 mm ²
Connection cross-section, finely stranded, min.	0.5 mm ²	Wire connection cross section, finely stranded, max.	4 mm ²
Wire connection cross section, finely stranded, min.	0.5 mm ²	Wire cross-section, solid, max.	4 mm ²
Wire cross-section, solid, min.	0.5 mm ²		

PTSI 4/LD 400V AC

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Clamping capacity, PUSH IN connection - PT6

Blade size	3.0 x 0.5 mm	Blade size, PUSH IN connection	3.0 x 0.5 mm
Conductor cross-section, flexible AEH 12 mm plus plastic collar DIN 46228/1, rated connection, min.	0.5 mm ²	Conductor cross-section, flexible AEH 12 mm plus plastic collar DIN 46228/4, rated connection, max.	4 mm ²
Conductor cross-section, flexible AEH 12 mm plus plastic collar DIN 46228/4, rated connection, min.	0.5 mm ²	Conductor cross-section, flexible AEH 8 mm plus plastic collar DIN 46228/1, rated connection, max.	4 mm ²
Conductor cross-section, flexible AEH 8 mm plus plastic collar DIN 46228/1, rated connection, min.	0.5 mm ²	Conductor cross-section, flexible AEH 8 mm plus plastic collar DIN 46228/4, rated connection, max.	4 mm ²
Conductor cross-section, flexible AEH 8 mm plus plastic collar DIN 46228/4, rated connection, min.	0.5 mm ²	Cross-section for connected wire PUSH IN connection, solid, min.	0.5 mm ²
Cross-section for connected wire, PUSH IN connection, solid, max.	4 mm ²	Cross-section for connected wire, flexible with wire-end ferrules, 12mm with plastic collar, DIN 46228/1, PUSH IN connection, max.	4 mm ²
Cross-section for connected wire, flexible with wire-end ferrules, 12mm with plastic collar, DIN 46228/1, PUSH IN connection, min.	0.5 mm ²	Cross-section for connected wire, flexible with wire-end ferrules, 12mm with plastic collar, DIN 46228/4, PUSH IN connection, max.	4 mm ²
Cross-section for connected wire, flexible with wire-end ferrules, 12mm with plastic collar, DIN 46228/4, PUSH IN connection, min.	0.5 mm ²	Cross-section for connected wire, flexible with wire-end ferrules, 8mm with plastic collar, DIN 46228/1, PUSH IN connection, max.	4 mm ²
Cross-section for connected wire, flexible with wire-end ferrules, 8mm with plastic collar, DIN 46228/1, PUSH IN connection, min.	0.5 mm ²	Cross-section for connected wire, flexible with wire-end ferrules, 8mm with plastic collar, DIN 46228/4, PUSH IN connection, max.	4 mm ²
Cross-section for connected wire, flexible with wire-end ferrules, 8mm with plastic collar, DIN 46228/4, PUSH IN connection, min.	0.5 mm ²	Cross-section for connected wire, flexible, PUSH IN connection, max.	4 mm ²
Cross-section for connected wire, flexible, PUSH IN connection, min.	0.5 mm ²	Cross-section for connected wire, stranded, two clampable wires, max.	0.5 mm ²
Cross-section for connected wire, stranded, two clampable wires, min.	4 mm ²	Finely-stranded flexible, max. PUSH IN connection	4 mm ²
Finely-stranded flexible, min. PUSH IN connection	0.5 mm ²	Stripping length	12 mm
Stripping length, PUSH IN connection	12 mm		

PTSI 4/LD 400V AC

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Clamping capacity, PUSH IN connection

Blade size, PUSH IN connection	3.0 x 0.5 mm	Clamping range, max. PUSH IN connection	4 mm ²
Clamping range, min. PUSH IN connection	0.5 mm ²	Cross-section for connected wire PUSH IN connection, solid, min.	0.5 mm ²
Cross-section for connected wire, PUSH IN connection, solid, max.	4 mm ²	Cross-section for connected wire, flexible with wire-end ferrules, 12mm with plastic collar, DIN 46228/1, PUSH IN connection, max.	4 mm ²
Cross-section for connected wire, flexible with wire-end ferrules, 12mm with plastic collar, DIN 46228/1, PUSH IN connection, min.	0.5 mm ²	Cross-section for connected wire, flexible with wire-end ferrules, 12mm with plastic collar, DIN 46228/4, PUSH IN connection, max.	4 mm ²
Cross-section for connected wire, flexible with wire-end ferrules, 12mm with plastic collar, DIN 46228/4, PUSH IN connection, min.	0.5 mm ²	Cross-section for connected wire, flexible with wire-end ferrules, 8mm with plastic collar, DIN 46228/1, PUSH IN connection, max.	4 mm ²
Cross-section for connected wire, flexible with wire-end ferrules, 8mm with plastic collar, DIN 46228/1, PUSH IN connection, min.	0.5 mm ²	Cross-section for connected wire, flexible with wire-end ferrules, 8mm with plastic collar, DIN 46228/4, PUSH IN connection, max.	4 mm ²
Cross-section for connected wire, flexible with wire-end ferrules, 8mm with plastic collar, DIN 46228/4, PUSH IN connection, min.	0.5 mm ²	Cross-section for connected wire, flexible, PUSH IN connection, max.	4 mm ²
Cross-section for connected wire, flexible, PUSH IN connection, min.	0.5 mm ²	Finely-stranded flexible, max. PUSH IN connection	4 mm ²
Finely-stranded flexible, min. PUSH IN connection	0.5 mm ²	Stripping length, PUSH IN connection	12 mm

General information #96 connectors

Can be coded	Yes, Coded on PE	Cartridge fuse	6.3 x 32 mm (1/4 x 1 1/4")
Colour of insulating material	black	Conductor outlet direction	90°
Continuous operating temp., max.	120 °C	Continuous operating temp., min.	-50 °C
Failure indicator	Red LED	Fuse holder (cartridge holder)	Pivoting
Number of connections / pole	1	Plug insulation material	PA
Test point	2 mm	Type of mounting	Plugged
UL 94 flammability rating	V-0	Wire connection method	PUSH IN
lockable	Yes		

General data

Can be coded	Yes, Coded on PE	Insulating material	PA
UL 94 flammability rating	V-0		

Rated data acc. to IEC

Rated cross-section	4 mm ²	Rated current	12 A
Rated impulse withstand voltage	6 kV	Rated voltage	500
Standards	IEC 60947-7-3, UL 1059		

PTSI 4/LD 400V AC

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data

Rated data acc. to UL

Rated current (Use group D / UL 1059)	20 A	Rated voltage (Use group D / UL 1059)	600 V
Standards	IEC 60947-7-3, UL 1059	Wire connection cross section AWG, max.	AWG 12
Wire connection cross section AWG, min.	AWG 16		

Classifications

ETIM 6.0	EC002943	ETIM 7.0	EC002943
ETIM 8.0	EC002943	ECLASS 9.0	27-44-02-92
ECLASS 9.1	27-44-03-90	ECLASS 10.0	27-44-02-92
ECLASS 11.0	27-44-02-92		

Approvals

Approvals



ROHS	Conform
UL File Number Search	E60693

Downloads

Approval/Certificate/Document of Conformity	UL Certificate FieldPower® terminals and plug-in connectors Manufacturer's Declaration FieldPower® plug-in connectors and HQ adapters
Engineering Data	CAD data – STEP
Catalogues	Catalogues in PDF-format

Data sheet

PTSI 4/LD 400V AC

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

