





Features:

- Toroidal ferrite cores which attenuate electrical noise in signal and data cables
- Applications include digital audio systems, computers and peripherals and any sensitive electronic equipment

Specifications:

Ferrite Case Style : Toroid
 Impedance : 86Ω
 Frequency Range : 25MHz to 100MHz
 Impedance @ 25MHz Typ : 40Ω
 Impedance @ 100MHz Typ : 125Ω
 Package / Case : Tubular



Dimensions

Outer Diameter (A)	Height (B)	Inner Diameter (C)
16 ±0.3	14 ±0.4	10 ±0.25

Dimensions : Millimetres

Part Number Table

Description	Part Number
Ferrite Core, Toroid, 10mm	33RI 16X14X10

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.