



# FWDFXX \*1) SA

e.g. FWDF15SA

\*1) xx No. of contacts 09, 15 or 25

xx	A mm	B mm	C mm
09	40	16.4	25
15	48.3	24.7	33.3
25	62	38.5	47.04

\*2) Dimension starts from front surface of shell (Part-No. 2)

max. torque are 40 Ncm  
 D-Sub connector with watertight frame,  
 Protection standard IP67, 100% checked  
 according to DIN EN 60529 (compl. mounted)

No.	St.	Part	Type Description/Material	Surface plating/Colour/Class
6	2	Threaded spacer	4-40/4-40 / Brass	tin plated
5	xx	Signal contact	S0 / Brass	AutoPlur / 0.1-0.2µm Au / AWG 20
4	1	O-ring seal	Silicone / UL94V-0	red
3	1	Watertight frame	PBT	black
2	1	Shell	Brass	tin plated
1	1	Insulator	PBT (-25°C - +70°C)	red

Measurement without tolerance acc. to ISO 2768-m	SCALE	TITLE
	2:1	
NAME / DATE		
toland.schneider		
10.07.2013		
CHECKED		
Anke Meyer-Richter		
11.07.2013		

REV.	DATE	CH.-NO.	DWG.NO.	REPLACEMENT FOR:	PAGES
1			FWDFxxSA	FWDFxxSA	1
					1



ORIGINAL: DIN A3-DRAWING AS A FILE