

NEXT STEP



atlas[®]
the shoe company



FLASH 4615 | ESD

Art.

- :EN ISO 20345 S1P SRC size
- :XP® metal free puncture-resistance 35-50
- :alu-tec® aluminium toecap
- :3D-cushioning system
- :Sportline upper
- :aktiv-X lining
- :clima-stream® concept
- :ESD-fitting
- :available in width 10 / 12 / 14
- :MPU® INNOFLEX System



alu-tec[®]
INSIDE



Flash 5405 | ESD

Art. 209

- :EN ISO 20345 S3 SRC size
- :XP® metal free puncture-resistance 36-49
- :alu-tec® aluminium toecap
- :3D-cushioning system
- :Sportline upper
- :aktiv-X lining
- :ESD-fitting
- :adapted for orthopedic insoles
- :MPU® INNOFLEX System



alu-tec[®]
INSIDE



SIZES
36 - 49



GX 130 black 2.0 | ESD

Art. 452

- :EN ISO 20345 S1 SRC size
- :3D-cushioning system 35-43
- :Sportline upper
- :aktiv-X lining
- :clima-stream® concept
- :ESD-fitting
- :MPU Light sole technology
- :adapted for orthopedic insoles
- :women's fit - besondere Damenpassform



AKTIV-X



SIZES
35 - 43



alu-tec[®]
INSIDE



SL 80 2.0 blue | ESD

Art. 447

- :EN ISO 20345 S2 SRC size
- :alu-tec[®] aluminium toecap 36-49
- :3D-cushioning system
- :SOFT-Nubuck leather
- :Safety reflectors
- :aktiv-X lining
- :ESD-fitting
- :also available in W12
- :adapted for orthopedic insoles
- :MPU[®] INNOFLEX System

SIZES
36 - 49



alu-tec[®]
INSIDE



SL 82 2.0 blue | ESD

Art. 449

- :EN ISO 20345 S1 SRC size
- :alu-tec[®] aluminium toecap 36-49
- :3D-cushioning system
- :Sportline upper
- :aktiv-X lining
- :clima-stream[®] concept
- :ESD-fitting
- :also available in W12
- :adapted for orthopedic insoles
- :MPU[®] INNOFLEX System

SIZES
36 - 49



3D



SIZES
35 - 43

CX 40 women | ESD

Art. 289

- :EN ISO 20345 S1 size
- :3D-cushioning system 35-43
- :aktiv-X lining
- :clima-stream[®] concept
- :ESD-fitting
- :steelcap
- :MPU[®] sole technology
- :women's fit - besondere Damenpassform
- :interchangeable insole with heel cushioning



CX 505 | ESD

Art. 346

- :EN ISO 20345 1P SRC size
- :Penetration resistance 39-48
- :3D-cushioning system
- :aktiv-X lining
- :clima-stream® concept
- :ESD-fitting
- :steelcap
- :MPU® sole technology
- :adapted for orthopedic insoles
- :interchangeable insole with heel cushioning



SIZES
39 - 48



XR 485 XP | ESD

Art. 414

- :EN ISO 20345 S3 SRC size
- :XP® metal free puncture-resistance 36-49
- :alu-tec® aluminium toecap
- :3D-cushioning system
- :Top cap
- :aktiv-X lining
- :ESD-fitting
- :Large stud profile
- :adapted for orthopedic insoles
- :Oiled nubuck
- :XR-Sohlentechnologie



SIZES
36 - 49



XC 420 | ESD

size
35-50

- :EN ISO 20345 S2 SRC
- :3D-cushioning system
- :aktiv-X lining
- :Side pull-on loop
- :clima-stream® concept
- :ESD-fitting
- :available in width 10 / 12 / 14
- :MPU® INNOFLEX System

