

T1-T1^{3/4} Bi-Polar LEDs unbased

- Dual-Chip LED, Bi-Polar
- Independent of Polarity
- Suitable for AC/DC

- Dual-Chip LED, Bi-Polar
- Polaritätsunabhängig
- Geeignet für AC/DC

- Dual-Chip LED, Bi-Polaire
- Indépendance des Polarités
- Appropriée pour AC/DC

All specifications according to information from our manufacturers, without additional guarantee on our part. Further types on request.

Alle Spezifikationen basieren auf Angaben unserer Lieferanten, ohne zusätzliche Garantie unsererseits. Weitere Typen auf Anfrage.

Toutes les spécifications selon indications de nos fabricants, sans garantie supplémentaire de notre part. Autres types sur demande.

L3
No. 49



L5
No. 59



Actual size
Größe 1:1
Echelle 1:1

SLOAN AG
Birmannsgasse 8
CH-4009 Basel
Switzerland
Tel.: +41 (0) 61 264 10 60
Fax: +41 (0) 61 264 10 75
E-Mail: sloan@sloan-basel.com
www.sloan-basel.com

Package dimensions All dimensions are in millimeters	No.	Emitted colour	Epoxy of LED	Electro-optical characteristics Ta = 25°C								Price-code Preis-Code Code de prix	Type Typ Type	Resistor Widerstand Résistance											
				Peak Wave-length λp nm	Operat. Temp. °C	Stor. Temp. °C	Luminous intensity Iy			Forward voltage VF				Code	V	mA									
							Viewing Angle	Typ. mcd	IF mA	Typ. V	Max. V						IF mA								
<p>L3</p>	49	Red	TL	625	- 40	- 40	60°	40	20	2.0	2.5	20	RR3F	O	without ohne sans										
		Red		625						2.0	2.5														
		Green		565						2.2	2.5														
		Green		565						2.2	2.5														
		Yellow		590						2.1	2.5														
		Yellow		590						2.1	2.5														
<p>L5</p>	59	Red	TL	660	- 40	- 40	60°	200	20	1.85	2.5	20	RR5W	H	36	15									
		Red		660						1.85	2.5														
		Green		565						2.2	2.5														
		Green		565						2.2	2.5														
		Yellow		590						2.1	2.5														
		Yellow		590						2.1	2.5														
		Other V/mA combinations on request Andere V/mA Kombinationen auf Wunsch Autres V/mA combinations sur demande																							
		<div style="display: flex; justify-content: space-between;"> RR3F GG3F YY3F </div>																							
		<div style="display: flex; justify-content: space-between;"> RR5W GG5F YY5F </div>																							
		<div style="display: flex; justify-content: space-between;"> RR3F GG3F YY3F </div>																							
<div style="display: flex; justify-content: space-between;"> RR5W GG5F YY5F </div>																									


① TL translucent / colour diffused

TL farbig durchscheinend

TL transparent coloré

Alternative or direct current can be applied – without a rectifier.
An excellent side visibility is provided using the Bipolars in our indicator Series 175, 176–178 and 355.
With our Bipolar LEDs the anode/cathode problem – is no longer a problem:

Order-code
Bestell-code
Code de commande



Reserve de modifications de toutes les données techniques
Änderungen die dem technischen Fortschritt dienen, sind vorbehalten
Specifications subject to change without notice