

Product / Process Change Notification (PCN)

- Major change
 Minor change

PCN #: PCN_IndRCIS_20220212

Affected Series: WE-IndRCIS; 7847229020

PCN Date: November 12, 2021

Effective Date: February 12, 2022

Change Category:

- Equipment / Location
 General Data
 Material
 Process
 Product Design
 Shipping / Packaging
 Supplier
 Software

Contact: Product Management

Phone: +49 (0) 7942 - 945 5001

Fax: +49 (0) 7942 - 945 5179

E-Mail: pcn.eisos@we-online.com

Data Sheet Change:

- Yes No

Attachment:

- Yes No

DESCRIPTION AND PURPOSE OF CHANGE:

As a datasheet information amendment, Würth Elektronik will correct the packaging tape and reel (shape and dimension) of the datasheet from the WE-IndRCIS, PN 7847229020.

This is a datasheet correction only. There will be no change in form, fit, function, quality or reliability of the product.

DETAIL OF CHANGE:

BEFORE CHANGE

Tape dimensions

Tape Type	A0 (mm)	B0 (mm)	W (mm)	T (mm)	T1 (mm)	T2 (mm)	K0 (mm)	P0 (mm)	P1 (mm)	P2 (mm)	D0 (mm)	D0 / 2 (mm)	D1 (mm)
	typ.	typ.	±0,3	ref.	max.	typ.	typ.	±0,1	±0,1	±0,1	+0,1	+0,05	min.
3	10,55	18,40	32,00	0,50	0,10	10,10	9,90	4,00	16,00	2,00	1,50	0,75	2,00
d (mm)	E (mm)	S (mm)	F (mm)	Material	Qty. (pcs.)								
±0,05	±0,1	±0,1	±0,1										
0,20	1,75	28,40	14,20	Polystyrene	300								

Würth Elektronik eiSos GmbH & Co. KG

EMC & Inductive Solutions

Max-Eyth-Straße 1 · 74638 Waldenburg · Germany

Tel. +49(0)79 42 945-0 · Fax +49(0)79 42 945-400

eiSos@we-online.de · www.we-online.de



Reel Dimensions

A (mm)	B (mm)	C (mm)	D (mm)	N (mm)	W1 (mm)	W2 (mm)	W3 (mm)	W3 (mm)	Material
± 2,0	min.	min.	min.	+ 2,0	+ 2,0	max	min	max.	
330,00	1,50	12,80	20,20	80,00	32,40	38,40	31,90	35,40	Polysytrene/Polyurethane

AFTER CHANGE

Tape Dimensions

Tape Type	A0 (mm)	B0 (mm)	W (mm)	T (mm)	T1 (μ m)	T2 (mm)	K0 (mm)	P0 (mm)	P1 (mm)	P2 (mm)	D0 (mm)	D0 / 2 (mm)	D1 (mm)
	±0,2	±0,2	±0,3	±0,05	typ	±0,15	±0,10	±0,1	±0,1	±0,1	+0,1	typ	+0,1
3	10,6	18,75	44	0,50	46	10,85	10,35	4,00	16,00	2,00	1,50	0,75	2,00
d (mm)	E (mm)	S (mm)	F (mm)	Material	Qty. (pcs.)								
typ	±0,1	±0,1	±0,15										
0,20	1,75	40,4	20,2	PE 875	300								

Reel Dimensions

A (mm)	B (mm)	C (mm)	D (mm)	N (mm)	W1 (mm)	W2 (mm)	W3 (mm)	W3 (mm)	Material
± 2,0	min.	min.	min.	min.	+ 2,0	max.	min.	max.	
330,00	1,50	12,80	20,20	80,00	44,40	50,40	43,90	47,40	Polysytrene

RELIABILITY / QUALIFICATION SUMMARY:

There will be no change of the product, therefore no additional reliability or qualification testing will be performed.