



VER-26980



VER-26978

Property	Value
Colour	Yellow
Size of plug casing	63mm x 49mm x 49mm
Weight	36g
Connector to earth pin resistance	0.8 - 1.2 megohm
Connector to connector resistance	approx 2 megohm

Item	Description
VER-26980	EBP, EUROPE, 2x4MM SOCKETS, 1x10MM STUD
VER-26978	EBP, PLUG, EUROPE, 2x10MMSTUDS 1x4MM STUD

“Common ground point, grounded device or location where the conductors of two or more ESD control items are bonded” [EN 61340-5-1]

Description

- To fit UK European CEE (7) VII Schuko sockets as used in Belgium, France, Germany, Holland, Spain.
- The Vermason Earth Bonding Point (EBP) plug is designed to provide a common ground point for grounding using protective earth in an ESD protected area (EPA). The plug fits into the mains supply socket, making a connection with the earth conductor only. In place of the live and neutral pins are moulded insulating plastic pins to allow positive location in the socket. Connectors on the front of the plug are available for connection via ground cords to the various elements of the EPA. Thus each element is held at a common potential.
- A resistance of sufficient resistance to limit current to less than 0.0005 amperes (0.5 milliamperes), at the highest voltage that may be encountered, should be incorporated. Nominally, 800 kilohms are sufficient for voltages of up to 240 volts alternating current (AC). The value of one megohm is specified because it is a standard value discrete resistor. Follow appropriate regulatory or company safe grounding instructions. (Ref: ANSI/ESD S1.1)
- DO NOT open or try to repair. Test the plug by measuring the resistance from each termination to the Earth pin. Resistance should be between 0.8 and 1.2 megohm.
- It is virtually impossible to misuse the plug, which is permanently sealed. The resistance between the terminations and the pin of each plug is tested after manufacture.
- Check that the connectors on the plug face correspond with the terminations on the wrist strap and ground cords: several variations of the plug are available. Insert the EBP plug into a mains supply socket and push it fully home. The plug functions whether the socket is switched off or on. Connect the elements of the EPA such as bench and floor mats to the EBP plug face using ground cords.
- The plug is ONLY to be used for ESD control purposes.
- ONLY use ground cords with compatible connections to those on plug. Vermason supply EBP plugs with terminations for all standard ground cords.
- NOT to be used for earthing electrical appliances
- To avoid the need for unduly long ground cords and to simplify the daily visual check, that all connections are sound and in place, an EBP plug should not be shared by more than two work stations.
- The EBP plug may also be used in conjunction with a Vermason EBP box or bar installed at the front of a bench for easier connecting of wrist straps for example.
- EBP plugs are packed and labelled individually in an antistatic polyethylene bag.

Unless otherwise noted, tolerance $\pm 10\%$
Specifications and procedures subject to change without notice.



Made in the
United Kingdom

Vermason

European Earth Bonding Plug

VERMASON
UNIT C, 4TH DIMENSION, FOURTH AVENUE, LETCHWORTH,
HERTS, SG6 2TD UK
PHONE: +44 (0) 1462-672005
E-MAIL: Service@Vermason.co.uk, INTERNET: Vermason.co.uk

Drawing Number
VER-26980

DATE:
September
2015