



Signalling switch ready to switch on, 1W (IZMX-SR)

Part no. IZMX-LCS-SR-1
Article no. 184106
Catalog No. 67C2814G31

Delivery programme

Product range		Accessories
Accessories		Auxiliary contact
Accessories		Operational readiness indicator with plug for direction connection to spring release
		Automatic closing after readiness for operation. Can only be used together with a closing release
For use with		IZMX16..., IZMX40... INX16..., INX40...
Instructions		Can be used with IZMX16(40)-SR... closing release for automatic closing upon availability
		1 changeover contact

Technical data

Rated breaking capacity

Inductive load			
250 V AC		A	10
125 V DC		A	0.5
250 V DC		A	0.25

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	70

Technical data ETIM 6.0

Low-voltage industrial components (EG000017) / Auxiliary contact block (EC000041)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Auxiliary switch block (ecl@ss8.1-27-37-13-02 [AKN342010])			
Number of contacts as change-over contact			1
Number of contacts as normally open contact			0
Number of contacts as normally closed contact			0
Rated operation current I _e at AC-15, 230 V		A	10
Type of electric connection			Flat plug-in connection
Model			Half-integrated
Mounting method			-