

SENCITY® Road VHF Antenna K5022211-R

Description

Broadband vehicle VHF antenna for bus and tram.
Support VHF band within 143-162 MHz.
Rugged design with fiberglass radome.
Meets EN 50155 Railway Standard.
Fire retardant according to EN 45545-2.
Gain dB 0 (ref. to the quarter-wave antenna).



Product Configuration

Technical Data

Electrical Data

Band 1	
Band Name	FM
Frequency (MHz)	143 - 162
VSWR	2
Impedance (Ohm)	50
Composite power max (W)	100
Ambient temperature (°C)	50

Ports

Port 1	
Port name	FM
Connector	N, jack (female)
Polarization	vertical
DC grounded	Yes

Connections

Band 1	
Port 1	X

General Data

Requires mounting on a conductive surface 1.0 x 2.0 m minimum with 3 studs M10 and counterflange.
Recommended torque: 14 Nm. Preferred frequency range 146-156 MHz with VSWR <<2.
Note: No superstructures in this area.

Mechanical Data

Dimensions (mm) 225 x 252 x 126 (Height x Width x Depth)
Weight (kg) 1.2

Radiator and Base: Aluminum.
Radome: Fiberglass, colour: Grey.
Studs and all screws and nuts: Stainless steel.
Sealing: Neoprene and polyurethane.
Note: Don't use detergents that might harm the sealing.

DC grounded to protect against lightning.

Packaging size (outside): 260 x 260 x 130 mm

SENCITY® Road VHF Antenna K5022211-R

Environmental Data

Environmental conditions	outdoor
Operation temperature (°C)	-40 to 85
Storage temperature (°C)	-55 to 85
IP rating	IP66
Flammability rating	EN 45545-2
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant
WEEE 2012/19/EU	no special marking needed
REACH 1907/2006/EC	compliant

Environmental tests: ISO 50155

Material Data

Radome colour	grey
Back plate/base plate colour	black
Back plate/base plate material	Aluminium

Related Documents

Mounting instruction	DOC-0000851877
Painting instruction	DOC-0000256180
Security instruction	DOC-0000278984
Outline drawing	DOU-00485617
3D-model	DOC-0000914708