



Figure can vary

Part no.: 50106732
ODSLR 96B M/C6-2000-S12
Optical distance sensor



Contents

- Technical data
- Electrical connection
- Operation and display
- Accessories

Technical data

Basic data	
Series	96
Type of scanning system	Against object
Optical data	
Light source 1	Laser , Red
Laser class	2 ,
Light source 2	LED , Red
Light spot size [at sensor distance]	2 mm x 6 mm []
Type of light spot geometry	Rectangular
Measurement data	
Measurement range	60 ... 2,000 mm
Resolution	1.0 ... 5.0 mm
Accuracy, short range	2 %
Accuracy, distant range	1.5 %
Accuracy, short range	60 ... 200 mm
Reference value, accuracy	Measurement distance
Repeatability	0.5 %
Reference value repeatability	Measurement distance
Measurement time	1 ... 5 ms
Referencing	No
Black/white behavior	1 %
Electrical data	
Protective circuit	Polarity reversal protection Short circuit protected Transient protection
Performance data	
Supply voltage U_B	18 ... 30 V , DC
Current consumption, max.	
Residual ripple	0 ... 15 % , From U_B
Open-circuit current	0 ... 150 mA
Inputs	
Number of digital switching inputs	1 Piece(s)
Switching inputs	
Digital switching input 1	
Function	Programmable
Teach inputs	
Voltage type	DC
Switching voltage	High: $\geq(U_B-2V)$

Outputs

Number of analog outputs	1 Piece(s)
Number of digital switching outputs	1 Piece(s)

Analog outputs
Analog output 1

Type	Current
------	---------

Switching outputs

Switching voltage	High: $\geq(U_B-2V)$
-------------------	----------------------

Switching output 1

Switching element	Transistor , Push-pull
-------------------	------------------------

Timing
Connection

Number of connections	1 Piece(s)
-----------------------	------------

Connection 1

Type of connection	Connector
Function	Signal IN Signal OUT Voltage supply
Thread size	M12
Type	Male
Material	Metal
No. of pins	5 -pin
Encoding	A-coded

Mechanical data

Design	Cubic
Dimension (W x H x L)	30 mm x 90 mm x 70 mm
Housing material	Metal , Diecast zinc
Lens cover material	Glass
Net weight	380 g
Housing color	Red
Type of fastening	Through-hole mounting Via optional mounting device

Operation and display

Type of display	LED OLED display
Type of configuration	Software
Operational controls	Membrane keyboard PC software

Environmental data

Ambient temperature, operation	-20 ... 50 °C
Ambient temperature, storage	-30 ... 70 °C

Certifications

Degree of protection	IP 67 IP 69K
Protection class	II

Part no.: 50106732 – ODSL R 96B M/C6-2000-S12 – Optical distance sensor

Certifications	c UL US
Standards applied	IEC 60947-5-2

Classification

Customs tariff number	90318020
eCl@ss 8.0	27270801
eCl@ss 9.0	27270801
ETIM 5.0	EC001825
ETIM 6.0	EC001825

Electrical connection

Connection 1	
Type of connection	Connector
Function	Signal IN Signal OUT Voltage supply
Thread size	M12
Type	Male
Material	Metal
No. of pins	5 -pin
Encoding	A-coded


Operation and display

LEDs


LED	Display	Meaning
1		
2		

Accessories


Connection technology - Connection cables

	Part no.	Designation	Article	Description
	50132077	KD U-M12-5A-V1-020	Connection cable	Connection 1: Connector, M12, Axial, Female, A-coded, 5 -pin Connection 2: Open end Shielded: No Cable length: 2,000 mm Sheathing material: PVC


Part no.: 50106732 – ODSL R 96B M/C6-2000-S12 – Optical distance sensor


	Part no.	Designation	Article	Description
	50133842	KD U-M12-5W-V1-020	Connection cable	Connection 1: Connector, M12, Angled, Female, A-coded, 5 -pin Connection 2: Open end Shielded: No Cable length: 2,000 mm Sheathing material: PVC

Mounting technology - Mounting brackets

	Part no.	Designation	Article	Description
	50025570	BT 96	Mounting device	Design of mounting device: Angle, L-shape Fastening, at system: Through-hole mounting Mounting bracket, at device: Screw type Type of mounting device: Rigid Material: Metal

Mounting technology - Rod mounts

	Part no.	Designation	Article	Description
	50082084	BT 450.1-96	Mounting device	Design of mounting device: Mounting system Fastening, at system: For 10 mm rod Mounting bracket, at device: Screw type Type of mounting device: Turning, 360°, Adjustable Material: Metal

	Part no.	Designation	Article	Description
	50107223	UPG 10	Configuration adapter	Functions: Configuration and test device

Note

A list with all available accessories can be found on the Leuze electronic website in the Download tab of the article detailed page.