

Product Search Data Sheet

Note: This datasheet may be out of date.

Please download the latest datasheet of DLM0NSB280HY2# from the official website of Murata Manufacturing Co., Ltd.


https://www.murata.com/en-eu/products/productdetail?partno=DLM0NSB280HY2%23

DLM0NSB280HY2#


"#" indicates a package specification code.

In Production RoHS REACH

< List of part numbers with package codes > DLM0NSB280HY2B DLM0NSB280HY2D







Features

1. Small size and tight dimensional tolerance

Size: 0.85×0.65×0.45mm

- Tolerance: +-0.05mm
- 2. Suitable common mode impedance of 12 or 28 ohm(at 100MHz) for high speed signal lines.
- 3. Prevents signal damaging in high speed differential lines.
- 4. Designed to match line impedance.

Applications

Limited Usage	For differential signal interface line
Other Usage	For general

Packaging Information

Packaging	Specifications	Minimum Order Quantity
В	Bulk(Bag)	500
D	180mm Paper Tape	10000

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Note: This datasheet may be out of date

Please download the latest datasheet of DLM0NSB280HY2# from the official website of Murata Manufacturing

Co., Ltd. https://www.murata.com/en-eu/products/productdetail?partno=DLM0NSB280HY2%23

DLM0NSB280HY2#

"#" indicates a package specification code.

Specifications

Shape	SMD	Cut-off Frequency	8.0GHz (Typ.)
Size Code (in mm)	0806	Operating Temperature Range	-40℃ to 85℃
Size Code (in inch)	03025	Mass(typ.)	0.9mg
Length	0.85mm	Number of Circuit	1
Length Tolerance	±0.05mm	Operating Temperature Range(Self- temperature rise is included)	No
Width	0.65mm		
Width Tolerance	±0.05mm		
Thickness	0.45mm		
Thickness Tolerance	±0.05mm		
Common Mode Impedance (at 100MHz)	28Ω		
Common Mode Impedance (at 100MHz) Tolerance	±30%		
Rated Current	130mA		
Rated Voltage	5Vdc		
Withstanding Voltage	12.5Vdc		
DC Resistance(max.)	2.375Ω		
DC Resistance	1.9Ω±25%		
Insulation Resistance(min.)	10ΜΩ		

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



Note: This datasheet may be out of date

Please download the latest datasheet of DLMONSB280HY2# from the official website of Murata Manufacturing Co., Ltd.


https://www.murata.com/en-eu/products/productdetail?partno=DLM0NSB280HY2%23


DLM0NSB280HY2#

"#" indicates a package specification code.




INNOVATOR IN FLEC






Impedance-Frequency Characteristics (Main Items)



Impedance-Frequency Characteristics

Differential Mode Transmission Characteristics (Typical Value)



Equivalent Circuit

3 of 3

Attention

 This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

