



REDUCING JUMPER, TO CONNECT SPRING CONNECTIONS 35 MM<sup>2</sup> WITH SPRING TERMINALS 2.5 MM<sup>2</sup> OR 4 MM<sup>2</sup>, SIEMENS COLOR

Figure similar

Main circuit

Operating current / Rated value	A	40
---------------------------------	---	----

Mechanical Design

Mounting type		plug-in
Contact spacing	mm	35

Certificates

Design tested acc. to type of protection / EEx e		No
--	--	----

General Product Approval	Declaration of Conformity
--------------------------	---------------------------



Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/8WH90200EC10>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/8WH90200EC10/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=8WH90200EC10](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WH90200EC10)

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://ausschreibungstexte.siemens.com/tiplv>

last modified:

11.03.2015