### **Jalas**®



### JALAS® 3118W LIGHT GRIP

EN ISO 20345:2011, S3 SRB

#### **PROPERTIES**

Highest level of protection, excellent grip, perfect fit, extra comfortable, excellent shock absorption

#### **SPECIFICATION**

TYPE OF SHOE Safety footwear, low shoes

 $\label{eq:protection} \mbox{MATERIAL Plasma-treated composite} \\ \mbox{(PTC) textile} \\$ 

FITTING Regular

SIZE RANGE 34-35

PLATFORM Ergosport

UPPER MATERIAL Split leather, textile

TOECAP MATERIAL Steel

LINING MATERIAL Polyester, polyamide

SOLE MATERIAL Plastic shank, PU outsole

**INSOLE FX2 Pro** 

INSOLE MATERIAL Textile, soft EVA, polyester-based conductive thread, double shock absorption zones in Poron® XRD®

FASTENING Laces

COLOUR Black, grey, yellow

SIZE ARI. NO. EAN NO.

34 3118W-34 6408487434211 35 3118W-35 6408487434228

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.





### **Jalas**®



### **(**E



Steel toecap



Nail protection in plasma-treated composite (PTC) textile



Water repellent



Oil-resistant outsole



Ergothan Shock Absorption System



Anti-static properties



ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

# JALAS® 3118W LIGHT GRIP

#### **FEATURES**

Oil-resistant outsole, anti-static properties, polstered shaft edge, ventilating insole, water repellent, double shock absorption zones, conforms with IEC 61340-5-1 (ESD)

#### **PRIMARY PROTECTION**

Prevents risk of:, toe injuries, nail penetration, antistatic

#### **PRIMARY ENVIRONMENTS OF USE**

Outdoors, environments with risk for outsole penetration



#### **EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden Phone +46 (0) 247 360 00 Fax +46 (0) 247 360 10

info@ejendals.com order@ejendals.com

www.ejendals.com

### **Jalas**®



### CE



Steel toecap



Nail protection in plasma-treated composite (PTC) textile



Water repellent



Oil-resistant outsole



Ergothan Shock Absorption System



Anti-static properties



ESD

The product features remain unchanged only when insoles recommended by the manufacturer are used. All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

# JALAS® 3118W LIGHT GRIP

COMPLIANCE EN ISO 20345:2011

#### **COMPLIANCE DESCRIPTION**

SB: Footwear with toe protection tested with 200 J impact and 15kN compression force (includes oil resistant outsole)

S1: Footwear made from leather and other materials excluding all-rubber or all-polymeric footwear + closed seat region + SB + A + E

S2: S1 + WRU

S3: S2 + P

WRU: Water-resistant upper

A: Electrical resistance (between 0.1-1000 Mega Ohms

E: Energy absorption in the heel area (tested at 20 Joules)

SRB: Slip-resistance on steel floor with glycerol

IEC 61340-5-1: Electrostatic Discharge (ESD) resistance below 35 megaohm

BGR 191: Orthopedic footwear adjustment according to German BGR 191. Footwear is tested with adjusted orthopedic insoles in accordance with EN ISO 20345 standard



#### **EJENDALS AB**

Box 7, SE-793 21 Leksand, Sweden Phone +46 (0) 247 360 00 Fax +46 (0) 247 360 10

> info@ejendals.com order@ejendals.com

> > www.ejendals.com